



All Products

Item #	Description	MSRP
TNB-9000	43.3mm full-frame CMOS Image Sensor, Max.15fps@8K, 20fps@24MP, 30fps@15MP, 60fps@4K, Compatible with Canon EF mount Lens, Intelligent video analytics based on AI (Object detection/classification, Attribute, BestShot), HDMI (1080p 30fps) Video Output, H.265/H.264 : Main/High, MJPEG, Single Micro SD slot (Up to 256GB), WiseStream II support, RJ-45, SFP slot(100/1000Mbps), HPoE(IEEE802.3bt, Class5), 12VDC, AI based analytics	\$ 15,000.00
PNM-9322VQP	Network vandal outdoor camera that combines Multi-sensor Multi-Directional camera, (2MP/5MP X 4 sensors sold separately) 8MP ~20MP (2MP @ 60fps or 5MP @30fps) fixed focal lens modules and 2MP 32x optical zoom PTZ, triple codec H.265/H.264/MJPEG with WiseStream II technology, WDR 150dB @ 2MP or 120dB @ 5MP, defocus detection, built in analytics, 4x SD card, hallway view, HLC, defog detection, DIS(Gyro Sensor), Audio I/O (PTZ ch only), HPoE injector (included), IP66/IK10, -40°C ~ +55°C (-40°F ~ +131°F), White color, 2MP Lens modules: SLA-2M2400P (2.4mm), SLA-2M2800P (2.8mm), SLA-2M3600P (3.6mm), SLA-2M6000P (6mm), SLA-2M1200P (12mm) 5MP Lens modules: SLA-5M3700P (3.7mm), SLA-5M4600P (4.6mm), SLA-5M7000P (7.0mm)	\$ 6,200.00
PNM-9084QZ1	Wisenet P series network vandal outdoor Multi-sensor Multi-Directional dome camera, (2MP X 4 sensors) 8MP @ 60fps, motorized vari-focal lens 2x (3.0~6.0mm) (107°~56.3°), PTRZ (Pan/Tilt/Rotate/Zoom) remote adjustment, triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, defocus detection, built in analytics, true D/N, 4x SD card, hallway view, HLC, defog detection, Bi-Directional Audio, Alarm I/O 1/1, HPoE (injector included), IP66/IK10, -40°C ~ +55°C (-40°F ~ +131°F), White	\$ 2,200.00
PNM-9084QZ	Wisenet P series network vandal outdoor Multi-sensor Multi-Directional dome camera, (2MP X 4 sensors) 8MP @ 60fps, motorized vari-focal lens 2x (3.0~6.0mm) (107°~56.3°), PTRZ (Pan/Tilt/Rotate/Zoom) remote adjustment, triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, defocus detection, built in analytics, true D/N, 4x SD card, hallway view, HLC, defog detection, Bi-Directional Audio, Alarm I/O 1/1, HPoE (injector included), IP66/IK10, -40°C ~ +55°C (-40°F ~ +131°F), White	\$ 2,200.00
PNM-9084RQZ1	Wisenet P series network vandal outdoor Multi-sensor Multi-Directional dome camera, 2MP x 4ch multi-directional camera, Motorized PTRZ support, Max. 60fps@2MP(H.265, H.264), 3.2~10mm(3.1x) motorized varifocal lens, IR viewable length : 30m, H.265, H.264, MJPEG codec, Multi streaming, Video analytics, WiseStream II, IP66, IK10, NEMA4X	\$ 2,880.00
PNM-9084RQZ	2MP x 4ch multi-directional camera, Motorized PTRZ support, Max. 60fps@2MP(H.265, H.264), 3.2~10mm(3.1x) motorized varifocal lens, IR viewable length : 30m, H.265, H.264, MJPEG codec, Multi streaming, Video analytics, WiseStream II, IP66, IK10, NEMA4X	\$ 2,880.00
PNM-9085RQZ1	Wisenet P series network vandal outdoor Multi-sensor Multi-Directional dome camera, 5MP x 4ch multi-directional camera, Motorized PTRZ support, Max. 30fps@5MP(H.265, H.264), 4.13~9.4mm(2.3x) motorized varifocal lens, IR viewable length : 30m, H.265, H.264, MJPEG codec, Multi streaming, Video analytics, WiseStream II, IP66, IK10, NEMA4X	\$ 3,800.00
PNM-9085RQZ	5MP x 4ch multi-directional camera, Motorized PTRZ support, Max. 30fps@5MP(H.265, H.264), 4.13~9.4mm(2.3x) motorized varifocal lens, IR viewable length : 30m, H.265, H.264, MJPEG codec, Multi streaming, Video analytics, WiseStream II, IP66, IK10, NEMA4X	\$ 3,800.00
PNM-9000QB	WN7 multi head camera, 4 x 2MP @ 30fps, triple codec H.265/H.264/MJPEG, extreme WDR 150dB, dual SD cards slots, Wisestream II, hallway view, HLC, defog detection, audio In/out, HDMI out 12VDC/PoE+, DIS support, analytics- defocus, directional, motion, enter/exit, tampering, virtual line, I/O in/out. Compatible with SLA-T4680A/T4680VA, SLA-T2480A/T2480VA, SLA-T1080FA	\$ 660.00
PNM-9002VQ	Network vandal outdoor Multi-sensor Multi-Directional dome camera, (2MP/5MP X 4 sensors sold separately) 8MP ~20MP (2MP @ 60fps or 5MP @30fps), fixed focal lens modules, triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR @ 2MP or 120dB @ 5MP, defocus detection, built in analytics, PTZ handover, 4x SD card, hallway view, HLC, defog detection, DIS(Gyro Sensor), PoE+, IP66/IK10, -40°C ~ +55°C (-40°F ~ +131°F) 2MP Lens modules: SLA-2M2400Q (2.4mm), SLA-2M2800Q (2.8mm), SLA-2M3600Q (3.6mm), SLA-2M6000Q (6mm) 5MP Lens modules: SLA-5M3700Q (3.7mm), SLA-5M4600Q (4.6mm), SLA-5M7000Q (7.0mm). WHITE COLOR	\$ 1,700.00
PNM-9002VQS	Stainless steel outdoor multi-sensor dome camera, (2MP/5MP X 4 sensors sold separately) 8MP ~20MP (2MP @ 60fps or 5MP @30fps), fixed focal lens modules, triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR @ 2MP or 120dB @ 5MP, defocus detection, built in analytics, PTZ handover, 4x SD card, hallway view, HLC, defog detection, DIS(Gyro Sensor), PoE+, IP66/IP6K9K/IK10, -40°C ~ +55°C (-40°F ~ +131°F) 2MP Lens modules: SLA-2M2400Q (2.4mm), SLA-2M2800Q (2.8mm), SLA-2M3600Q (3.6mm), SLA-2M6000Q (6mm) 5MP Lens modules: SLA-5M3700Q (3.7mm), SLA-5M4600Q (4.6mm), SLA-5M7000Q (7.0mm)	\$ 4,700.00
PNM-9000VD	Network vandal outdoor Multi-sensor Multi-Directional dome camera, (5MP X 2 sensors sold separately) 10MP @ 30fps, modular lenses from 3.7, 4.6 and 7.0mm lenses, triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, built in analytics, 2x SD card, hallway view, HLC, defog detection, DIS, PoE, IP66/IK10, -40°C ~ +55°C (-40°F ~ +131°F). Lens modules: SLA-5M3700D (3.7mm), SLA-5M4600D (4.6mm), SLA-5M7000D (7.0mm)	\$ 1,100.00
PNM-8082VT	Powered by WN7, 2MP x 3CH @ 30FPS, multi directional camera, 3~6mm motorized varifocal lens, donut shape bubble, max 321° coverage, Triple codec H.264/265 MJPEG, WiseStream II, extreme WDR 150dB, defocus detection, video analytics, 2x microSD card, PoE+, IP66, IK10, NEMA4X, operating temp -40°C~+55°C	\$ 1,700.00
PNM-7002VD	Network vandal outdoor Multi-sensor Multi-Directional dome camera, (2MP X 2 sensors sold separately) 4MP @ 60fps, modular lenses from 2.4, 2.8, 3.6 and 6mm lenses, triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, built in analytics, 4x SD card, hallway view, HLC, defog detection, DIS, PoE, IP66/IK10, -40°C ~ +55°C (-40°F ~ +131°F). Lens modules: SLA-2M2402D (2.4mm), SLA-2M2802D (2.8mm), SLA-2M3602D (3.6mm), SLA-2M6002D (6mm). WHITE COLOR	\$ 1,100.00
PNM-9031RV	Network vandal outdoor Multi-sensor dome camera, panoramic view with stitched image, (5MP X 4 sensors) 15MP @ 20fps, triple codec H.265/H.264/MJPEG with WiseStream II technology, WDR 120dB, IR viewable length 20m (65.5'), built in video analytics and sound classification, Heatmap, Bi-directional audio support, Micro SD 2 slots, IP66/IK10/NEMA4X, TPM 2.0 (FIPS 140-2 level 2), PoE+/12VDC	\$ 2,700.00
PNM-9022V	WN7 Panoramic Multi-sensor camera, 180° view, (2MP X 4 sensors) 7.3MP @ 30fps, panoramic 209° view, 8.3MP, triple codec H.265/H.264/MJPEG with WiseStream II technology, extreme WDR 120dB, defocus detection, built in analytics, Heatmap, Micro USB for easy installation, 2 x Micro SD cards PoE+, IP66/IK10/NEMA4X	\$ 1,800.00
PND-A9081RF	4K Network AI IR Dome Camera, Max. 4K resolution, 0.05Lux@F1.6 (Color), 0Lux (B/W, IR LED on), Day & Night(ICR), WDR(120dB), H.265, H.264, MJPEG codec, WiseStream II, Video Analytics based on AI, Object detection and classification(Person, Face, Vehicle, License Plate), Attribute, BestShot, Compatible with Wisenet Retail Insight v2.0 for Business Intelligence, Age/gender based People counting, Heatmap, Queue management, Modular structure for easy installation, POE+, Face Mask Detection, Social Distancing Detection	\$ 1,950.00

PND-A9081RV	4K Network AI IR Dome Camera, Max. 4K resolution, 0.05Lux@F1.6 (Color), 0Lux (B/W, IR LED on), Day & Night(ICR), WDR(120dB), H.265, H.264, MJPEG codec, WiseStream II , Video Analytics based on AI, Object detection and classification(Person, Face, Vehicle, License Plate), Attribute, BestShot, Compatible with Wisenet Retail Insight v2.0 for Business Intelligence, Age/gender based People counting, Heatmap, Queue management, Modular structure for easy installation, PoE+, Face Mask Detection, Social Distancing Detection	\$	1,950.00
PNV-A9081R	4K Network AI IR Vandal Dome Camera, Max. 4K resolution, 0.05Lux@F1.6 (Color), 0Lux (B/W, IR LED on), Day & Night(ICR), WDR(120dB) H.265, H.264, MJPEG codec, WiseStream II , Video Analytics based on AI, Object detection and classification(Person, Face, Vehicle, License Plate), Attribute, BestShot, Compatible with Wisenet Retail Insight v2.0 for Business Intelligence, Age/gender based People counting, Heatmap, Queue management, Modular structure for easy installation, POE+, Face Mask Detection, Social Distancing Detection	\$	2,150.00
PNO-A9081R	4K Network AI IR Bullet Camera, Max. 4K resolution, 0.05Lux@F1.6 (Color), 0Lux (B/W, IR LED on), Day & Night(ICR), WDR(120dB), H.265, H.264, MJPEG codec, WiseStream II , Video Analytics based on AI, Object detection and classification(Person, Face, Vehicle, License Plate), Attribute, BestShot, Compatible with Wisenet Retail Insight v2.0 for Business Intelligence, Age/gender based People counting, Heatmap, Queue management, POE+, Face Mask Detection, Social Distancing Detection	\$	2,050.00
PNB-A9001	4K AI Network Box Camera, Max. 4K resolution, 0.03Lux@F1.2(Color), Day & Night(ICR), WDR(120dB), H.265, H.264, MJPEG codec, WiseStream II , Video Analytics based on AI, Object detection and classification(Person, Face, Vehicle, License Plate), Attribute, BestShot, Compatible with Wisenet Retail Insight v2.0 for Business Intelligence, Age/gender based People counting, Heatmap, Queue management, POE+, Face Mask Detection, Social Distancing Detection	\$	1,500.00
XNP-9300RW	Powered by WN7, 4K @ 30FPS resolution, 5mm~150mm (30x) lens, build in wiper and adaptive Wise IR (200m), extreme WDR 120dB, Day & Night ICR, H.265, H.264, MJPEG codec support, Intelligent Analytics, Object auto tracking (Person/Vehicle), Target lock track, BLC, HLC, SSDR, lens heater for water/snow removal, IP66, IK10(Camera body only), NEMA4X, HPoE injector included, (Compatible with I/O Box SPM-4210)	\$	4,900.00
XNP-9250R	Powered by WN7, 4K @ 30FPS resolution, 5mm~125mm (25x) lens, adaptive Wise IR (200m), extreme WDR 120dB, Day & Night ICR, H.265, H.264, MJPEG codec support, Intelligent Analytics, Object auto tracking (Person/Vehicle), Target lock track, BLC, HLC, SSDR, lens heater for water/snow removal, IP66, IK10(Camera body only), NEMA4X, NEMA-TS 2 (2.2.8, 2.2.9), HPoE injector included, (Compatible with I/O Box SPM-4210)	\$	4,550.00
XNP-9250	Powered by WN7, 4K @ 30FPS resolution, 5mm~125mm (25x) lens, extreme WDR 120dB, Day & Night ICR, H.265, H.264, MJPEG codec support, Intelligent Analytics, Object auto tracking (Person/Vehicle), Target lock track, BLC, HLC, SSDR, IP66, IK10, NEMA4X, NEMA-TS 2 (2.2.8, 2.2.9), Power: PoE+, (Compatible with I/O Box SPM-4210)	\$	4,300.00
XNO-C9083R	Powered by WN7, Outdoor Network AI IR Bullet Camera, 4K resolution @ 30FPS, 4.4~9.3mm(2.1x) (112.1°~47.5°) motorized varifocal lens, Triple codec (H.265/H.264/MJPEG), IR viewable length 40m (131.2ft), USB port for easy installation, Day & Night (ICR), extremeWDR (120dB), DIS with built-in Gyro sensor, Handover, Hard-coated window, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/Licence plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, UL CAP certified, P66, IP67, NEMA4X, IK10, Operating temperature: -40°C~-+55°C(-40°F ~ +131°F) Power: PoE/12VDC, Metal shielded RJ-45	\$	1,800.00
XNO-9083R	Powered by WN7, X-Plus series, Outdoor Network AI IR Bullet Camera, 4K resolution @ 30FPS, 4.4~9.3mm(2.1x) (112.1°~47.5°) motorized varifocal lens, Triple codec (H.265/H.264/MJPEG), IR viewable length 50m (164ft), USB port for easy installation, Day & Night (ICR), extremeWDR (120dB), DIS with built-in Gyro sensor, Handover, Hard-coated window, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, FIPS 140-2, 2x micro SD card (512GB x2), P66, IP67, NEMA4X, IK10, Operating temperature: -50°C~-+60°C(-58°F ~ +140°F), Power: PoE+/12VDC, Metal shielded RJ-45	\$	1,950.00
XNO-9082R	Wisenet 7 X series network IR bullet camera, 4K (8MP Max) @ 30fps, motorized vari-focal lens 3x (2.8~8.4mm), triple codec H.265/H.264/MJPEG with WiseStreamII technology, Extreme WDR, USB and CVBS port for easy installation, advanced video analytics, sound classification and business analytics, high powered IR LEDs range of 131.23', shock detection, audio playback, true D/N, dual SD cards slots, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/24VAC/PoE, IP67/IP66, IK10, Nema 4X, -50°C ~ +60°C (-58°F ~ +140°F)	\$	1,750.00
XND-C9083RV	Powered by WN7, Indoor Network AI IR Dome Camera, 4K resolution @ 30FPS, 4.4~9.3mm(2.1x) (112.1°~47.5°) motorized varifocal lens, Triple codec (H.265/H.264/MJPEG), IR viewable length 40m (131.2ft), USB port for easy installation, Day & Night (ICR), extremeWDR (120dB), DIS with built-in Gyro sensor, Handover, Hard-coated dome bubble, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, IP52, IK08, Operating temperature: -10 °C ~ 50 °C(14°F ~ +122°F), Power: PoE/12VDC, Metal shielded RJ-45	\$	1,600.00
XNV-C9083R	Powered by WN7, Outdoor Network AI IR Vandal Dome Camera, 4K resolution @ 30FPS, 4.4~9.3mm(2.1x) (112.1°~47.5°) motorized varifocal lens, Triple codec (H.265/H.264/MJPEG), IR viewable length 40m (131.2ft), USB port for easy installation, USB port for easy installation, Day & Night (ICR), extremeWDR (120dB), DIS with built-in Gyro sensor, Handover, Hard-coated dome bubble, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, P66, IP67, NEMA4X, IK10, Operating temperature: -40°C~-+55°C(-40°F ~ +131°F), Power: PoE/12VDC, Metal shielded RJ-45	\$	1,800.00
XNV-9082R	Wisenet 7 X-plus series network IR vandal outdoor camera, 4K (8MP Max) @ 30fps, motorized vari-focal lens 3x (2.8~8.4mm), triple codec H.265/H.264/MJPEG with WiseStreamII technology, Extreme WDR, USB and CVBS port for easy installation, advanced video analytics, sound classification and business analytics, high powered IR LEDs range of 131.23', shock detection, audio playback, true D/N, dual SD cards slots, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/24VAC/PoE, IP67/IP66/IP6K9K, IK10, Nema 4X, -50°C ~ +60°C (-58°F ~ +140°F)	\$	1,750.00
XND-9083RV	Powered by WN7, X-Plus series, Indoor Network AI IR Dome Camera, 4K resolution @ 30FPS, 4.4~9.3mm(2.1x) (112.1°~47.5°) motorized varifocal lens, Triple codec (H.265/H.264/MJPEG), IR viewable length 50m (164ft), USB port for easy installation, Day & Night (ICR), extremeWDR (120dB), DIS with built-in Gyro sensor, Handover, Hard-coated dome bubble, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, FIPS 140-2, 2x micro SD card (512GB x2), IP52, IK10, Operating temperature: -25 °C ~ 50 °C (-13°F ~ +122°F), Power: PoE+/12VDC, Metal shielded RJ-45	\$	1,750.00
XNV-9083R	Powered by WN7, X-Plus series, Outdoor Network AI IR Vandal Dome Camera, 4K resolution @ 30FPS, 4.4~9.3mm(2.1x) (112.1°~47.5°) motorized varifocal lens, Triple codec (H.265/H.264/MJPEG), IR viewable length 50m (164ft), USB port for easy installation, USB port for easy installation, Day & Night (ICR), extremeWDR (120dB), DIS with built-in Gyro sensor, Handover, Hard-coated dome bubble, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, FIPS 140-2, 2x micro SD card (512GB x2), P66, IP67, NEMA4X, IK10+, Operating temperature: -50°C~-+55°C(-58°F ~ +131°F), Power: PoE+/12VDC, Metal shielded RJ-45	\$	1,950.00
XND-9082RF	Wisenet 7 X-plus series network IR flush mount camera (plenum), 4K (8MP Max) @ 30fps, motorized vari-focal lens 3x (2.8~8.4mm), triple codec H.265/H.264/MJPEG with WiseStreamII technology, Extreme WDR, USB and CVBS port for easy installation, advanced video analytics, sound classification and business analytics, high powered IR LEDs range of 131.23', shock detection, audio playback, true D/N, dual SD cards slots, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/PoE, IP52, IK10, -25°C ~ +60°C (-13°F ~ +140°F)	\$	1,500.00

XND-9082RV	Wisenet 7 X-plus series network IR vandal indoor camera, 4K (8MP Max) @ 30fps, motorized vari-focal lens 3x (2.8~8.4mm), triple codec H.265/H.264/MJPEG with WiseStreamII technology, Extreme WDR, USB and CVBS port for easy installation, advanced video analytics, sound classification and business analytics, high powered IR LEDs range of 131.23', shock detection, audio playback, true D/N, dual SD cards slots, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/PoE, IP52, IK10, -25°C ~ +60°C (-13°F ~ +140°F)	\$	1,500.00
XNB-9003	Powered by WN7, X-Plus series, Box Camera, 8MP resolution @ 30FPS, Triple codec (H.265/H.264/MJPEG), USB port for easy installation, Day & Night (ICR), extremeWDR (120dB), DIS with built-in Gyro sensor, Handover, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, FIPS 140-2, 2x micro SD card (512GB x2), Operating temperature: -10 °C ~ 55 °C(14°F ~ +131°F), Power: PoE+/12VDC, Metal shielded RJ-45	\$	1,150.00
XNB-9002	Wisenet 7 X series network box camera, 4K (8MP Max) @ 30fps, triple codec H.265/H.264/MJPEG with WiseStreamII technology, Extreme WDR, USB and CVBS port for easy installation, advanced video analytics, sound classification and business analytics, shock detection, audio playback, true D/N, dual SD cards slots, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/24VAC/PoE, -10°C ~ +55°C (+14°F ~ +131°F)	\$	1,000.00
XNF-9010RS	Stainless steel Fisheye, powered by WN7, 1/2.3" 12MP CMOS, Max resolution 3008x3008 @ 30FPS, 1.08mm fixed focal lens, Stereo graphic type lens, enhanced resolution for the peripheral regions, H.265, H.264, MJPEG codec supported, Fisheye, Single panorama, Double panorama, Quad view, On board dewarping, Digital PTZ, extreme WDR (120dB), WiseStream II support, Wise IR, IR viewable length 26.2' (8m), Virtual channel support, selectable I/O port, Video Analytics, Heatmap, People counting, Queue management, Nylon dome, Handover, IP66/IP67/IP6K9K/IK10/NEMA4X, PoE, 12VDC	\$	2,150.00
XNF-9010RV	Powered by WN7, 1/2.3" 12MP CMOS, Max resolution 3008x3008 @ 30FPS, 1.08mm fixed focal lens, Stereo graphic type lens, enhanced resolution for the peripheral regions, H.265, H.264, MJPEG codec supported, Fisheye, Single panorama, Double panorama, Quad view, On board dewarping, Digital PTZ, extreme WDR (120dB), WiseStream II support, Wise IR, IR viewable length 32.8' (10m), Virtual channel support, Plugin support, selectable I/O port, Video Analytics, Heatmap, People counting, Queue management, Hard coated dome cover, Handover, IP66/IK10/NEMA4X, PoE, 12VDC	\$	1,200.00
XNF-9010RVM	Powered by WN7, 1/2.3" 12MP CMOS, Max resolution 3008x3008 @ 30FPS, 1.08mm fixed focal lens, Stereo graphic type lens, enhanced resolution for the peripheral regions, H.265, H.264, MJPEG codec supported, Fisheye, Single panorama, Double panorama, Quad view, On board dewarping, Digital PTZ, extreme WDR (120dB), WiseStream II support, Wise IR, IR viewable length 32.8' (10m), Virtual channel support, Plugin support, selectable I/O port, Video Analytics, Heatmap, People counting, Queue management, Hard coated dome cover, Handover, IP66/IK10/NEMA4X, EN50155 class T3, PoE, 12VDC, supports M12, Special order	\$	1,260.00
QNF-9010	Wisenet Q series network Indoor fisheye dome camera, 12MP CMOS sensor, max resolution 3008x3008 @ 30fps, triple codec H.265/H.264/MJPEG with WiseStream II technology, WDR 120dB, business analytics (heatmap and people counting), built-in SD card slot, PoE	\$	950.00
XNP-8300RW	Powered by WN7, 6MP @ 30FPS resolution, 5mm~150mm (30x) lens, Wise IR (200m), extreme WDR 120dB, Day & Night ICR, H.265, H.264, MJPEG codec support, Intelligent Analytics, Object auto tracking (Person/Vehicle), Target lock track, BLC, HLC, SSDR, lens heater for water/snow removal, IP66, IK10(Camera body only), NEMA4X, HPoE injector included, (Compatible with I/O Box SPM-4210)	\$	4,550.00
XNP-8250R	Powered by WN7, 6MP @ 30FPS resolution, 5mm~125mm (25x) lens, Wise IR (200m), extreme WDR 120dB, Day & Night ICR, H.265, H.264, MJPEG codec support, Intelligent Analytics, Object auto tracking (Person/Vehicle), Target lock track, BLC, HLC, SSDR, lens heater for water/snow removal, IP66, IK10(Camera body only), NEMA4X, HPoE injector included, NEMA-TS 2 (2.2.8, 2.2.9), (Compatible with I/O Box SPM-4210)	\$	4,250.00
XNP-8250	Powered by WN7, 6MP @ 30FPS resolution, 5mm~125mm (25x) lens, extreme WDR 120dB, Day & Night ICR, H.265, H.264, MJPEG codec support, Intelligent Analytics, Object auto tracking (Person/Vehicle), Target lock track, BLC, HLC, SSDR, IP66, IK10, NEMA4X, NEMA-TS 2 (2.2.8, 2.2.9), Power: PoE+, (Compatible with I/O Box SPM-4210)	\$	4,000.00
XNO-C8083R	Powered by WN7, Outdoor Network AI IR Bullet Camera, 6MP resolution @ 30FPS, 4.4~9.3mm(2.1x) (112.1°~47.5°) motorized varifocal lens, Triple codec (H.265/H.264/MJPEG), IR viewable length 40m (131.2ft), USB port for easy installation, Day & Night (ICR), extremeWDR (120dB), DIS with built-in Gyro sensor, Handover, Hard-coated window, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, UL CAP certified, P66, IP67, NEMA4X, IK10, Operating temperature: -40°C~+55°C(-40°F ~ +131°F), Power: PoE/12VDC, Metal shielded RJ-45	\$	1,550.00
XNO-8083R	Powered by WN7, X-Plus series, Outdoor Network AI IR Bullet Camera, 6MP resolution @ 30FPS, 4.4~9.3mm(2.1x) (112.1°~47.5°) motorized varifocal lens, Triple codec (H.265/H.264/MJPEG), IR viewable length 50m (164ft), USB port for easy installation, Day & Night (ICR), extremeWDR (120dB), DIS with built-in Gyro sensor, Handover, Hard-coated window, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, FIPS 140-2, 2x micro SD card (512GB x2), P66, IP67, NEMA4X, IK10, Operating temperature: -50°C~+60°C(-58°F ~ +140°F), Power: PoE+/12VDC, Metal shielded RJ-45	\$	1,750.00
XNO-8082R	Wisenet 7 X series network IR bullet camera, 6MP @ 30fps, motorized vari-focal lens 3x (2.8~8.4mm), triple codec H.265/H.264/MJPEG with WiseStreamII technology, Extreme WDR, USB and CVBS port for easy installation, advanced video analytics, sound classification and business analytics, high powered IR LEDs range of 131.23', shock detection, audio playback, true D/N, dual SD cards slots, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/24VAC/PoE, IP67/IP66, IK10, Nema 4X, -50°C ~ +60°C (-58°F ~ +140°F)	\$	1,550.00
XNV-C8083R	Powered by WN7, Outdoor Network AI IR Vandal Dome Camera, 6MP resolution @ 30FPS, 4.4~9.3mm(2.1x) (112.1°~47.5°) motorized varifocal lens, Triple codec (H.265/H.264/MJPEG), IR viewable length 40m (131.2ft), USB port for easy installation, Day & Night (ICR), extremeWDR (120dB), DIS with built-in Gyro sensor, Handover, Hard-coated dome bubble, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, P66, IP67, NEMA4X, IK10, Operating temperature: -40°C~+55°C(-40°F ~ +131°F), Power: PoE/12VDC, Metal shielded RJ-45	\$	1,550.00
XNV-8093R	Powered by WN7, X-Plus series, Outdoor Network AI IR Vandal Dome Camera, 6MP resolution @ 30FPS, 10.9~29mm(2.7x) (42°~15°) motorized varifocal lens, Triple codec (H.265/H.264/MJPEG), IR viewable length 70m (229.66ft), USB port for easy installation, Day & Night (ICR), extremeWDR (120dB), DIS with built-in Gyro sensor, Handover, Hard-coated dome bubble, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, FIPS 140-2, 2x micro SD card (512GB x2), P66, IP67, NEMA4X, IK10+, Operating temperature: -50°C~+55°C(-58°F ~ +131°F), Power: PoE+/12VDC, Metal shielded RJ-45	\$	2,000.00
XNV-8083R	Powered by WN7, X-Plus series, Outdoor Network AI IR Vandal Dome Camera, 6MP resolution @ 30FPS, 4.4~9.3mm(2.1x) (112.1°~47.5°) motorized varifocal lens, Triple codec (H.265/H.264/MJPEG), IR viewable length 50m (164ft), USB port for easy installation, Day & Night (ICR), extremeWDR (120dB), DIS with built-in Gyro sensor, Handover, Hard-coated dome bubble, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, FIPS 140-2, 2x micro SD card (512GB x2), P66, IP67, NEMA4X, IK10+, Operating temperature: -50°C~+55°C(-58°F ~ +131°F), Power: PoE+/12VDC, Metal shielded RJ-45	\$	1,750.00

XNV-8082R	Wisenet 7 X-plus series network IR vandal indoor camera, 6MP @ 30fps, motorized vari-focal lens 3x (2.8~8.4mm), triple codec H.265/H.264/MJPEG with WiseStreamII technology, Extreme WDR, USB and CVBS port for easy installation, advanced video analytics, sound classification and business analytics, high powered IR LEDs range of 131.23', shock detection, audio playback, true D/N, dual SD cards slots, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/24VAC/PoE, IP67/IP66/IP6K9K, IK10, Nema 4X, -50°C ~ +60°C (-58°F ~ +140°F)	\$	1,550.00
XND-C8083RV	Powered by WN7, Indoor Network AI IR Dome Camera, 6MP resolution @ 30FPS, 4.4~9.3mm(2.1x) (112.1°~47.5°) motorized varifocal lens, Triple codec (H.265/H.264/MJPEG), IR viewable length 40m (131.2ft), USB port for easy installation, Day & Night (ICR), extremeWDR (120dB), DIS with built-in Gyro sensor, Handover, Hard-coated dome bubble, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, IP52, IK08, Operating temperature: -10 °C ~ 50 °C(14°F ~ +122°F), Power: PoE/12VDC	\$	1,350.00
XND-8093RV	Powered by WN7, X-Plus series, Indoor Network AI IR Dome Camera, 6MP resolution @ 30FPS, 10.9~29mm(2.7x) (42°~15°) motorized varifocal lens, Triple codec (H.265/H.264/MJPEG), IR viewable length 70m (229.66ft), USB port for easy installation, Day & Night (ICR), extremeWDR (120dB), DIS with built-in Gyro sensor, Handover, Hard-coated dome bubble, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, FIPS 140-2, 2x micro SD card (512GB x2), IP52, IK10, Operating temperature: -25 °C ~ 50 °C(-13°F ~ +122°F), Power: PoE+/12VDC, Metal shielded RJ-45	\$	1,800.00
XND-8083RV	Powered by WN7, X-Plus series, Indoor Network AI IR Dome Camera, 6MP resolution @ 30FPS, 4.4~9.3mm(2.1x) (112.1°~47.5°) motorized varifocal lens, Triple codec (H.265/H.264/MJPEG), IR viewable length 50m (164ft), USB port for easy installation, Day & Night (ICR), extremeWDR (120dB), DIS with built-in Gyro sensor, Handover, Hard-coated dome bubble, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, FIPS 140-2, 2x micro SD card (512GB x2), IP52, IK10, Operating temperature: -25 °C ~ 50 °C(-13°F ~ +122°F), Power: PoE+/12VDC	\$	1,550.00
XND-8082RF	Wisenet 7 X-plus series network IR flush mount camera (plenum), 6MP @ 30fps, motorized vari-focal lens 3x (2.8~8.4mm), triple codec H.265/H.264/MJPEG with WiseStreamII technology, Extreme WDR, USB and CVBS port for easy installation, advanced video analytics, sound classification and business analytics, high powered IR LEDs range of 131.23', shock detection, audio playback, true D/N, dual SD cards slots, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/PoE, IP52, IK10, -25°C ~ +60°C (-13°F ~ +140°F)	\$	1,350.00
XND-8082RV	Wisenet 7 X-plus series network IR vandal indoor camera, 6MP @ 30fps, motorized vari-focal lens 3x (2.8~8.4mm), triple codec H.265/H.264/MJPEG with WiseStreamII technology, Extreme WDR, USB and CVBS port for easy installation, advanced video analytics, sound classification and business analytics, high powered IR LEDs range of 131.23', shock detection, audio playback, true D/N, dual SD cards slots, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/PoE, IP52, IK10, -25°C ~ +60°C (-13°F ~ +140°F)	\$	1,350.00
XNB-8003	Powered by WN7, X-Plus series, Box Camera, 6MP resolution @ 30FPS, Triple codec (H.265/H.264/MJPEG), USB port for easy installation, Day & Night (ICR), extremeWDR (120dB), DIS with built-in Gyro sensor, Handover, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, FIPS 140-2, 2x micro SD card (512GB x2), Operating temperature: -10 °C ~ 55 °C(14°F ~ +131°F), Power: PoE+/12VDC, Metal shielded RJ-45	\$	1,050.00
XNB-8002	Wisenet 7 X series network box camera, 6MP @ 30fps, triple codec H.265/H.264/MJPEG with WiseStreamII technology, Extreme WDR, USB and CVBS port for easy installation, advanced video analytics, sound classification and business analytics, shock detection, audio playback, true D/N, dual SD cards slots, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/24VAC/PoE, -10°C ~ +55°C (+14°F ~ +131°F)	\$	950.00

XND-8081REV	Wisenet X powered by Wisenet 5 network IR indoor dome camera with PoE Extender, PoE+ in PoE out, 5MP @30fps, Motorized Varifocal Lens (3.9mm ~9.4mm), triple codec H.265/H.264/MJPEG with WiseStream II technology,WDR 120dB, USB port for easy installation, advanced video analytics and sound classification, true D/N, dual SD card, hallway view, HLC, defog detection, DIS(Gyro), PoE/PoE+, IP52, IK10, -25°C ~ +60°C (-13°F ~ +140°F)	\$	1,600.00
XNV-8081RE	Wisenet X powered by Wisenet 5 network IR outdoor vandal dome camera with PoE Extender, PoE+ in PoE out, 5MP @30fps, Motorized Varifocal Lens (3.9mm ~9.4mm), triple codec H.265/H.264/MJPEG with WiseStream II technology,WDR 120dB, USB port for easy installation, advanced video analytics and sound classification, true D/N, dual SD card, hallway view, HLC, defog detection, DIS(Gyro), PoE/PoE+, IP66/IP67/IP6K9K, IK10+, NEMA4X, -50°C ~ +60°C (-58°F ~ +140°F)	\$	1,850.00
XNV-8081R	Wisenet X series Plus powered by Wisenet 5 IR network outdoor vandal dome camera, modular structure, 5MP @ 30fps, motorized vari-focal lens 2.6x (3.6~9.4mm) (102.5°~38.7°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video analytics, sound classification and business analytics, high powered IR LEDs range of 164', shock detection, audio playback, true D/N, dual SD card, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/PoE, optional 24VAC, IP67/IP66/IP6K9K, IK10+, Nema 4X, -50°C ~ +60°C (-58°F ~ +140°F), white color, ivory skin included, optional black skin cover	\$	1,800.00
XND-8081RF	Wisenet X series Plus powered by Wisenet 5 IR network indoor flush mount vandal dome camera, modular structure, 5MP @ 30fps, motorized vari-focal lens 2.6x (3.6~9.4mm) (102.5°~38.7°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video analytics, sound classification and business analytics, high powered IR LEDs range of 164', shock detection, audio playback, true D/N, dual SD card, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/PoE, IP52, plenum housing	\$	1,550.00
XND-8081RV	Wisenet X series Plus powered by Wisenet 5 IR network indoor vandal dome camera, modular structure, 5MP @ 30fps, motorized vari-focal lens 2.6x (3.6~9.4mm) (102.5°~38.7°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video analytics, sound classification and business analytics, high powered IR LEDs range of 164', shock detection, audio playback, built-in mic, true D/N, dual SD card, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/PoE, IP52, IK10, white color, ivory skin included, optional black skin cover	\$	1,550.00
XNV-8081Z	Wisenet X series Plus powered by Wisenet 5 network outdoor vandal dome camera, modular structure, 5MP @ 30fps, motorized vari-focal lens 2.6x (3.6~9.4mm) (102.5°~38.7°), PTRZ, triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video analytics, sound classification and business analytics, shock detection, audio playback, true D/N, dual SD card, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/PoE, optional 24VAC, IP67/IP66/IP6K9K, IK10+, Nema 4X, -50°C ~ +60°C (-58°F ~ +140°F), white color, ivory skin included, optional black skin cover	\$	1,850.00
XND-8081VZ	Wisenet X series Plus powered by Wisenet 5 network indoor vandal dome camera, modular structure, 5MP @ 30fps, motorized vari-focal lens 2.6x (3.6~9.4mm) (102.5°~38.7°), PTRZ, triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video analytics, sound classification and business analytics, shock detection, audio playback, built-in mic, true D/N, dual SD card, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/PoE, IP52, IK10, white color, ivory skin included, optional black skin cover	\$	1,600.00
XND-8081FZ	Wisenet X series Plus powered by Wisenet 5 network indoor flush mount vandal dome camera, modular structure, 5MP @ 30fps, motorized vari-focal lens 2.6x (3.6~9.4mm) (102.5°~38.7°), PTRZ, triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video analytics, sound classification and business analytics, shock detection, audio playback, true D/N, dual SD card, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/PoE, IP52, plenum housing	\$	1,600.00
XNF-8010R	Wisenet X powered by Wisenet 5 network indoor fisheye, 6MP CMOS sensor, 2048x2048 @ 30fps, 1.6mm fixed lens (192°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video, sound classification and business analytics, high powered IR LEDs range of 49', simple focus, dual SD card, HLC, defog detection, DIS, 12VDC/PoE	\$	950.00

XNF-8010RW	Wisenet X powered by Wisenet 5 network indoor fisheye (white color), 6MP CMOS sensor, 2048x2048 @ 30fps, 1.6mm fixed lens (192°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video, sound classification and business analytics, high powered IR LEDs range of 49', simple focus, dual SD card, HLC, defog detection, DIS, 12VDC/PoE, white color	\$	950.00
XNF-8010RV	Wisenet X powered by Wisenet 5 network outdoor vandal fisheye, 6MP CMOS sensor, 2048x2048 @ 30fps, 1.6mm fixed lens (192°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video, sound classification and business analytics, high powered IR LEDs range of 49', simple focus, dual SD card, HLC, defog detection, DIS, 12VDC/PoE, IP66, IK10, -40°C ~ +55°C (-40°F ~ +131°F)	\$	1,050.00
XNF-8010RVM	Wisenet X powered by Wisenet 5 network mobile vandal fisheye, 6MP CMOS sensor, 2048x2048 @ 30fps, 1.6mm fixed lens (192°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video, sound classification and business analytics, high powered IR LEDs range of 49', simple focus, dual SD card, HLC, defog detection, DIS, For Mobile Application (M12 Connector) RJ45 to M12 adapter is NOT included, 12VDC/PoE, IP66, IK10, -40°C ~ +55°C (-40°F ~ +131°F)	\$	1,150.00
XNV-8080RSA	Wisenet X powered by Wisenet 5 network IR stainless steel dome camera, 5MP @30fps, motorized vari-focal lens 2.4x (3.9~9.4mm) (92.1°~38.7°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video analytics and sound classification, high powered IR LEDs range of 164', true D/N, dual SD card, hallway view, HLC, defog detection, DIS, 12VDC/24VAC/PoE, IP67/IP6K9K/ IK10, Nema 4X, IP6K9K, □ -40°C ~ +55°C (-40°F ~ +131°F)	\$	2,200.00
XNV-8080R	Wisenet X powered by Wisenet 5 network IR outdoor vandal dome camera, 5MP @30fps, motorized vari-focal lens 2.4x (3.9~9.4mm) (92.1°~38.7°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video analytics and sound classification, high powered IR LEDs range of 164', true D/N, dual SD card, hallway view, HLC, defog detection, DIS, 12VDC/24VAC/PoE, IP67, IK10, Nema 4X, -40°C ~ +55°C (-40°F ~ +131°F)	\$	1,550.00
XNV-8020R	Wisenet X powered by Wisenet 5 network IR outdoor vandal dome camera, 5MP @30fps, 3.7mm fixed focal lens (97.5°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, high powered IR LEDs range of 98', true D/N, dual SD card, hallway view, HLC, defog detection, DIS, 12VDC/PoE, IP67, IK10	\$	900.00
XNV-8030R	Wisenet X powered by Wisenet 5 network IR outdoor vandal dome camera, 5MP @30fps, 4.6mm fixed focal lens (77.9°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, high powered IR LEDs range of 98', true D/N, dual SD card, hallway view, HLC, defog detection, DIS, 12VDC/PoE, IP67, IK10	\$	900.00
XNV-8040R	Wisenet X powered by Wisenet 5 network IR outdoor vandal dome camera, 5MP @30fps, 7mm fixed focal lens (50.7°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, high powered IR LEDs range of 98', true D/N, dual SD card, hallway view, HLC, defog detection, DIS, 12VDC/PoE, IP67, IK10	\$	900.00
XNO-8080R	Wisenet X powered by Wisenet 5 network IR outdoor bullet camera, 5MP @30fps, motorized vari-focal lens 2.4x (3.7~9.4mm) (100.2°~38.7°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video analytics and sound classification, high powered IR LEDs range of 164', true D/N, dual SD card, hallway view, HLC, defog detection, DIS, backbox included, 12VDC/24VAC/PoE, IP67, IK10, Nema 4X, -40°C ~ +55°C (-40°F ~ +131°F)	\$	1,550.00
XNO-8020R	Wisenet X powered by Wisenet 5 network outdoor vandal bullet camera, 5MP @30fps, 3.7mm fixed lens (97.5°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, high powered IR LEDs range of 98', true D/N, dual SD card, hallway view, HLC, defog detection, DIS, backbox included, 12VDC/PoE, IP67, IK10, Nema 4X	\$	900.00
XNO-8030R	Wisenet X powered by Wisenet 5 network outdoor vandal bullet camera, 5MP @30fps, 4.6mm fixed lens (77.9°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, high powered IR LEDs range of 98', true D/N, dual SD card, hallway view, HLC, defog detection, DIS, backbox included, 12VDC/PoE, IP67, IK10, Nema 4X	\$	900.00
XNO-8040R	Wisenet X powered by Wisenet 5 network outdoor vandal bullet camera, 5MP @30fps, 7mm fixed lens (50.7°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, high powered IR LEDs range of 98', true D/N, dual SD card, hallway view, HLC, defog detection, DIS, backbox included, 12VDC/PoE, IP67, IK10, Nema 4X	\$	900.00
XND-8080RV	Wisenet X powered by Wisenet 5 network IR indoor vandal dome camera, 5MP @30fps, motorized vari-focal lens 2.4x (3.9~9.4mm) (92.1°~38.7°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video analytics and sound classification, high powered IR LEDs range of 98', true D/N, dual SD card, hallway view, HLC, defog detection, DIS, 12VDC/PoE, IK08	\$	1,350.00
XND-8020R	Wisenet X powered by Wisenet 5 network IR indoor vandal dome camera, 5MP @30fps, 3.7mm fixed focal lens (97.5°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, high powered IR LEDs range of 98', true D/N, dual SD card, hallway view, HLC, defog detection, DIS, 12VDC/PoE, IK08	\$	775.00
XND-8030R	Wisenet X powered by Wisenet 5 network IR indoor vandal dome camera, 5MP @30fps, 4.6mm fixed focal lens (77.9°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, high powered IR LEDs range of 98', true D/N, dual SD card, hallway view, HLC, defog detection, DIS, 12VDC/PoE, IK08	\$	775.00
XND-8040R	Wisenet X powered by Wisenet 5 network IR indoor vandal dome camera, 5MP @30fps, 7mm fixed focal lens (50.7°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, high powered IR LEDs range of 98', true D/N, dual SD card, hallway view, HLC, defog detection, DIS, 12VDC/PoE, IK08	\$	775.00
XND-8020F	Wisenet X powered by Wisenet 5 network flush mount dome camera, 5MP @ 30fps, 3.7mm fixed lens (97.5°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, built-in Mic, magnetic cover, electronic D/N, SD card, hallway view, HLC, defog detection, DIS, PoE only	\$	600.00
XNB-8000	Wisenet X powered by Wisenet 5 network box camera, 5MP @30fps, simple focus, triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, true D/N, dual SD card, hallway view, HLC, defog detection, DIS using a Gyro sensor, 12VDC/24VAC/PoE	\$	950.00
QNO-8010R	Wisenet Q network outdoor vandal bullet camera, 5MP @ 30fps, 2.8mm fixed focal lens (104°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 65', defocus detection, hallway View, SD card, video analytics, CVBS, open platform, IP66, IK10, PoE	\$	470.00
QNO-8020R	Wisenet Q network outdoor vandal bullet camera, 5MP @ 30fps, 4.0mm fixed focal lens (79°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 82', defocus detection, hallway View, SD card, video analytics, CVBS, open platform, IP66, IK10, PoE	\$	470.00
QNO-8030R	Wisenet Q network outdoor vandal bullet camera, 5MP @ 30fps, 6.0mm fixed focal lens (49°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 98', defocus detection, hallway View, SD card, video analytics, CVBS, open platform, IP66, IK10, PoE	\$	470.00
QNO-8080R	Wisenet Q network outdoor vandal bullet camera, 5MP @ 30fps, motorized vari-focal lens 3.1x (3.2 ~ 10.0mm) (100°~31°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 98', defocus detection, hallway View, SD card, video analytics, CVBS, open platform, IP66, IK10, PoE	\$	680.00
QNV-8010R	Wisenet Q network outdoor vandal dome camera, 5MP @ 30fps, 2.8mm fixed focal lens (104°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 65', defocus detection, hallway View, SD card, video analytics, CVBS, open platform, IP66, IK10, PoE, white color	\$	470.00

QNV-8020R	Wisenet Q network outdoor vandal dome camera, 5MP @ 30fps, 4.0mm fixed focal lens (79°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 82', defocus detection, hallway View, SD card, video analytics, CVBS, open platform, IP66, IK10, PoE, white color	\$	470.00
QNV-8030R	Wisenet Q network outdoor vandal dome camera, 5MP @ 30fps, 6.0mm fixed focal lens (49°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 98', defocus detection, hallway View, SD card, video analytics, CVBS, open platform, IP66, IK10, PoE, white color	\$	470.00
QNV-8080R	Wisenet Q network outdoor vandal dome camera, 5MP @ 30fps, motorized vari-focal lens 3.1x (3.2 ~ 10.0mm) (100°~31°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 98', defocus detection, hallway View, SD card, video analytics, CVBS, open platform, IP66, IK10, PoE, white color	\$	680.00
QND-8010R	Wisenet Q network indoor dome camera, 5MP @ 30fps, 2.8mm fixed focal lens (104°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 65', defocus detection, hallway View, SD card, video analytics, CVBS, open platform, PoE, white color	\$	370.00
QND-8020R	Wisenet Q network indoor dome camera, 5MP @ 30fps, 4.0mm fixed focal lens (79°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 65', defocus detection, hallway View, SD card, video analytics, CVBS, open platform, PoE, white color	\$	370.00
QND-8030R	Wisenet Q network indoor dome camera, 5MP @ 30fps, 6.0mm fixed focal lens (49°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 65', defocus detection, hallway View, SD card, video analytics, CVBS, open platform, PoE, white color	\$	370.00
QND-8080R	Wisenet Q network indoor dome camera, 5MP @ 30fps, motorized vari-focal lens 3.1x (3.2 ~ 10.0mm) (100°~31°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 98', defocus detection, hallway View, SD card, video analytics, CVBS, open platform, PoE, white color	\$	615.00
QND-8011	Wisenet Q mini network indoor dome camera, 5MP @ 30fps, 2.8mm fixed focal lens (104°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, defocus detection, hallway View, SD card, people counting, open platform, IP42, IK08, PoE, white color	\$	370.00
QND-8021	Wisenet Q mini network indoor dome camera, 5MP @ 30fps, 4.0mm fixed focal lens (80°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, defocus detection, hallway View, SD card, people counting, open platform, IP42, IK08, PoE, white color	\$	370.00
QNE-8011R	Wisenet Q mini network outdoor flateye camera, 5MP @ 30fps, 2.8mm fixed focal lens (104°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 65', defocus detection, hallway View, SD card, video analytics, open platform, IP67, IK10, PoE, white color	\$	470.00
QNF-8010	Wisenet Q series network Indoor fisheye dome camera, 6MP CMOS sensor, max resolution 2048x2048 @ 30fps, triple codec H.265/H.264/MJPEG with WiseStream II technology, WDR 120dB, business analytics (heatmap and people counting), built-in SD card slot, PoE	\$	675.00
TNV-8011C	Compact corner mount camera, 5MP @ 30fps, triple codec, WDR 120dB, 2.3mm fixed, USB and CVBS, true D/N, SD cards slots, hallway view, HLC, defog detection, PoE, Audio-in/Audio-out, Wisenet open platform IP66, IP6K9K, IK10, video analytics- Defocus, Directional, Motion, Enter/Exit, Tampering, Virtual line, Audio	\$	850.00

QND-7012R	Wisenet Q network indoor dome camera, 4MP @30fps, 2.8mm fixed focal lens (107°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 65', motion detection, tampering, defocus detection, hallway View, one way audio and SD card (max. 128GB). PoE/12VDC, white color	\$	339.00
QND-7022R	Wisenet Q network indoor dome camera, 4MP @30fps, 4mm fixed focal lens (78°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 65', motion detection, tampering, defocus detection, hallway View, one way audio and SD card (max. 128GB). PoE/12VDC, white color	\$	339.00
QND-7032R	Wisenet Q network indoor dome camera, 4MP @30fps, 6mm fixed focal lens (49°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 65', motion detection, tampering, defocus detection, hallway View, one way audio and SD card (max. 128GB). PoE/12VDC, white color	\$	339.00
QND-7082R	Wisenet Q network indoor dome camera, 4MP @30fps, motorized vari-focal lens 3.1x (3.2 ~ 10.0mm) (109°~33.2°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 20m (65.62'), Motion detection, Tampering, Defocus detection, Hallway view, LDC support, Built-in mic (One way audio), Micro SD/SDHC/SDXC card 1 slot (Max. 128GB), PoE/12VDC (White color)	\$	559.00
QNV-7012R	Wisenet Q network outdoor vandal dome camera, 4MP @30fps, 2.8mm fixed focal lens (107°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 65', motion detection, tampering, defocus detection, hallway View, one way audio and SD card (max. 128GB). IP66, IK10, PoE/12VDC, white color	\$	429.00
QNV-7022R	Wisenet Q network outdoor vandal dome camera, 4MP @30fps, 4mm fixed focal lens (78°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 82', motion detection, tampering, defocus detection, hallway View, one way audio and SD card (max. 128GB). IP66, IK10, PoE/12VDC, white color	\$	429.00
QNV-7032R	Wisenet Q network outdoor vandal dome camera, 4MP @30fps, 6mm fixed focal lens (49°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 98', motion detection, tampering, defocus detection, hallway View, one way audio and SD card (max. 128GB). IP66, IK10, PoE/12VDC, white color	\$	429.00
QNV-7082R	Wisenet Q network outdoor vandal dome camera, 4MP @30fps, motorized vari-focal lens 3.1x (3.2 ~ 10.0mm) (109°~33.2°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 30m (98.42'), Motion detection, Tampering, Defocus detection, Hallway view, LDC support, One way audio - Line in, Micro SD/SDHC/SDXC card 1 slot (Max. 128GB). IP66, IK10, PoE/12VDC (White color)	\$	619.00
QNO-7012R	Wisenet Q network outdoor vandal bullet camera, 4MP @30fps, 2.8mm fixed focal lens (107°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 65', motion detection, tampering, defocus detection, hallway View, one way audio and SD card (max. 128GB). IP66, IK10, PoE/12VDC	\$	429.00
QNO-7022R	Wisenet Q network outdoor vandal bullet camera, 4MP @30fps, 4mm fixed focal lens (78°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 82', motion detection, tampering, defocus detection, hallway View, one way audio and SD card (max. 128GB). IP66, IK10, PoE/12VDC	\$	429.00
QNO-7032R	Wisenet Q network outdoor vandal bullet camera, 4MP @30fps, 6mm fixed focal lens (49°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 98', motion detection, tampering, defocus detection, hallway View, one way audio and SD card (max. 128GB). IP66, IK10, PoE/12VDC	\$	429.00
QNO-7082R	Wisenet Q network outdoor vandal bullet camera, 4MP @30fps, motorized vari-focal lens 3.1x (3.2 ~ 10.0mm) (109°~33.2°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 30m (98.42'), Motion detection, Tampering, Defocus detection, Hallway view, LDC support, One way audio - Line in, Micro SD/SDHC/SDXC card 1 slot (Max. 128GB). IP66, IK10, PoE/12VDC	\$	619.00
XND-C7083RV	Powered by WN7, Indoor Network AI IR Dome Camera, 4MP resolution @ 60FPS (WDR off)/30FPS (WDR on), 2.8~10mm(3.6x) (109.7°~30.4°) motorized varifocal lens, Triple codec (H.265/H.264/MJPEG), IR viewable length 40m (131.2ft), USB port for easy installation, Day & Night (ICR), extremeWDR (120dB), DIS with built-in Gyro sensor, Handover, Hard-coated dome bubble, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/Licence plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, IP52, IK08, Operating temperature: -10 °C ~ 50 °C(14°F ~ +122°F), Power: PoE/12VDC, Metal shielded RJ-45	\$	1,300.00
XNO-C7083R	Powered by WN7, Outdoor Network AI IR Bullet Camera, 4MP resolution @ 60FPS (WDR off)/30FPS (WDR on), 2.8~10mm(3.6x) (109.7°~30.4°) motorized varifocal lens, Triple codec (H.265/H.264/MJPEG), IR viewable length 40m (131.2ft), USB port for easy installation, Day & Night (ICR), extremeWDR (120dB), DIS with built-in Gyro sensor, Handover, Hard-coated window, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/Licence plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, UL CAP certified, P66, IP67, NEMA4X, IK10, Operating temperature 40°C~+55°C(-40°F ~ +131°F), Power: PoE/12VDC, Metal shielded RJ-45	\$	1,400.00

XNV-C7083R	Powered by WN7, Outdoor Network AI IR Vandal Dome Camera, 4MP resolution @ 60FPS (WDR off)/30FPS (WDR on), 2.8~10mm(3.6x) (109.7°~30.4°) motorized varifocal lens, Triple codec (H.265/H.264/MJPEG), IR viewable length 40m (131.2ft), USB port for easy installation, Day & Night (ICR), extremeWDR (120dB), DIS with built-in Gyro sensor, Handover, Hard-coated dome bubble, Analytics events based on AI engine : Object detection(Person/Face/Vehicle/Licence plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, P66, IP67, NEMA4X, IK10, Operating temperature: -40°C~+55°C(-40°F ~ +131°F), Power: PoE/12VDC, Metal shielded RJ-45	\$	1,400.00
TNV-7011RC	Wisenet T powered by Wisenet 5 network outdoor IR corner mount camera, 3MP, 2048*1536 @ 30fps, 2.8mm fixed lens (102°*75°), 940nm IR 32', built-in mic, triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, advanced video analytics and business analytics, single SD card, HLC, defog detection, DIS, PoE, IP66,Nema 4X, IK10	\$	1,500.00
PND-A6081RF	2MP Network AI IR Dome Camera, Max. 2MP resolution, Up to 120fps, 0.007Lux@F1.3 (Color), 0Lux (B/W, IR LED on), IR Viewable Length 40m(131.23ft), Wise IR, Day & Night (ICR), WDR (120dB), WiseNR II (Using AI engine), H.265, H.264, MJPEG, WiseStream II, WiseStream III (Using AI engine), Video Analytics based on AI [Object detection and classification (Person, Face, Vehicle, License Plate), Face mask detection, Social distancing detection, Attribute, BestShot] People counting, Heatmap, Queue management based on AI, TPM with FIPS 140-2 level2, Secure boot, Verify firmware forgery, Hard-coated dome bubble, IP52, IK10, Plenum rate, Modular structure for easy Install, PoE+	\$	1,470.00
PND-A6081RV	2MP Network AI IR Dome Camera, Max. 2MP resolution, Up to 120fps, 0.007Lux@F1.3 (Color), 0Lux (B/W, IR LED on), IR Viewable Length 40m(131.23ft), Wise IR, Day & Night (ICR), WDR (120dB), WiseNR II (Using AI engine), H.265, H.264, MJPEG, WiseStream II, WiseStream III (Using AI engine), Video Analytics based on AI [Object detection and classification (Person, Face, Vehicle, License Plate), Face mask detection, Social distancing detection, Attribute, BestShot] People counting, Heatmap, Queue management based on AI, TPM with FIPS 140-2 level2, Secure boot, Verify firmware forgery, Hard-coated dome bubble, IP52, IK10, Modular structure for easy Install, PoE+	\$	1,470.00
PNV-A6081R	2MP Network AI IR Vandal Dome Camera, Max. 2MP resolution, Up to 120fps, 0.007Lux@F1.3 (Color), 0Lux (B/W, IR LED on), IR Viewable Length 40m(131.23ft), Wise IR, Day & Night (ICR), WDR (120dB), WiseNR II (Using AI engine), H.265, H.264, MJPEG, WiseStream II, WiseStream III (Using AI engine), Video Analytics based on AI [Object detection and classification (Person, Face, Vehicle, License Plate), Face mask detection, Social distancing detection, Attribute, BestShot] People counting, Heatmap, Queue management based on AI, TPM with FIPS 140-2 level2, Secure boot, Verify firmware forgery, Hard-coated dome bubble/IP66, IP67, IP6K9K, IK10+, NEMA4X, Modular structure for easy Install, PoE+	\$	1,670.00
PNO-A6081R	2MP Network AI IR Bullet Camera, Max. 2MP resolution, Up to 120fps, 0.007Lux@F1.3 (Color), 0Lux (B/W, IR LED on), IR Viewable Length 40m(131.23ft), Wise IR, Day & Night (ICR), WDR (120dB), WiseNR II (Using AI engine), H.265, H.264, MJPEG, WiseStream II, WiseStream III (Using AI engine), Video Analytics based on AI [Object detection and classification (Person, Face, Vehicle, License Plate), Face mask detection, Social distancing detection, Attribute, BestShot] People counting, Heatmap, Queue management based on AI, TPM with FIPS 140-2 level2, Secure boot, Verify firmware forgery, IP66, IP67, IK10, NEMA4X, PoE+	\$	1,570.00
PNB-A6001	2MP Network AI Box Camera, Max. 2MP resolution, Up to 120fps, 0.006Lux@F1.2, (Color), 0.0006Lux@F1.2, 1/30sec. (B/W), Day & Night (ICR), WDR (120dB), WiseNR II (Using AI engine), H.265, H.264, MJPEG, WiseStream II, WiseStream III (Using AI engine), Video Analytics based on AI [Object detection and classification (Person, Face, Vehicle, License Plate), Face mask detection, Social distancing detection, Attribute, BestShot] People counting, Heatmap, Queue management based on AI, TPM with FIPS 140-2 level2, Secure boot, Verify firmware forgery, PoE+	\$	1,120.00
XND-C6083RV	Powered by WN7, Indoor Network AI IR Dome Camera, 2MP resolution @ 60FPS, 2.8~12mm(4.3x) (119.5°~27.9°) motorized varifocal lens, Triple codec (H.265/H.264/MJPEG), IR viewable length 40m (131.2ft), USB port for easy installation, Day & Night (ICR), extremeWDR (150dB), DIS with built-in Gyro sensor, Handover, Hard-coated dome bubble, Analytics events based on AI engine : Object detection(Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, IP52, IK08, Operating temperature: -10 °C ~ 50 °C(14°F ~ +122°F), Power: PoE/12VDC, Metal shielded RJ-45	\$	1,050.00
XNV-C6083R	Powered by WN7, Outdoor Network AI IR Vandal Dome Camera, 2MP resolution @ 60FPS, 2.8~12mm(4.3x) (119.5°~27.9°) motorized varifocal lens, Triple codec (H.265/H.264/MJPEG), IR viewable length 40m (131.2ft), USB port for easy installation, Day & Night (ICR), extremeWDR (150dB), DIS with built-in Gyro sensor, Handover, Hard-coated dome bubble, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, P66, IP67, NEMA4X, IK10, Operating temperature: -40°C~+55°C(-40°F ~ +131°F), Power: PoE/12VDC, Metal shielded RJ-45	\$	1,200.00
XND-6083RV	Powered by WN7, X-Plus series, Indoor Network AI IR Dome Camera, 2MP resolution @ 120FPS, 2.8~12mm(4.3x) (119.5°~27.9°) motorized varifocal lens, Triple codec (H.265/H.264/MJPEG), IR viewable length 50m (164ft), USB port for easy installation, Day & Night (ICR), extremeWDR (150dB), DIS with built-in Gyro sensor, Handover, Hard-coated dome bubble, Analytics events based on AI engine : Object detection(Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, FIPS 140-2, 2x micro SD card (512GB x2), IP52, IK10, Operating temperature: -25 °C ~ 50 °C(-13°F ~ +122°F), Power: PoE+/12VDC, Metal shielded RJ-45	\$	1,200.00
XNV-6083R	Powered by WN7, X-Plus series, Outdoor Network AI IR Vandal Dome Camera, 2MP resolution @ 120FPS, 2.8~12mm(4.3x) (119.5°~27.9°) motorized varifocal lens, Triple codec (H.265/H.264/MJPEG), IR viewable length 50m (164ft), USB port for easy installation, Day & Night (ICR), extremeWDR (150dB), DIS with built-in Gyro sensor, Handover, Hard-coated dome bubble, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, FIPS 140-2, 2x micro SD card (512GB x2), P66, IP67, NEMA4X, IK10+, Operating temperature: -50°C~+55°C(-58°F ~ +131°F), Power: PoE+/12VDC, Metal shielded RJ-45	\$	1,400.00
XNB-6003	Powered by WN7, X-Plus series, Box Camera, 2MP resolution @ 120FPS, Triple codec (H.265/H.264/MJPEG), USB port for easy installation, Day & Night (ICR), extremeWDR (150dB), DIS with built-in Gyro sensor, Handover, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, FIPS 140-2, 2x micro SD card (512GB x2), Operating temperature: -10 °C ~ 55 °C(14°F ~ +131°F), Power: PoE+/12VDC, Metal shielded RJ-45	\$	900.00
XNP-6400RW	Powered by WN7, 2MP @ 60FPS resolution, 4.25mm~170mm (40x) lens, build in wiper and Wise IR (200m), extreme WDR 150dB, Day & Night ICR, H.265, H.264, MJPEG codec support, Intelligent Analytics, Object auto tracking(Person/Vehicle), Target lock track, BLC, HLC, SSDR, lens heater for water/snow removal, IP66, IK10(Camera body only), NEMA4X, HPoE injector included, (Compatible with I/O Box SPM-4210)	\$	3,900.00
XNP-6400R	Powered by WN7, 2MP @ 60FPS resolution, 4.25mm~170mm (40x) lens, Wise IR (200m), extreme WDR 150dB, Day & Night ICR, H.265, H.264, MJPEG codec support, Intelligent Analytics, Object auto tracking(Person/Vehicle), Target lock track, BLC, HLC, SSDR, lens heater for water/snow removal, IP66, IK10(Camera body only), NEMA4X, NEMA-TS 2 (2.2.8, 2.2.9), HPoE injector included, (Compatible with I/O Box SPM-4210)	\$	3,600.00
XNP-6400	Powered by WN7, 2MP @ 60FPS resolution, 4.25mm~170mm (40x) lens, extreme WDR 150dB, Day & Night ICR, H.265, H.264, MJPEG codec support, Intelligent Analytics, Object auto tracking (Person/Vehicle), Target lock track, BLC, HLC, SSDR, lens heater for water/snow removal, IP66, IK10, NEMA4X, NEMA-TS 2 (2.2.8, 2.2.9), Power: PoE+, (Compatible with I/O Box SPM-4210)	\$	3,350.00

XND-6081REV	Wisenet X powered by Wisenet 5 network IR indoor dome camera with PoE Extender, PoE+ in PoE out, 2MP @60fps, Motorized Varifocal Lens (2.8mm ~12mm), triple codec H.265/H.264/MJPEG with WiseStream II technology, WDR 150dB, USB port for easy installation, advanced video analytics and sound classification, true D/N, dual SD card, hallway view, HLC, defog detection, DIS(Gyro), PoE/PoE+, IP52, IK10, -25°C ~ +60°C (-13°F ~ +140°F)	\$	1,250.00
XNV-6081RE	Wisenet X powered by Wisenet 5 network IR outdoor vandal dome camera with PoE Extender, PoE+ in PoE out, 2MP @60fps, Motorized Varifocal Lens (2.8mm ~12mm), triple codec H.265/H.264/MJPEG with WiseStream II technology, WDR 150dB, USB port for easy installation, advanced video analytics and sound classification, true D/N, dual SD card, hallway view, HLC, defog detection, DIS(Gyro), PoE/PoE+, IP66/IP67/IP6K9K, IK10+, NEMA4X, -50°C ~ +60°C (-58°F ~ +140°F)	\$	1,350.00
XNV-6081R	Wisenet X series Plus powered by Wisenet 5 IR network outdoor vandal dome camera, modular structure, 2MP, Full HD(1080p) @ 60fps, motorized vari-focal lens 4.3x (2.8~12mm) (119.5°~27.9°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics, sound classification and business analytics, high powered IR LEDs range of 164', shock detection, audio playback, true D/N, dual SD card, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/PoE, optional 24VAC, IP67/IP66/IP6K9K, IK10+, Nema 4X, -50°C ~ +60°C (-58°F ~ +140°F), white color, ivory skin included, optional black skin cover	\$	1,300.00
XND-6081RF	Wisenet X series Plus powered by Wisenet 5 IR network indoor flush mount vandal dome camera, modular structure, 2MP, Full HD(1080p) @ 60fps, motorized vari-focal lens 4.3x (2.8~12mm) (119.5°~27.9°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics, sound classification and business analytics, high powered IR LEDs range of 164', shock detection, audio playback, true D/N, dual SD card, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/PoE, IP52, plenum housing	\$	1,200.00
XND-6081RV	Wisenet X series Plus powered by Wisenet 5 IR network indoor vandal dome camera, modular structure, 2MP, Full HD(1080p) @ 60fps, motorized vari-focal lens 4.3x (2.8~12mm) (119.5°~27.9°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics, sound classification and business analytics, high powered IR LEDs range of 164', shock detection, audio playback, built-in mic, true D/N, dual SD card, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/PoE, IP52, IK10, white color, ivory skin included, optional black skin cover	\$	1,200.00
XNV-6081	Wisenet X series Plus powered by Wisenet 5 network outdoor vandal dome camera, modular structure, 2MP, Full HD(1080p) @ 60fps, motorized vari-focal lens 4.3x (2.8~12mm) (119.5°~27.9°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics, sound classification and business analytics, shock detection, audio playback, true D/N, dual SD card, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/PoE, optional 24VAC, IP67/IP66/IP6K9K, IK10+, Nema 4X, -50°C ~ +60°C (-58°F ~ +140°F), white color, ivory skin included, optional black skin cover	\$	1,200.00
XND-6081V	Wisenet X series Plus powered by Wisenet 5 network indoor vandal dome camera, modular structure, 2MP, Full HD(1080p) @ 60fps, motorized vari-focal lens 4.3x (2.8~12mm) (119.5°~27.9°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics, sound classification and business analytics, shock detection, audio playback, built-in mic, true D/N, dual SD card, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/PoE, IP52, IK10, white color, ivory skin included, optional black skin cover	\$	1,100.00
XNV-6081Z	Wisenet X series Plus powered by Wisenet 5 network outdoor vandal dome camera, modular structure, 2MP, Full HD(1080p) @ 60fps, motorized vari-focal lens 4.3x (2.8~12mm) (119.5°~27.9°), PTRZ, triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics, sound classification and business analytics, shock detection, audio playback, true D/N, dual SD card, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/PoE, optional 24VAC, IP67/IP66/IP6K9K, IK10+, Nema 4X, -50°C ~ +60°C (-58°F ~ +140°F), white color, ivory skin included, optional black skin cover	\$	1,350.00
XND-6081VZ	Wisenet X series Plus powered by Wisenet 5 network indoor vandal dome camera, modular structure, 2MP, Full HD(1080p) @ 60fps, motorized vari-focal lens 4.3x (2.8~12mm) (119.5°~27.9°), PTRZ, triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics, sound classification and business analytics, shock detection, audio playback, built-in mic, true D/N, dual SD card, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/PoE, IP52, IK10, white color, ivory skin included, optional black skin cover	\$	1,250.00
XND-6081FZ	Wisenet X series Plus powered by Wisenet 5 network indoor flush mount vandal dome camera, modular structure, 2MP, Full HD(1080p) @ 60fps, motorized vari-focal lens 4.3x (2.8~12mm) (119.5°~27.9°), PTRZ, triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics, sound classification and business analytics, shock detection, audio playback, true D/N, dual SD card, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/PoE, IP52, plenum housing	\$	1,250.00
XNP-6550RH	Wisenet X powered by Wisenet 5 network outdoor PTZ camera, 2MP, Full HD(1080p) @ 60fps, 55X optical zoom lens (4.75mm ~ 261.4mm) (58.8° ~ 1.23°), Pan: 360° endless. Tilt: -5°~ 185°, triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, built-in IR 1640ft (500m), USB port for easy installation, advanced video analytics and sound classification, true D/N, dual SD card, HLC, defog (optical) DIS(Gyro), 24VAC/HPoE, IP66/IK10, -58°F ~ +131°F W/ 24VAC power supply	\$	5,000.00
XNP-6320RH	Wisenet X powered by Wisenet 5 network IR PTZ camera, IR range for up to 656', 2MP, Full HD(1080p) @60fps, triple codec H.265/H.264/MJPEG, 32x optical zoom lens (4.44mm ~142.6mm) (61.8° ~ 2.19°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, advanced video analytics and sound classification, auto tracking, true D/N, dual SD card, HLC, defog detection, DIS(Gyro), IP66/IK10, 24VAC/HPoE	\$	4,500.00
XNP-6320H	Wisenet X powered by Wisenet 5 network outdoor PTZ camera, 2MP, Full HD(1080p) @ 60fps, 32X optical zoom lens (4.44mm ~142.6mm) (61.8° ~ 2.19°), Pan: 360° endless. Tilt: -15°~ 195°, triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, Auto Tracking, true D/N, dual SD card, HLC, defog detection, DIS(Gyro), 24VAC/PoE+, IP66/IK10, -58°F ~ +131°F W/ 24VAC power supply	\$	4,350.00
XNP-6320	Wisenet X powered by Wisenet 5 network indoor PTZ camera, 2MP, Full HD(1080p) @ 60fps, 32X optical zoom lens (4.44mm ~142.6mm) (61.8° ~ 2.19°), Pan: 360° endless. Tilt: -15°~ 195°, triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, Auto Tracking, true D/N, dual SD card, HLC, defog detection, DIS(Gyro), 24VAC/PoE+	\$	4,000.00
XNP-6321H	Wisenet X powered by Wisenet 5 network outdoor PTZ camera, 2MP, Full HD(1080p) @ 60fps, 32X optical zoom lens (4.44mm ~142.6mm) (61.8° ~ 2.19°), Pan: 360° endless. Tilt: -15°~ 195°, triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, true D/N, dual SD card, HLC, defog detection, DIS(Gyro), 24VAC/PoE+, IP66/IK10, -58°F ~ +131°F W/ 24VAC power supply	\$	3,300.00
XNP-6120H	Wisenet X powered by Wisenet 5 network outdoor PTZ camera, 2MP, Full HD(1080p) @ 60fps, 12X optical zoom lens (5.2mm ~62.4mm) (54.58° ~ 5.30°), Pan: 360° endless. Tilt: -5°~ 185°, triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, true D/N, dual SD card, HLC, defog detection, DIS(Gyro), 12VDC/PoE, IP66, IK10, -22°F ~ 131°F	\$	1,700.00
XNP-6040H	Wisenet X powered by Wisenet 5 network outdoor PTZ camera, 2MP, Full HD(1080p) @ 60fps, 4.3X optical zoom lens (2.8mm ~12mm) (119.5° ~ 27.9°), Pan: 0°~350°. Tilt: 0°~ 90°, triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, true D/N, dual SD card, HLC, defog detection, DIS(Gyro), 12VDC/PoE, IP66, IK10, -22°F ~ 131°F	\$	1,200.00
XNO-6085R	Wisenet X powered by Wisenet 5 network IR outdoor vandal bullet camera, eXtraLUX features 1/2" sensor with F0.94 Lens, back box, 2MP, Full HD(1080p) @60fps, motorized vari-focal lens 4.0x (4.1~16.4mm) (100°~26.2.9°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, high powered IR LEDs range of 229', true D/N, dual SD card, hallway view, HLC, defog detection, DIS (Gyro), backbox included, 12VDC/24VAC/PoE, IP67, IK10, Nema 4X, -40°C ~ +55°C (-40°F ~ +131°F)	\$	1,350.00

XNV-6085	Wisenet X powered by Wisenet 5 network outdoor vandal dome camera, eXtraLUX features 1/2" sensor with F0.94 Lens, PTRZ, 2MP, Full HD(1080p) @60fps, motorized vari-focal lens 4.0x (4.1~16.4mm) (100°~26.2.9°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, true D/N, dual SD card, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/24VAC/PoE, IP67, IK10, Nema 4X, -40°C ~ +55°C (-40°F ~ +131°F)	\$	1,400.00
XNV-6123R	Powered by WN7, Outdoor Network AI IR 12x Zoom Vandal Dome Camera, 2MP @ 120 FPS, 5.2~62.4mm(12x) (54.58°~5.30°) zoom lens, Triple codec (H.265/H.264/MJPEG), IR viewable length 90m (295.28ft), USB port for easy installation, Day & Night (ICR), extremeWDR (150dB), DIS with built-in Gyro sensor, Handover, Hard-coated dome bubble, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/Licence plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, FIPS 140-2 certified, P66, IP67, NEMA4X, IK10, Power: PoE/12VDC, Metal shielded RJ-45	\$	1,600.00
XNV-6120R	Wisenet X powered by Wisenet 5 network IR outdoor vandal dome camera, 2MP, Full HD(1080p) @60fps, 12X optical zoom lens (5.2mm ~62.4mm) (54.58° ~ 5.30°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, high powered IR LEDs range of 229', true D/N, dual SD card, hallway view, HLC, defog detection, DIS(Gyro), 12VDC/24VAC/PoE, IP67, IK10, Nema 4X, -40°C ~ +55°C (-40°F ~ +131°F)	\$	1,500.00
XNV-6120R/LPR	Wisenet X powered by Wisenet 5 network IR outdoor Low Speed LPR dome camera for Parking Lots; Drive-thrus; and Entry Gates up to 35MPH , 2MP, Full HD(1080p) @60fps, 12X optical zoom lens (5.2mm ~62.4mm) (54.58° ~ 5.30°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, backbox included, 12VDC/24VAC/PoE, IP67, IK10, NEMA4X, -40°C ~ +55°C (-40°F ~ +131°F) CARE IS RECOMMENDED IN SELECTING MOUNTING LOCATION – See Quick Start Guide Step 1. DEALER TRAINING OR HANWHA ENGINEER CONSULT RECOMMENDED BEFORE INSTALLING.	\$	2,000.00
XNO-6123R	Powered by WN7, Outdoor Network AI IR 12x Zoom Bullet Camera, 2MP @ 120 FPS, 5.2~62.4mm(12x) (54.58°~5.30°) zoom lens, Triple codec (H.265/H.264/MJPEG), IR viewable length 90m (295.28ft), USB port for easy installation, Day & Night (ICR), extremeWDR (150dB), DIS with built-in Gyro sensor, Handover, Hard-coated window, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/Licence plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, FIPS 140-2 certified, P66, IP67, NEMA4X, IK10, Power: PoE/12VDC, Metal shielded RJ-45	\$	1,600.00
XNO-6120R	Wisenet X powered by Wisenet 5 network IR outdoor bullet camera, 2MP, Full HD(1080p) @60fps, 12X optical zoom lens (5.2mm ~62.4mm) (54.58° ~ 5.30°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, high powered IR LEDs range of 229', true D/N, dual SD card, hallway view, HLC, defog detection, DIS(Gyro), backbox included, 12VDC/24VAC/PoE, IP67, IK10, Nema 4X, -40°C ~ +55°C (-40°F ~ +131°F)	\$	1,500.00
XNO-6120R/LPR	Wisenet X powered by Wisenet 5 network IR outdoor Low Speed LPR bullet camera for Parking Lots; Drive-thrus; and Entry Gates up to 35MPH , 2MP, Full HD(1080p) @60fps, 12X optical zoom lens (5.2mm ~62.4mm) (54.58° ~ 5.30°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, backbox included, 12VDC/24VAC/PoE, IP67, IK10, NEMA4X, -40°C ~ +55°C (-40°F ~ +131°F) CARE IS RECOMMENDED IN SELECTING MOUNTING LOCATION – See Quick Start Guide Step 1. DEALER TRAINING OR HANWHA ENGINEER CONSULT RECOMMENDED BEFORE INSTALLING.	\$	2,000.00
XNV-6080RSA	Wisenet X powered by Wisenet 5 network IR stainless steel dome camera, 2MP, Full HD(1080p) @60fps, motorized vari-focal lens 4.3x (2.8~12mm) (119.5°~27.9°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, high powered IR LEDs range of 164', true D/N, dual SD card, hallway view, HLC, defog detection, DIS, 12VDC/24VAC/PoE, IP67, IK10, Nema 4X, IP6K9K, -40°C ~ +55°C (-40°F ~ +131°F)	\$	1,620.00
XNV-6080R	Wisenet X powered by Wisenet 5 network IR outdoor vandal dome camera, 2MP, Full HD(1080p) @60fps, motorized vari-focal lens 4.3x (2.8~12mm) (119.5°~27.9°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, high powered IR LEDs range of 164', true D/N, dual SD card, hallway view, HLC, defog detection, DIS, 12VDC/24VAC/PoE, IP67, IK10, Nema 4X, -40°C ~ +55°C (-40°F ~ +131°F)	\$	1,150.00
XNV-6080	Wisenet X powered by Wisenet 5 network outdoor vandal dome camera, 2MP, Full HD(1080p) @60fps, motorized vari-focal lens 4.3x (2.8~12mm) (119.5°~27.9°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, true D/N, dual SD card, hallway view, HLC, defog detection, DIS, 12VDC/24VAC/PoE, IP67, IK10, Nema 4X, -40°C ~ +55°C (-40°F ~ +131°F)	\$	1,050.00
XNV-6010	Wisenet X powered by Wisenet 5 network outdoor vandal dome camera, 2MP, Full HD(1080p) @60fps, 2.4mm fixed lens (139°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, true D/N, dual SD card, hallway view, HLC, defog detection, DIS, 12VDC/PoE, IP67, IK10	\$	650.00
XNV-6020R	Wisenet X powered by Wisenet 5 network outdoor vandal dome camera, 2MP, Full HD(1080p) @60fps, 4mm fixed lens (88.6°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, high powered IR LEDs range of 98', true D/N, dual SD card, hallway view, HLC, defog detection, DIS, 12VDC/PoE, IP67, IK10	\$	650.00
XNV-6011	Wisenet X powered by Wisenet 5 network outdoor compact vandal dome camera, 2MP, Full HD(1080p) @60fps, 2.8mm fixed lens (112°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and business analytics, single SD card, hallway view, HLC, defog detection, DIS, PoE, IP66, Nema 4X, IK10	\$	399.00
XNV-6011W	Wisenet X powered by Wisenet 5 network outdoor compact vandal dome camera (white color), 2MP, Full HD(1080p) @60fps, 2.8mm fixed lens (112°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and business analytics, single SD card, hallway view, HLC, defog detection, DIS, PoE, IP66, Nema 4X, IK10, white color	\$	399.00
XNO-C6083R	Powered by WN7, Outdoor Network AI IR Bullet Camera, 2MP @ 60FPS, 2.8~12mm(4.3x) (119.5°~27.9°) motorized varifocal lens, Triple codec (H.265/H.264/MJPEG), IR viewable length 40m (131.2ft), USB port for easy installation, Day & Night (ICR), extremeWDR (150dB), DIS with built-in Gyro sensor, Handover, Hard-coated window, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/Licence plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, UL CAP certified, P66, IP67, NEMA4X, IK10, Power: PoE/12VDC, Metal shielded RJ-45	\$	1,200.00
XNO-6083R	Powered by WN7, X-Plus series, Outdoor Network AI IR Bullet Camera, 2MP @ 120FPS, 2.8~12mm(4.3x) (119.5°~27.9°) motorized varifocal lens, Triple codec (H.265/H.264/MJPEG), IR viewable length 50m (164ft), USB port for easy installation, Day & Night (ICR), extremeWDR (150dB), DIS with built-in Gyro sensor, Handover, Hard-coated window, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, FIPS 140-2, 2x micro SD card (512GB x2), P66, IP67, NEMA4X, IK10, Operating temperature: -50°C~+60°C(-58°F ~ +140°F), Power: PoE+/12VDC, Metal shielded RJ-45	\$	1,400.00
XNO-6080R	Wisenet X powered by Wisenet 5 network IR outdoor vandal bullet camera, 2MP, Full HD(1080p) @60fps, motorized vari-focal lens 4.3x (2.8~12mm) (119.5°~27.9°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, high powered IR LEDs range of 164', true D/N, dual SD card, hallway view, HLC, defog detection, DIS, backbox included, 12VDC/24VAC/PoE, IP67, IK10, Nema 4X, -40°C ~ +55°C (-40°F ~ +131°F)	\$	1,150.00

XNO-6010R	Wisenet X powered by Wisenet 5 network IR outdoor vandal bullet camera, 2MP, Full HD(1080p) @60fps, 2.4mm fixed focal lens (139°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, high powered IR LEDs range of 65', true D/N, dual SD card, hallway view, HLC, defog detection, DIS, backbox included, 12VDC/PoE, IP67, IK10, Nema 4X	\$	650.00
XNO-6020R	Wisenet X powered by Wisenet 5 network IR outdoor vandal bullet camera, 2MP, Full HD(1080p) @60fps, 4mm fixed focal lens (88.6°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, high powered IR LEDs range of 98', true D/N, dual SD card, hallway view, HLC, defog detection, DIS, backbox included, 12VDC/PoE, IP67, IK10, Nema 4X	\$	650.00
XND-6080RV	Wisenet X powered by Wisenet 5 network IR indoor vandal dome camera, 2MP, Full HD(1080p) @60fps, motorized vari-focal lens 4.3x (2.8~12mm) (119.5°~27.9°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, high powered IR LEDs range of 98', true D/N, dual SD card, hallway view, HLC, defog detection, DIS, 12VDC/PoE, IK08	\$	1,050.00
XND-6080V	Wisenet X powered by Wisenet 5 network indoor vandal dome camera, 2MP, Full HD(1080p) @60fps, motorized vari-focal lens 4.3x (2.8~12mm) (119.5°~27.9°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, true D/N, dual SD card, hallway view, HLC, defog detection, DIS, 12VDC/PoE, IK08	\$	950.00
XND-6010	Wisenet X powered by Wisenet 5 network indoor vandal dome camera, 2MP, Full HD(1080p) @60fps, 2.4mm fixed lens (139°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, true D/N, dual SD card, hallway view, HLC, defog detection, DIS, 12VDC/PoE, IK08	\$	600.00
XND-6020R	Wisenet X powered by Wisenet 5 network indoor vandal dome camera, 2MP, Full HD(1080p) @60fps, 4mm fixed lens (88.6°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, high powered IR LEDs range of 98', true D/N, dual SD card, hallway view, HLC, defog detection, DIS, 12VDC/PoE, IK08	\$	600.00
XND-6011F	Wisenet X powered by Wisenet 5 network flush mount dome camera, 2MP, Full HD(1080p) @ 60fps, 2.8mm fixed lens (112°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, built-in Mic, magnetic cover, electronic D/N, SD card, hallway view, HLC, defog detection, DIS, PoE only	\$	500.00
XNV-6013M	Wisenet X powered by Wisenet 5 network outdoor vandal dome camera, 2MP, Full HD(1080p) @60fps, 2.8mm fixed lens (107.4°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, electrical D/N, single SD card, hallway view, HLC, defog detection, DIS, PoE, IP6K9K, IK10 NEMA 4X, -40°C ~ +60°C (-40°F ~ +140°F) This camera was designed to be mounted outside of the vehicle, M12 connector (M12 to RJ45 is not included)	\$	810.00
XNV-6012	Wisenet X powered by Wisenet 5 network outdoor vandal dome camera, 2MP, Full HD(1080p) @60fps, 2.4mm fixed lens (135.4°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, electrical D/N, single SD card, hallway view, HLC, defog detection, DIS, PoE, IP66, IK10 NEMA 4X	\$	670.00
XNV-6012M	Wisenet X powered by Wisenet 5 network outdoor vandal dome camera, 2MP, Full HD(1080p) @60fps, 2.4mm fixed lens (135.4°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, electrical D/N, single SD card, hallway view, HLC, defog detection, DIS, PoE, IP66, IK10 NEMA 4X, M12 connector (M12 to RJ45 is not included)	\$	670.00
XNV-6022R	Wisenet X powered by Wisenet 5 network outdoor vandal dome camera, 2MP, Full HD(1080p) @60fps, 3.6mm fixed lens (94.8°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, IR LEDs range of 49', true D/N, single SD card, hallway view, HLC, defog detection, DIS, PoE, IP66, IK10 NEMA 4X	\$	740.00
XNV-6022RM	Wisenet X powered by Wisenet 5 network outdoor vandal dome camera, 2MP, Full HD(1080p) @60fps, 3.6mm fixed lens (94.8°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, IR LEDs range of 49', true D/N, single SD card, hallway view, HLC, defog detection, DIS, PoE, IP66, IK10 NEMA 4X, M12 connector (M12 to RJ45 is not included)	\$	740.00
XNZ-L6320A	Wisenet X powered by Wisenet 5 network zoom box camera, 2MP, Full HD(1080p) @60fps, 32X optical zoom lens (4.44mm ~ 142.6mm) (61.8° ~ 2.19°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, advanced video analytics and sound classification, true D/N, built in SD card slot, HLC, defog detection, 12VDC/PoE	\$	1,400.00
XNZ-L6320	Wisenet X powered by Wisenet 5 network zoom box camera, 2MP, Full HD(1080p) @60fps, 32X optical zoom lens (4.44mm ~ 142.6mm) (61.8° ~ 2.19°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, advanced video analytics and sound classification, true D/N, built in SD card slot, HLC, defog detection, 12VDC/PoE	\$	1,400.00
XNB-6000	Wisenet X powered by Wisenet 5 network box camera, 2MP, Full HD(1080p) @60fps, simple focus, triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, true D/N, dual SD card, hallway view, HLC, defog detection, DIS(Gyro), 12VDC/24VAC/PoE	\$	850.00
XNB-6001	Wisenet X powered by Wisenet 5 covert camera body, 2MP, full HD(1080p) 60fps, triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, micro SD/SDHC/SDXC, USB port for easy installation, advanced video analytics and sound classification and business analytics, hallway view, HLC, defog detection, DIS, 12VDC/PoE, +14°F ~ 131°F, lens module is not included compatible lens modules (SLA-T2480, SLA-T2480V, SLA-T4680, SLA-T4680V, SLA-T1080F, SLA-T4680D, SLA-T4680DS, SLA-T4680DW)	\$	510.00
XNV-L6080R	Wisenet X powered by Wisenet 5 network outdoor vandal dome camera, 2MP, Full HD(1080p) @60fps, motorized vari-focal lens 3.1x (3.2~10mm) (109°~33.2°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, high powered IR LEDs range of 98.43', true D/N, single SD card, hallway view, HLC, defog detection, DIS, PoE, IP66, IK10, -40°C ~ +55°C (-40°F ~ +131°F)	\$	925.00
XNV-L6080	Wisenet X powered by Wisenet 5 network outdoor vandal dome camera, 2MP, Full HD(1080p) @60fps, motorized vari-focal lens 3.1x (3.2~10mm) (109°~33.2°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, true D/N, single SD card, hallway view, HLC, defog detection, DIS, PoE, IP66, IK10, -40°C ~ +55°C (-40°F ~ +131°F)	\$	825.00
XND-L6080RV	Wisenet X powered by Wisenet 5 network indoor vandal dome camera, 2MP, Full HD(1080p) @60fps, motorized vari-focal lens 3.1x (3.2~10mm) (109°~33.2°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, high powered IR LEDs range of 98.43', true D/N, single SD card, hallway view, HLC, defog detection, DIS, PoE, IK08	\$	825.00
XND-L6080V	Wisenet X powered by Wisenet 5 network indoor vandal dome camera, 2MP, Full HD(1080p) @60fps, motorized vari-focal lens 3.1x (3.2~10mm) (109°~33.2°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, true D/N, single SD card, hallway view, HLC, defog detection, DIS, PoE, IK08	\$	725.00
XNO-L6080R	Wisenet X powered by Wisenet 5 network IR outdoor bullet camera, 2MP, Full HD(1080p) @60fps, motorized vari-focal lens 3.1x (3.2~10mm) (109°~33.2°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, high powered IR LEDs range of 98.43', true D/N, single SD card, hallway view, HLC, defog detection, DIS, PoE, IP66, IK10, -40°C ~ +55°C (-40°F ~ +131°F)	\$	925.00
TNB-6030	PVM camera powered by Wisenet 5, 1080p (1920x1080), micro HDMI output, 16:9 aspect ratio, face detection display for visual deterrent, customizable text overlay, 4.6mm fixed lens(73.8°H), 150dB WDR, H.265/H.264/MJPEG, WiseStream II compression technology, micro SD/SDHC/SDXC, bi-directional audio, hallway view mode	\$	709.00
TNO-6010M	Wisenet T network mobile front facing camera, 2MP @ 60fps, 2.8mm fixed focal lens (113°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics, true D/N, SD card, hallway view, HLC, defog detection, DIS (Gyro), PoE, IP66, IK10, M12 connector (M12 to RJ45 is not included)	\$	750.00

QNO-6012R	Wisenet Q network outdoor vandal bullet camera, 2MP @ 30fps, 2.8mm fixed focal lens (113°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 65', defocus detection, hallway View, one way audio and SD card, video analytics, CVBS, open platform, IP66, IK10, PoE/12VDC	\$	379.00
QNO-6012R1	Wisenet Q network outdoor vandal bullet camera, 2MP @ 30fps, 2.8mm fixed focal lens (113°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 65', defocus detection, hallway View, no audio in/out, SD card, video analytics, CVBS, open platform, IP66, IK10, PoE/12VDC	\$	379.00
QNO-6022R	Wisenet Q network outdoor vandal bullet camera, 2MP @ 30fps, 4.0mm fixed focal lens (87°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 82', defocus detection, hallway View, one way audio and SD card, video analytics, CVBS, open platform, IP66, IK10, PoE/12VDC	\$	379.00
QNO-6032R	Wisenet Q network outdoor vandal bullet camera, 2MP @ 30fps, 6.0mm fixed focal lens (52°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 98', defocus detection, hallway View, one way audio and SD card, video analytics, CVBS, open platform, IP66, IK10, PoE/12VDC	\$	379.00
QNO-6082R	Wisenet Q network outdoor vandal bullet camera, 2MP @ 30fps, motorized vari-focal lens 3.1x (3.2 ~ 10.0mm) (109°~33°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 98', defocus detection, hallway View, one way audio and SD card, video analytics, CVBS, open platform, IP66, IK10, PoE/12VDC	\$	519.00
QNO-6082R1	Wisenet Q network outdoor vandal bullet camera, 2MP @ 30fps, motorized vari-focal lens 3.1x (3.2 ~ 10.0mm) (109°~33°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 98', defocus detection, hallway View, no audio in/out, SD card, video analytics, CVBS, open platform, IP66, IK10, PoE/12VDC	\$	519.00
QNV-6012R	Wisenet Q network outdoor vandal dome camera, 2MP @ 30fps, 2.8mm fixed focal lens (113°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 65', defocus detection, hallway View, one way audio and SD card, video analytics, CVBS, open platform, IP66, IK10, PoE/12VDC, white color	\$	395.00
QNV-6012R1	Wisenet Q network outdoor vandal dome camera, 2MP @ 30fps, 2.8mm fixed focal lens (113°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 65', defocus detection, hallway View, no audio in/out, SD card, video analytics, CVBS, open platform, IP66, IK10, PoE/12VDC, white color	\$	395.00
QNV-6022R	Wisenet Q network outdoor vandal dome camera, 2MP @ 30fps, 4.0mm fixed focal lens (87°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 82', defocus detection, hallway View, one way audio and SD card, video analytics, CVBS, open platform, IP66, IK10, PoE/12VDC, white color	\$	395.00
QNV-6022R1	Wisenet Q network outdoor vandal dome camera, 2MP @ 30fps, 4.0mm fixed focal lens (87°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 82', defocus detection, hallway View, no audio in/out, SD card, video analytics, CVBS, open platform, IP66, IK10, PoE/12VDC, white color	\$	395.00
QNV-6024RM	Wisenet Q network Mobile IR vandal dome camera, 2MP, Full HD(1080p) 30fps, triple codec H.265/H.264/MJPEG with WiseStream technology, Fixed focal Lens 3.6mm, Built in Mic, M12 Network connectors (M12 connector to RJ-45 adaptor is not included), hallway View, 120dB WDR, built-in IR range of 32.8', true D/N, built-in SD card slot, IP66, IK10	\$	399.00
QNV-6032R	Wisenet Q network outdoor vandal dome camera, 2MP @ 30fps, 6.0mm fixed focal lens (52°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 98', defocus detection, hallway View, one way audio and SD card, video analytics, CVBS, open platform, IP66, IK10, PoE/12VDC, white color	\$	395.00
QNV-6082R	Wisenet Q network outdoor vandal dome camera, 2MP @ 30fps, motorized vari-focal lens 3.1x (3.2 ~ 10.0mm) (109°~33°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 98', defocus detection, hallway View, one way audio and SD card, video analytics, CVBS, open platform, IP66, IK10, PoE/12VDC, white color	\$	535.00
QNV-6082R1	Wisenet Q network outdoor vandal dome camera, 2MP @ 30fps, motorized vari-focal lens 3.1x (3.2 ~ 10.0mm) (109°~33°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 98', defocus detection, hallway View, no audio in/out, SD card, video analytics, CVBS, open platform, IP66, IK10, PoE/12VDC, white color	\$	535.00
QNV-6023R	Wisenet Q network outdoor vandal dome camera, 2MP @ 30fps, 3.6mm fixed focal lens (94.8°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 49', defocus detection, hallway View, one way audio and SD card, video analytics, CVBS, open platform, IP66, IK10, PoE	\$	339.00
QND-6012R	Wisenet Q network indoor dome camera, 2MP @ 30fps, 2.8mm fixed focal lens (113°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 65', defocus detection, hallway View, one way audio and SD card, video analytics, CVBS, open platform, PoE/12VDC, white color	\$	289.00
QND-6012R1	Wisenet Q network indoor dome camera, 2MP @ 30fps, 2.8mm fixed focal lens (113°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 65', defocus detection, hallway View, no audio in/out, SD card, video analytics, CVBS, open platform, PoE/12VDC, white color	\$	289.00
QND-6022R	Wisenet Q network indoor dome camera, 2MP @ 30fps, 4.0mm fixed focal lens (87°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 65', defocus detection, hallway View, one way audio and SD card, video analytics, CVBS, open platform, PoE/12VDC, white color	\$	289.00
QND-6032R	Wisenet Q network indoor dome camera, 2MP @ 30fps, 6.0mm fixed focal lens (52°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 65', defocus detection, hallway View, one way audio and SD card, video analytics, CVBS, open platform, PoE/12VDC, white color	\$	289.00
QND-6082R	Wisenet Q network indoor dome camera, 2MP @ 30fps, motorized vari-focal lens 3.1x (3.2 ~ 10.0mm) (109°~33°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 98', defocus detection, hallway View, one way audio and SD card, video analytics, CVBS, open platform, PoE/12VDC, white color	\$	459.00
QND-6082R1	Wisenet Q network indoor dome camera, 2MP @ 30fps, motorized vari-focal lens 3.1x (3.2 ~ 10.0mm) (109°~33°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 98', defocus detection, hallway View, no audio in/out, SD card, video analytics, CVBS, open platform, PoE/12VDC, white color	\$	459.00
QND-6011	Wisenet Q mini network indoor dome camera, 2MP @ 30fps, 2.8mm fixed focal lens (113°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, defocus detection, hallway View, SD card, people counting, open platform, IP42, IK08, PoE, white color	\$	280.00
QND-6021	Wisenet Q mini network indoor dome camera, 2MP @ 30fps, 4.0mm fixed focal lens (87°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, defocus detection, hallway View, SD card, people counting, open platform, IP42, IK08, PoE, white color	\$	280.00
LVN-6072R	L series outdoor vandal dome camera, 2MP @ 30fps, vari-focal lens 3.1x (3.2 ~ 10mm) (101.6° ~31.3°), Double codec H.264/MJPEG, Wisestream II, 120dB WDR, IR LEDs, hallway view, SD card, IP66, IK10, PoE, White	\$	359.00
LVN-6012R	L series outdoor vandal dome camera, 2MP @ 30fps, 3mm fixed focal lens (102°), Double codec H.264/MJPEG, Wisestream II, 120dB WDR, IR LEDs, hallway view, SD card, IP66, IK10, PoE, White	\$	265.00
LVN-6022R	L series outdoor vandal dome camera, 2MP @ 30fps, 4mm fixed focal lens (80°), Double codec H.264/MJPEG, Wisestream II, 120dB WDR, IR LEDs, hallway view, SD card, IP66, IK10, PoE, White	\$	265.00
LVN-6032R	L series outdoor vandal dome camera, 2MP @ 30fps, 6mm fixed focal lens (51°), Double codec H.264/MJPEG, Wisestream II, 120dB WDR, IR LEDs, hallway view, SD card, IP66, IK10, PoE, White	\$	265.00
LND-6072R	L series indoor dome camera, 2MP @ 30fps, vari-focal lens 3.1x (3.2 ~ 10mm) (101.6° ~31.3°), Double codec H.264/MJPEG, Wisestream II, 120dB WDR, IR LEDs, hallway view, SD card, PoE, White	\$	319.00
LND-6012R	L series indoor dome camera, 2MP @ 30fps, 3mm fixed focal lens (102°), Double codec H.264/MJPEG, Wisestream II, 120dB WDR, IR LEDs, hallway view, SD card, PoE, White	\$	209.00
LND-6022R	L series indoor dome camera, 2MP @ 30fps, 4mm fixed focal lens (80°), Double codec H.264/MJPEG, Wisestream II, 120dB WDR, IR LEDs, hallway view, SD card, PoE, White	\$	209.00
LND-6032R	L series indoor dome camera, 2MP @ 30fps, 6mm fixed focal lens (51°), Double codec H.264/MJPEG, Wisestream II, 120dB WDR, IR LEDs, hallway view, SD card, PoE, White	\$	209.00
LNO-6072R	L series outdoor bullet camera, 2MP @ 30fps, vari-focal lens 3.1x (3.2 ~ 10mm) (101.6° ~31.3°), Double codec H.264/MJPEG, Wisestream II, 120dB WDR, IR LEDs, hallway view, SD card, IP66, PoE, White	\$	359.00
LNO-6012R	L series outdoor bullet camera, 2MP @ 30fps, 3mm fixed focal lens (102°), Double codec H.264/MJPEG, Wisestream II, 120dB WDR, IR LEDs, hallway view, SD card, IP66, PoE, White	\$	249.00
LNO-6022R	L series outdoor bullet camera, 2MP @ 30fps, 4mm fixed focal lens (80°), Double codec H.264/MJPEG, Wisestream II, 120dB WDR, IR LEDs, hallway view, SD card, IP66, PoE, White	\$	249.00
LNO-6032R	L series outdoor bullet camera, 2MP @ 30fps, 6mm fixed focal lens (51°), Double codec H.264/MJPEG, Wisestream II, 120dB WDR, IR LEDs, hallway view, SD card, IP66, PoE, White	\$	249.00

XNB-H6241A	Wisenet X powered by Wisenet 5 network ATM camera, 2MP, Full HD(1080p) 60fps, 2.4mm fixed lens (138°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, micro SD/SDHC/SDXC, USB port for easy installation, advanced video analytics and sound classification and business analytics, hallway view, HLC, defog detection, DIS, 12VDC/PoE, +14°F ~ 131°F, cable Length is 8m (26 feet).	\$	849.00
XNB-H6240A	Wisenet X powered by Wisenet 5 network ATM camera, 2MP, Full HD(1080p) 60fps, 2.4mm fixed lens (138°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, micro SD/SDHC/SDXC, USB port for easy installation, advanced video analytics and sound classification and business analytics, hallway view, HLC, defog detection, DIS, 12VDC/PoE, +14°F ~ 131°F, cable Length is 1.5m (4.9 feet).	\$	849.00
XNB-H6461H	Wisenet X powered by Wisenet 5 network pinhole camera with height strip housing, 2MP, Full HD(1080p) 60fps, 4.6mm fixed lens (73°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, micro SD/SDHC/SDXC, USB port for easy installation, advanced video analytics and sound classification and business analytics, hallway view, HLC, defog detection, DIS, 12VDC/PoE, +14°F ~ 131°F, cable Length is 8m (26 feet).	\$	1,055.00
XNB-H6280B	Wisenet X powered by Wisenet 5 network Bandit Barrier camera, 2MP, Full HD(1080p) 60fps, 2.8mm fixed lens (107.4°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, micro SD/SDHC/SDXC, USB port for easy installation, advanced video analytics and sound classification and business analytics, hallway view, HLC, defog detection, DIS, 12VDC/PoE, +14°F ~ 131°F, cable Length is 1.5m (4.9 feet).	\$	1,300.00
QNP-6230	Wisenet Q network indoor PTZ camera, 2MP, Full HD(1080p) 30fps, H.265/H.264/MJPEG, Optical Zoom Lens 23x (4.44-102.1mm), 120dB WDR, true D/N, 500°/sec Pan, SD/SDHC/SDXC, 24VAC/PoE+	\$	1,500.00
QNP-6230H	Wisenet Q network outdoor PTZ camera, 2MP, Full HD(1080p) 30fps, H.265/H.264/MJPEG, Optical Zoom Lens 23x (4.44-102.1mm), 120dB WDR, true D/N, 500°/sec Pan, SD/SDHC/SDXC, 24VAC/PoE+, Analytics, IP66, IK10, Heater on -58°F 24VAC	\$	1,700.00
QNP-6230RH	Wisenet Q network outdoor IR PTZ camera, IR range for up to 328ft, 2MP, Full HD(1080p) 30fps, triple codec H.265/H.264/MJPEG with WiseStream II, 23x optical zoom (4.44 ~ 102.2mm) (61.8° ~ 3.08°), 120dB WDR, HLC, true D/N, 24VAC / HPoE, IP66, IK10, Built-in -58°F (-50°C) Heater (24VAC only) HPoE injector not included	\$	2,000.00
QNP-6250	Wisenet Q network indoor PTZ camera, 2MP, Full HD(1080p) 60fps, triple codec H.265/H.264/MJPEG with WiseStream II technology, 4.44~111mm (25x) lens, 120dB WDR, Day & Night (ICR), DIS (Built-in gyro sensor), Intelligent Analytics, Micro SD/SDHC/SDXC 1slot 256GB, Focus Save, white color	\$	1,500.00
QNP-6250H	Wisenet Q network outdoor PTZ camera, 2MP, Full HD(1080p) 60fps, triple codec H.265/H.264/MJPEG with WiseStream II technology, 4.44~111mm (25x) lens, 120dB WDR, Day & Night (ICR), DIS (Built-in gyro sensor), Intelligent Analytics, Micro SD/SDHC/SDXC 1slot 256GB, Focus Save, IP66, IK10, NEMA4X, white color	\$	1,700.00
QNP-6250R	Wisenet Q network IR PTZ camera, IR range of up to 328ft, 2MP, Full HD(1080p) 60fps, triple codec H.265/H.264/MJPEG with WiseStream II technology, 4.44~111mm (25x) lens, 120dB WDR, Day & Night (ICR), DIS (Built-in gyro sensor), Intelligent Analytics, Micro SD/SDHC/SDXC 1slot 256GB, Focus Save, IP66, IK10, NEMA4X, white color	\$	2,000.00
QNP-6320	Wisenet Q network indoor PTZ camera, 2MP, Full HD(1080p) 60fps, triple codec H.265/H.264/MJPEG with WiseStream II technology, 4.44~142.6mm (32x) lens, 120dB WDR, Day & Night (ICR), DIS (Built-in gyro sensor), Intelligent Analytics, Micro SD/SDHC/SDXC 1slot 256GB, Focus Save, white color	\$	2,300.00
QNP-6320H	Wisenet Q network outdoor PTZ camera, 2MP, Full HD(1080p) 60fps, triple codec H.265/H.264/MJPEG with WiseStream II technology, 4.44~142.6mm (32x) lens, 120dB WDR, Day & Night (ICR), DIS (Built-in gyro sensor), Intelligent Analytics, Micro SD/SDHC/SDXC 1slot 256GB, Focus Save, IP66, IK10, NEMA4X, white color	\$	2,500.00
QNP-6320R	Wisenet Q network IR PTZ camera, IR range of up to 328ft, 2MP, Full HD(1080p) 60fps, triple codec H.265/H.264/MJPEG with WiseStream II technology, 4.44~142.6mm (32x) lens, 120dB WDR, Day & Night (ICR), DIS (Built-in gyro sensor), Intelligent Analytics, Micro SD/SDHC/SDXC 1slot 256GB, Focus Save, IP66, IK10, NEMA4X, white color	\$	2,700.00
QNP-6320HS	Wisenet Q stainless steel PTZ camera, 2MP, Full HD(1080p) 60fps, triple codec H.265/H.264/MJPEG with WiseStream II technology, 4.44~142.6mm (32x) lens, 120dB WDR, Day & Night (ICR), DIS (Built-in gyro sensor), Directional detection, Motion detection, Enter/Exit, Tampering, Virtual line, Audio detection* (with NW I/O Box), Micro SD/SDHC/SDXC 1slot 256GB, Focus Save, IP66/IP67, IK10, NEMA4X, PoE+	\$	5,040.00
TNU-6321	2MP Network Positioning Camera (1920 x 1080) resolution, 4.44 ~ 142.6mm (32x) varifocal lens, 60fps@2MP (H.264), 30fps@2MP (MJPEG), H.265, H.264, MJPEG codec support, 360° Endless, Tilt -90°~40°, Day & Night (ICR), WDR (120dB), Defog, Tampering, Virtual line, Enter / Exit, (Dis)Appear, Audio detection, Face detection, Motion detection, micro SD / SDHC / SDXC slot, Power 24VAC (Optional IR illuminators: SPI-50)	\$	5,100.00
PNV-A9081RLP	4K Low-Moderate Speed LPR Vandal Dome Camera with Wisenet Road AI. Max. 4K resolution, 4.5~10mm(2.2x) M-Varifocal(4K) lens, 0.05Lux@F1.6 (Color), 0Lux (B/W, IR LED on), Day & Night(ICR), WDR(120dB), H.265, H.264, MJPEG codec, WiseStream III, POE+, IP66/67/IP6K9K, IK10+, NEMA4X LPR + MMCR: Make, Model & Color* Recognition on the Edge. 32GB Micro SD storage for up to 10,000 LPR/Vehicle images, Licensed open platform application for multiple regions/countries. (* Color recognition only during day time) CARE IS RECOMMENDED IN SELECTING THE INSTALL LOCATION – See product selector and quick reference guide for details. Use Hanwha pre-sales support consult at lrsupport@hanwha.com	\$	3,050.00
PNO-A9081RLP	4K Low-Moderate Speed LPR Bullet Camera with Wisenet Road AI. Max. 4K resolution, 4.5~10mm(2.2x) M-Varifocal(4K) lens, 0.05Lux@F1.6 (Color), 0Lux (B/W, IR LED on), Day & Night(ICR), WDR(120dB), H.265, H.264, MJPEG codec, WiseStream III, POE+, IP66/67/IP6K9K, IK10+, NEMA4X LPR + MMCR: Make, Model & Color* Recognition on the Edge. 32GB Micro SD storage for up to 10,000 LPR/Vehicle images, Licensed open platform application for multiple regions/countries. (* Color recognition only during day time) CARE IS RECOMMENDED IN SELECTING THE INSTALL LOCATION – See product selector and quick reference guide for details. Use Hanwha pre-sales support consult at lrsupport@hanwha.com	\$	2,950.00
TNO-4041T	Wisenet T network outdoor vandal thermal camera (uncooled), 640x480 @ 30fps, 19mm fixed focal lens (32°), triple codec H.265/H.264/MJPEG with Wisestream II, SD card, advanced video analytics and sound classification, PTZ handover, open platform, DIS(Gyro), IP66, IK10, PoE/12VDC/24VAC, white color RS485/422, built to go on PT head unit	\$	7,000.00
TNO-4040T	Wisenet T network outdoor vandal thermal bullet camera (uncooled), 640x480 @ 30fps, 19mm fixed focal lens (32°), triple codec H.265/H.264/MJPEG with Wisestream II, SD card, advanced video analytics and sound classification, PTZ handover, open platform, DIS(Gyro), integrated back box, IP66, IK10, PoE/12VDC/24VAC, white color	\$	7,000.00
TNO-4030T	Wisenet T network outdoor vandal thermal bullet camera (uncooled), 640x480 @ 30fps, 13mm fixed focal lens (48.6°), triple codec H.265/H.264/MJPEG with Wisestream II, SD card, advanced video analytics and sound classification, PTZ handover, open platform, DIS(Gyro), integrated back box, IP66, IK10, PoE/12VDC/24VAC, white color	\$	7,000.00
TNO-4051T	Wisenet T network outdoor vandal thermal camera (uncooled), 640x480 @ 30fps, 35mm fixed focal lens (17.2°), triple codec H.265/H.264/MJPEG with Wisestream II, SD card, advanced video analytics and sound classification, PTZ handover, open platform, DIS(Gyro), IP66, IK10, PoE/12VDC/24VAC, white color RS485/422, built to go on PT head unit	\$	8,400.00

TNO-4050T	Wisenet T network outdoor thermal bullet camera (uncooled), 640x480 @ 30fps, 35mm fixed focal lens (17.2°), triple codec H.265/H.264/MJPEG with Wisestream II, SD card, advanced video analytics and sound classification, PTZ handover, open platform, DIS(Gyro), integrated back box, IP66, IK10, PoE/12VDC/24VAC, white color	\$	8,400.00
TNU-4041T	Wisenet T network outdoor thermal positioning camera (uncooled), 640x480 @ 30fps, 19mm fixed focal lens (32°), pan: 360° endless, Tilt: -90° ~ 40°, triple codec H.265/H.264/MJPEG with Wisestream II, SD card, advanced video analytics and sound classification, PTZ handover, open platform, DIS(Gyro), integrated back box, IP66, IK10, 24VAC, white color	\$	14,250.00
TNU-4051T	Wisenet T network outdoor thermal positioning camera (uncooled), 640x480 @ 30fps, 35mm fixed focal lens (17.2°), pan: 360° endless, Tilt: -90° ~ 40°, triple codec H.265/H.264/MJPEG with Wisestream II, SD card, advanced video analytics and sound classification, PTZ handover, open platform, DIS(Gyro), integrated back box, IP66, IK10, 24VAC, white color	\$	16,000.00
TNO-4030TR	Wisenet T network outdoor vandal Radiometric bullet camera (uncooled), 640x480 @ 30fps, 13mm fixed focal lens (48.6°), triple codec H.265/H.264/MJPEG with Wisestream II, SD card, advanced video analytics and sound classification, PTZ handover, up to 3 user programmable temperature detection areas, temperature detection range is from (-4°F ~ 266°F) , open platform, DIS(Gyro), integrated back box, IP66, IK10, PoE/12VDC/24VAC, white color	\$	9,500.00
TNO-4040TR	Wisenet T network outdoor vandal Radiometric bullet camera (uncooled), 640x480 @ 30fps, 19mm fixed focal lens (32°), triple codec H.265/H.264/MJPEG with Wisestream II, SD card, advanced video analytics and sound classification, PTZ handover, up to 3 user programmable temperature detection areas, temperature detection range is from (-4°F ~ 266°F) , open platform, DIS(Gyro), integrated back box, IP66, IK10, PoE/12VDC/24VAC, white color	\$	9,500.00
TNO-4041TR	Wisenet T network outdoor vandal Radiometric bullet camera (uncooled), 640x480 @ 30fps, 19mm fixed focal lens (32°), triple codec H.265/H.264/MJPEG with Wisestream II, SD card, advanced video analytics and sound classification, PTZ handover, up to 3 user programmable temperature detection areas, temperature detection range is from (-4°F ~ 266°F) , open platform, DIS(Gyro), integrated back box, IP66, IK10, PoE/12VDC/24VAC, white color RS485/422, built to go on PT head unit	\$	9,500.00
TNM-3620TDY	Wisenet T network indoor body temperature detection camera (uncooled), dual sensor camera with QVGA thermal (320x240) & 2MP (1920x1080) visible video outputs, built-in 4.7mm fixed lens (50°) (thermal), 4mm fixed lens (87.6°) (visible), AI Face & temperature detection, Estimated Body Temperature Mode: +30°C~+45°C (+86°F~+113°F), accuracy ±0.5°C (±0.9°F) / with blackbody ±0.3°C (±0.54°F), normal radiometric mode temperature detection range from (-4°F~+266°F), triple codec H.265/H.264/MJPEG with Wisestream II, 150dB WDR, USB and CVBS port for easy installation, advanced video analytics, micro SD, DIS, PoE/12VDC	\$	7,600.00
TNO-3010T	QVGA Thermal camera, Max. 320 x 240 resolution support, built-in 2.7mm fixed lens, H.265, H.264, MJPEG codec, Max. 30fps@all resolutions, full video and audio analytics, temperature detection, shock detection, micro SD Max. 256GB, Hallway View, WiseStreamII, PoE, 24VAC, 12VDC / IP66, NEMA4X, IK10	\$	4,100.00
TNO-3020T	QVGA Thermal camera, Max. 320 x 240 resolution support, built-in 4.3mm fixed lens, H.265, H.264, MJPEG codec, Max. 30fps@all resolutions, full video and audio analytics, temperature detection, shock detection, micro SD Max. 256GB, Hallway View, WiseStreamII, PoE, 24VAC, 12VDC / IP66, NEMA4X, IK10	\$	4,100.00
TNO-3030T	QVGA Thermal camera, Max. 320 x 240 resolution support, built-in 13.7mm fixed lens, H.265, H.264, MJPEG codec, Max. 30fps@all resolutions, full video and audio analytics, temperature detection, shock detection, micro SD Max. 256GB, Hallway View, WiseStreamII, PoE, 24VAC, 12VDC / IP66, NEMA4X, IK10	\$	4,100.00
TNO-3040T	QVGA Thermal camera, Max. 320 x 240 resolution support, built-in 19mm fixed lens, H.265, H.264, MJPEG codec, Max. 30fps@all resolutions, full video and audio analytics, temperature detection, shock detection, micro SD Max. 256GB, Hallway View, WiseStreamII, PoE, 24VAC, 12VDC / IP66, NEMA4X, IK10	\$	5,000.00
TNO-3050T	QVGA Thermal camera, Max. 320 x 240 resolution support, built-in 35mm fixed lens, H.265, H.264, MJPEG codec, Max. 30fps@all resolutions, full video and audio analytics, temperature detection, shock detection, micro SD Max. 256GB, Hallway View, WiseStreamII, PoE, 24VAC, 12VDC / IP66, NEMA4X, IK10	\$	6,520.00

TNO-X6320EPT0-Z	Explosion proof housing using the XNZ-6320 PoE Only (No Wiper), cLCus C1/D1 certification, -10°C ~ +55°C (+14°F ~ +131°F), IP66/IP67,IP68, "-Z" for cLCus C1/D1	\$	7,650.00
TNO-X6320EPT0-C	Explosion proof housing using the XNZ-6320 PoE Only (No Wiper), cLCus C1/D1 certification, -10°C ~ +55°C (+14°F ~ +131°F), IP66/IP67,IP68, "-C" for cLC CSA	\$	7,650.00
TNO-X6320EPT0-M	Explosion proof housing using the XNZ-6320 PoE Only (No Wiper), cLCus C1/D1 certification, -10°C ~ +55°C (+14°F ~ +131°F), IP66/IP67,IP68, "-M" for INMETRO	\$	7,650.00
TNO-X6320E1WT1-Z	Explosion proof housing using the XNZ-6320 24VAC Only with wiper, cLCus C1/D1 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP66/IP67,IP68, "-Z" for cLCus C1/D1	\$	10,400.00
TNO-X6320E1WT1-C	Explosion proof housing using the XNZ-6320 24VAC Only with wiper, cLCus C1/D1 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP66/IP67,IP68, "-C" for cLC CSA	\$	10,400.00
TNO-X6320E1WT2-C	Explosion proof housing using the XNZ-6320 24VAC Only with wiper, cLCus C1/D1 certification, -60°C ~ +40°C (-67°F ~ +104°F), IP66/IP67,IP68, "-C" for cLC CSA	\$	11,100.00
TNO-X6320E1WT1-M	Explosion proof housing using the XNZ-6320 24VAC Only with wiper, cLCus C1/D1 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP66/IP67,IP68, "-M" for INMETRO	\$	10,400.00
TNO-X6320E2F2T1-Z	Explosion proof housing using the XNZ-6320 110VAC Only, Single Mode Fiber (No Wiper), cLCus C1/D1 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP66/IP67,IP68, "-Z" for cLCus C1/D1	\$	14,000.00
TNO-X6320E2F2T1-C	Explosion proof housing using the XNZ-6320 110VAC Only, Single Mode Fiber (No Wiper), cLCus C1/D1 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP66/IP67,IP68, "-C" for cLC CSA	\$	14,000.00
TNO-X6320E2F2T2-C	Explosion proof housing using the XNZ-6320 110VAC Only, Single Mode Fiber (No Wiper), cLCus C1/D1 certification, -60°C ~ +40°C (-67°F ~ +104°F), IP66/IP67,IP68, "-C" for cLC CSA	\$	14,700.00
TNO-X6320E2F2T1-M	Explosion proof housing using the XNZ-6320 110VAC Only, Single Mode Fiber (No Wiper), cLCus C1/D1 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP66/IP67,IP68, "-M" for INMETRO	\$	14,000.00
TNO-X6320E2F2WT1-Z	Explosion proof housing using the XNZ-6320 110VAC Only, Single Mode Fiber with Wiper, cLCus C1/D1 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP66/IP67,IP68, "-Z" for cLCus C1/D1	\$	15,325.00
TNO-X6320E2F2WT1-C	Explosion proof housing using the XNZ-6320 110VAC Only, Single Mode Fiber with Wiper, cLCus C1/D1 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP66/IP67,IP68, "-C" for cLC CSA	\$	15,325.00
TNO-X6320E2F2WT2-C	Explosion proof housing using the XNZ-6320 110VAC Only, Single Mode Fiber with Wiper, cLCus C1/D1 certification, -60°C ~ +40°C (-67°F ~ +104°F), IP66/IP67,IP68, "-C" for cLC CSA	\$	16,025.00
TNO-X6320E2F2WT1-M	Explosion proof housing using the XNZ-6320 110VAC Only, Single Mode Fiber with Wiper, cLCus C1/D1 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP66/IP67,IP68, "-M" for INMETRO	\$	15,325.00
TNU-X6320E2WT1-Z	Explosion proof positioning camera using the XNZ-6320 110VAC Only, with Wiper, cLCus C1/D1 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP66/IP67, "-Z" for cLCus C1/D1	\$	30,175.00
TNU-X6320E2WT1-C	Explosion proof positioning camera using the XNZ-6320 110VAC Only, with Wiper, cLCus C1/D1 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP66/IP67, "-C" for cLC CSA	\$	30,175.00
TNU-X6320E2WT2-C	Explosion proof positioning camera using the XNZ-6320 110VAC Only, with Wiper, cLCus C1/D1 certification, -60°C ~ +40°C (-67°F ~ +104°F), IP66/IP67, "-C" for cLC CSA	\$	30,875.00
TNU-X6320E2WT1-M	Explosion proof positioning camera using the XNZ-6320 110VAC Only, with Wiper, cLCus C1/D1 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP66/IP67, "-M" for INMETRO	\$	30,175.00
TNU-X6320E2F2WT1-Z	Explosion proof positioning camera using the XNZ-6320 110VAC Only, Single Mode Fiber with Wiper, cLCus C1/D1 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP66/IP67, "-Z" for cLCus C1/D1	\$	31,500.00
TNU-X6320E2F2WT1-C	Explosion proof positioning camera using the XNZ-6320 110VAC Only, Single Mode Fiber with Wiper, cLCus C1/D1 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP66/IP67, "-C" for cLC CSA	\$	31,500.00
TNU-X6320E2F2WT2-C	Explosion proof positioning camera using the XNZ-6320 110VAC Only, Single Mode Fiber with Wiper, cLCus C1/D1 certification, -60°C ~ +40°C (-67°F ~ +104°F), IP66/IP67, "-C" for cLC CSA	\$	32,200.00
TNU-X6320E2F2WT1-M	Explosion proof positioning camera using the XNZ-6320 110VAC Only, Single Mode Fiber with Wiper, cLCus C1/D1 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP66/IP67, "-M" for INMETRO	\$	31,500.00
TNU-X6320E1WT1-Z	Explosion proof positioning camera using the XNZ-6320 24VAC Only, with Wiper, cLCus C1/D1 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP66/IP67, "-Z" for cLCus C1/D1	\$	30,175.00

TNU-X6320E1WT1-C	Explosion proof positioning camera using the XNZ-6320 24VAC Only, with Wiper, cLCus C1/D1 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP66/IP67, "-C" for cLC CSA	\$	30,175.00
TNU-X6320E1WT2-C	Explosion proof positioning camera using the XNZ-6320 24VAC Only, with Wiper, cLCus C1/D1 certification, -60°C ~ +40°C (-67°F ~ +104°F), IP66/IP67, "-C" for cLC CSA	\$	30,875.00
TNU-X6320E1WT1-M	Explosion proof positioning camera using the XNZ-6320 24VAC Only, with Wiper, cLCus C1/D1 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP66/IP67, "-M" for INMETRO	\$	30,175.00
TNU-X6320E1F2WT1-Z	Explosion proof positioning camera using the XNZ-6320 24VAC Only, Single Mode Fiber with Wiper, cLCus C1/D1 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP66/IP67, "-Z" for cLCus C1/D1	\$	31,500.00
TNU-X6320E1F2WT1-C	Explosion proof positioning camera using the XNZ-6320 24VAC Only, Single Mode Fiber with Wiper, cLCus C1/D1 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP66/IP67, "-C" for cLC CSA	\$	31,500.00
TNU-X6320E1F2WT2-C	Explosion proof positioning camera using the XNZ-6320 24VAC Only, Single Mode Fiber with Wiper, cLCus C1/D1 certification, -60°C ~ +40°C (-67°F ~ +104°F), IP66/IP67, "-C" for cLC CSA	\$	32,200.00
TNU-X6320E1F2WT1-M	Explosion proof positioning camera using the XNZ-6320 24VAC Only, Single Mode Fiber with Wiper, cLCus C1/D1 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP66/IP67, "-M" for INMETRO	\$	31,500.00
HT-E-XWP10UL	Stainless steel Washer tank for cameras with Wiper model (TNP-6320E2W, TNP-6320E2WF, TNP-6320E1W, TNP-6320E1WF, TNU positioning camera, TNO-6070E2WF, TNO-6320E2WF, TNO-6070E1W)	\$	7,725.00
HT-E-BFP00SW	Stainless steel Top mounting bracket	\$	775.00
HT-E-BFW320SW	Stainless steel wall mount for (TNO-6070EP, TNO-6320EP, TNO-6070EW2, TNO-6320EW2)	\$	1,650.00
HT-E-BPW6800	Stainless steel Wall mount for (TNP-xxx, TNU-xxxx)	\$	1,475.00
HT-E-BFW50SW	Stainless steel wall mount for (TNO-6070EF2, TNO-6320EF2, TNO-6070EWF2, TNO-6320EWF2)	\$	1,825.00
HT-E-BFP00CL	Stainless steel pole mount adaptor	\$	1,550.00
TNO-X6072EPT1-Z	Explosion proof camera using the XNB-6000 (2MP @ 60fps) + 2.8-9mm Lens PoE Only (No Wiper), -40°C ~ +55°C (-40°F ~ +131°F), type 4x, IP66, FM (Factory Mutual)", C1/D1 certification	\$	6,950.00
TNO-X8072EPT1-Z	Explosion proof camera using the XNB-8000 (5MP @ 30fps) + 4.1-9mm Lens PoE Only (No Wiper), -40°C ~ +55°C (-40°F ~ +131°F), type 4x, IP66, FM (Factory Mutual)", C1/D1 certification	\$	7,150.00
TNO-X6322EPT1-Z	Explosion proof zoom camera using the XNZ-L6320 (2MP @ 60fps) with 32x optical zoom, PoE Only (No Wiper), -40°C ~ +55°C (-40°F ~ +131°F), type 4x, IP66, FM (Factory Mutual)", C1/D1 certification	\$	7,900.00
TNP-X6322EPT3-Z	Explosion proof PTZ using the XNP-6320 (2MP @ 60fps) +with 32x optical zoom PoE+ (No Wiper), -20°C ~ +55°C (-4°F ~ +131°F), type 4x, IP66, FM (Factory Mutual)", C1/D1 certification	\$	21,400.00
TNP-Q6232EPT3-Z	Explosion proof PTZ using the QNP-6230 (2MP @ 30fps) +with 23x optical zoom PoE+ (No Wiper), -20°C ~ +55°C (-4°F ~ +131°F), type 4x, IP66, FM (Factory Mutual)", C1/D1 certification	\$	18,900.00
TNO-P9072EPT1-Z	AI 4K Explosion proof camera using the PNB-A9001 (8MP @ 30fps) + 3.9-10mm f1.5 Varifocal i-CS Lens PoE+ (No Wiper), -40°C ~ +55°C (-40°F ~ +131°F), type 4x, IP66, FM (Factory Mutual), cLCus C1/D1 certification	\$	8,000.00
TNM-P9022EPT3-Z	WN7 Panoramic Multi-sensor explosion proof camera, 180° view, (2MP X 4 sensors) 7.3MP @ 30fps, panoramic 209° view, 8.3MP, triple codec H.265/H.264/MJPEG with WiseStream II technology, extreme WDR 120dB, defocus detection, built in analytics, Heatmap, Micro USB for easy installation, 2 x Micro SD cards PoE+, IP66/IK10/NEMA4X; FM (Factory Mutual), cLCus C1/D1 certification	\$	14,500.00
HT-F1XX-WM	Wall mount for the (TNO-X6072EPT1-Z, TNO-X8072EPT1-Z, and TNO-X6322EPT1-Z)	\$	950.00
HT-SD-FP	Protection kit for the (TNP-X6322EPT3-Z, TNP-Q6232EPT3-Z)	\$	400.00
HT-SD-WM	Wall mount for the (TNP-X6322EPT3-Z, TNP-Q6232EPT3-Z)	\$	950.00
HT-SF-FP	Protection kit for the (TNO-X6072EPT1-Z, TNO-X8072EPT1-Z and TNO-X6322EPT1-Z)	\$	400.00
HT-SPMA-SD	Pole mount for the (TNO-X6072EPT1-Z, TNO-X8072EPT1-Z and TNO-X6322EPT1-Z, TNP-X6322EPT3-Z, TNP-Q6232EPT3-Z) requires a wall mount	\$	1,150.00
HT-SD-CM	Corner mount for the (TNO-X6072EPT1-Z, TNO-X8072EPT1-Z and TNO-X6322EPT1-Z, TNP-X6322EPT3-Z, TNP-Q6232EPT3-Z) requires a wall mount	\$	1,050.00
TID-600R	Video Intercom Station, 2MP@60fps, 1.6mm fixed lens (180° x 114°), triple codec H.265/H.264/MJPEG with Wisestream II, 150dB WDR, IR LEDs range 16', Touchless call, Tow-way (Full duplex) audio, 85dB@0.5m, Echo cancellation and noise reduction, Built in tamper switch, Built in Relay, SIP 2.0, P2P-SIP, SIPS, IP65, IK08, NEMA4X, PoE, 12VDC	\$	1,133.00
WAVE-PRO-01	WAVE Professional License. Enables one (1) IP stream recording, includes life-time SW upgrade. No annual & maintenance cost required.	\$	165.00
WAVE-PRO-04	WAVE Professional License. Enables four (4) IP stream recording, includes life-time SW upgrade. No annual & maintenance cost required.	\$	660.00
WAVE-PRO-08	WAVE Professional License. Enables eight (8) IP stream recording, includes life-time SW upgrade. No annual & maintenance cost required.	\$	1,320.00
WAVE-PRO-16	WAVE Professional License. Enables sixteen (16) IP stream recording, includes life-time SW upgrade. No annual & maintenance cost required.	\$	2,640.00
WAVE-PRO-24	WAVE Professional License. Enables twenty-four (24) IP stream recording, includes life-time SW upgrade. No annual & maintenance cost required.	\$	3,960.00
WAVE-PRO-48	WAVE Professional License. Enables forty-eight (48) IP stream recording, includes life-time SW upgrade. No annual & maintenance cost required.	\$	7,920.00
WAVE-VW-02	WAVE Video Wall License. Enables up to two (2) monitors, includes life-time SW upgrade. No annual & maintenance cost required.	\$	1,400.00
WAVE-ENC-04	WAVE Encoder License. Enables up to four (4) recording channels, includes life-time SW upgrade. No annual & maintenance cost required.	\$	165.00
WAVE-IO-01	WAVE I/O License. Enables one (1) I/O module, includes life-time SW upgrade. No annual & maintenance cost required.	\$	165.00
WAVE-EMB-04	WAVE Embedded Recorder License. Enables four (4) channel Hanwha Embedded Recorder playback, includes life-time SW upgrade. No annual & maintenance cost required.	\$	110.00
WAVE-EMB-08	WAVE Embedded Recorder License. Enables eight (8) channel Hanwha Embedded Recorder playback, includes life-time SW upgrade. No annual & maintenance cost required.	\$	220.00
WAVE-EMB-16	WAVE Embedded Recorder License. Enables sixteen (16) channel Hanwha Embedded Recorder playback, includes life-time SW upgrade. No annual & maintenance cost required.	\$	440.00
WAVE-EMB-32	WAVE Embedded Recorder License. Enables thirty-two (32) channel Hanwha Embedded Recorder playback, includes life-time SW upgrade. No annual & maintenance cost required.	\$	880.00
WAVE-EMB-64	WAVE Embedded Recorder License. Enables sixty-four (64) channel Hanwha Embedded Recorder playback, includes life-time SW upgrade. No annual & maintenance cost required.	\$	1,760.00
WWT-P-3201W	Small form factor Wisenet WAVE Client Workstation for 2 monitor output, Wisenet WAVE pre-installed, (10th Gen) Intel Core i3, 8GB RAM, 256 SSD OS Drive, Windows 10 IoT Enterprise, Nvidia Quadro P400 GPU w/ (3) Mini DisplayPort output, Single GbE NIC, (2) MiniDisplayPort to HDMI adapters included, Keyboard and mouse included	\$	3,860.00
WWT-P-7401W	Small form factor Wisenet WAVE Client Workstation for 4 monitor output, Wisenet WAVE pre-installed, (10th Gen) Intel Core i7, 16GB RAM, 256 SSD OS Drive, Windows 10 IoT Enterprise, Nvidia Quadro P620 GPU w/ (4) Mini DisplayPort output, Single GbE NIC, (4) MiniDisplayPort to HDMI adapters included, Keyboard and mouse included	\$	5,400.00
WWT-P-7200MW	Micro form factor Wisenet WAVE Client Workstation for 2 monitor output, Wisenet WAVE pre-installed, (10th Gen) Intel Core i7, 16GB RAM, 256GB SSD OS Drive, Windows 10 IoT Enterprise, Single GbE NIC, (2) DisplayPort output, (2) DisplayPort to HDMI adapters included, Keyboard and Mouse Included	\$	4,320.00
WRN-1610S-2TB	2U WAVE PoE NVR (Intel based) with 4 Professional licenses, 2TB RAW, supports: 16 channels with 16 PoE/PoE+ ports (PoE Budget 200W), Wisenet WAVE pre-installed, H.264/H.265/MJPEG, 4 fixed internal SATA HDDs (6TB max per HDD), Wisestream technology, HDMI/VGA output, Dual GbE NICs	\$	2,623.00
WRN-1610S-4TB	2U WAVE PoE NVR (Intel based) with 4 Professional licenses, 4TB RAW, supports: 16 channels with 16 PoE/PoE+ ports (PoE Budget 200W), Wisenet WAVE pre-installed, H.264/H.265/MJPEG, 4 fixed internal SATA HDDs (6TB max per HDD), Wisestream technology, HDMI/VGA output, Dual GbE NICs	\$	2,983.00

WRN-1610S-6TB	2U WAVE PoE NVR (Intel based) with 4 Professional licenses, 6TB RAW, supports: 16 channels with 16 PoE/PoE+ ports (PoE Budget 200W), Wisenet WAVE pre-installed, H.264/H.265/MJPEG, 4 fixed internal SATA HDDs (6TB max per HDD), Wisestream technology, HDMI/VGA output, Dual GbE NICs	\$	3,343.00
WRN-1610S-8TB	2U WAVE PoE NVR (Intel based) with 4 Professional licenses, 8TB RAW, supports: 16 channels with 16 PoE/PoE+ ports (PoE Budget 200W), Wisenet WAVE pre-installed, H.264/H.265/MJPEG, 4 fixed internal SATA HDDs (6TB max per HDD), Wisestream technology, HDMI/VGA output, Dual GbE NICs	\$	3,703.00
WRN-1610S-12TB	2U WAVE PoE NVR (Intel based) with 4 Professional licenses, 12TB RAW, supports: 16 channels with 16 PoE/PoE+ ports (PoE Budget 200W), Wisenet WAVE pre-installed, H.264/H.265/MJPEG, 4 fixed internal SATA HDDs (6TB max per HDD), Wisestream technology, HDMI/VGA output, Dual GbE NICs	\$	4,423.00
WRN-1610S-18TB	2U WAVE PoE NVR (Intel based) with 4 Professional licenses, 18TB RAW, supports: 16 channels with 16 PoE/PoE+ ports (PoE Budget 200W), Wisenet WAVE pre-installed, H.264/H.265/MJPEG, 4 fixed internal SATA HDDs (6TB max per HDD), Wisestream technology, HDMI/VGA output, Dual GbE NICs	\$	5,503.00
WRN-1610S-24TB	2U WAVE PoE NVR (Intel based) with 4 Professional licenses, 24TB RAW, supports: 16 channels with 16 PoE/PoE+ ports (PoE Budget 200W), Wisenet WAVE pre-installed, H.264/H.265/MJPEG, 4 fixed internal SATA HDDs (6TB max per HDD), Wisestream technology, HDMI/VGA output, Dual GbE NICs	\$	6,583.00
WRN-810S-1TB	1U WAVE PoE NVR (Intel based) with 4 Professional licenses, 1TB RAW, supports: 8 channels with 8 PoE/PoE+ ports (PoE Budget 100W), Wisenet WAVE pre-installed, H.264/H.265/MJPEG, 2 fixed internal SATA HDDs (6TB max per HDD), Wisestream technology, HDMI/VGA output, Dual GbE NICs	\$	2,036.00
WRN-810S-2TB	1U WAVE PoE NVR (Intel based) with 4 Professional licenses, 2TB RAW, supports: 8 channels with 8 PoE/PoE+ ports (PoE Budget 100W), Wisenet WAVE pre-installed, H.264/H.265/MJPEG, 2 fixed internal SATA HDDs (6TB max per HDD), Wisestream technology, HDMI/VGA output, Dual GbE NICs	\$	2,216.00
WRN-810S-4TB	1U WAVE PoE NVR (Intel based) with 4 Professional licenses, 4TB RAW, supports: 8 channels with 8 PoE/PoE+ ports (PoE Budget 100W), Wisenet WAVE pre-installed, H.264/H.265/MJPEG, 2 fixed internal SATA HDDs (6TB max per HDD), Wisestream technology, HDMI/VGA output, Dual GbE NICs	\$	2,576.00
WRN-810S-6TB	1U WAVE PoE NVR (Intel based) with 4 Professional licenses, 6TB RAW, supports: 8 channels with 8 PoE/PoE+ ports (PoE Budget 100W), Wisenet WAVE pre-installed, H.264/H.265/MJPEG, 2 fixed internal SATA HDDs (6TB max per HDD), Wisestream technology, HDMI/VGA output, Dual GbE NICs	\$	2,936.00
WRN-810S-8TB	1U WAVE PoE NVR (Intel based) with 4 Professional licenses, 8TB RAW, supports: 8 channels with 8 PoE/PoE+ ports (PoE Budget 100W), Wisenet WAVE pre-installed, H.264/H.265/MJPEG, 2 fixed internal SATA HDDs (6TB max per HDD), Wisestream technology, HDMI/VGA output, Dual GbE NICs	\$	3,297.00
WRN-810S-12TB	1U WAVE PoE NVR (Intel based) with 4 Professional licenses, 12TB RAW, supports: 8 channels with 8 PoE/PoE+ ports (PoE Budget 100W), Wisenet WAVE pre-installed, H.264/H.265/MJPEG, 2 fixed internal SATA HDDs (6TB max per HDD), Wisestream technology, HDMI/VGA output, Dual GbE NICs	\$	4,017.00
WRT-P-3100MW-1TB	Micro form factor Wisenet WAVE Network Video Recorder with 4 Professional licenses, Wisenet WAVE pre-installed, 1TB raw, 45 Mbps recording B/W, (1) 2.5" HDD, (10th Gen) Intel Core i3, 8GB RAM, 256 GB SSD OS Drive, Windows 10 IoT Enterprise, (1) HDMI, (1) DisplayPort output, , 1 GbE NIC, , Keyboard and mouse included	\$	3,730.00
WRT-P-3100MW-2TB	Micro form factor Wisenet WAVE Network Video Recorder with 4 Professional licenses, Wisenet WAVE pre-installed, 2TB raw, 45 Mbps recording B/W, (1) 2.5" HDD, (10th Gen) Intel Core i3, 8GB RAM, 256 GB SSD OS Drive, Windows 10 IoT Enterprise, (1) HDMI, (1) DisplayPort output, , 1 GbE NIC, , Keyboard and mouse included	\$	3,840.00
WRT-P-3101W-4TB	Mini-tower form factor Wisenet WAVE Network Video Recorder with 4 Professional licenses, Wisenet WAVE pre-installed, 4TB raw, 170 Mbps recording B/W, (1) 3.5" HDD, (10th Gen) Intel Core i3, 8GB RAM, 256 GB SSD OS Drive, Windows 10 IoT Enterprise, (2) DisplayPort output, (1) DisplayPort to HDMI adapter included, Dual GbE NICs, Single 550W power supply, Keyboard and mouse included	\$	4,740.00
WRT-P-3101W-8TB	Mini-tower form factor Wisenet WAVE Network Video Recorder with 4 Professional licenses, Wisenet WAVE pre-installed, 8TB raw, 170 Mbps recording B/W, (2) 3.5" HDD, (10th Gen) Intel Core i3, 8GB RAM, 256 GB SSD OS Drive, Windows 10 IoT Enterprise, (2) DisplayPort output, (1) DisplayPort to HDMI adapter included, Dual GbE NICs, Single 550W power supply, Keyboard and mouse included	\$	5,810.00
WRT-P-3101W-12TB	Mini-tower form factor Wisenet WAVE Network Video Recorder with 4 Professional licenses, Wisenet WAVE pre-installed, 12TB raw, 170 Mbps recording B/W, (3) 3.5" HDD, (10th Gen) Intel Core i3, 8GB RAM, 256 GB SSD OS Drive, Windows 10 IoT Enterprise, (2) DisplayPort output, (1) DisplayPort to HDMI adapter included, Dual GbE NICs, Single 550W power supply, Keyboard and mouse included	\$	6,350.00
WRT-P-3101W-16TB	Mini-tower form factor Wisenet WAVE Network Video Recorder with 4 Professional licenses, Wisenet WAVE pre-installed, 16TB raw, 170 Mbps recording B/W, (2) 3.5" HDD, (10th Gen) Intel Core i3, 8GB RAM, 256 GB SSD OS Drive, Windows 10 IoT Enterprise, (2) DisplayPort output, (1) DisplayPort to HDMI adapter included, Dual GbE NICs, Single 550W power supply, Keyboard and mouse included	\$	6,770.00
WRT-P-5201W-4TB	Mini-tower form factor Wisenet WAVE Network Video Recorder with 4 Professional licenses, Wisenet WAVE pre-installed, 4TB raw, 470 Mbps recording B/W, (1) 3.5" HDD, (10th Gen) Intel Core i5, 16GB RAM, 256 GB SSD OS Drive, Windows 10 IoT Enterprise, (2) DisplayPort output, (1) DisplayPort to HDMI adapter included, Dual GbE NICs, Single 550W power supply, Keyboard and mouse included	\$	5,460.00
WRT-P-5201W-8TB	Mini-tower form factor Wisenet WAVE Network Video Recorder with 4 Professional licenses, Wisenet WAVE pre-installed, 8TB raw, 470 Mbps recording B/W, (2) 3.5" HDD, (10th Gen) Intel Core i5, 16GB RAM, 256 GB SSD OS Drive, Windows 10 IoT Enterprise, (2) DisplayPort output, (1) DisplayPort to HDMI adapter included, Dual GbE NICs, Single 550W power supply, Keyboard and mouse included	\$	6,550.00
WRT-P-5201W-12TB	Mini-tower form factor Wisenet WAVE Network Video Recorder with 4 Professional licenses, Wisenet WAVE pre-installed, 12TB raw, 470 Mbps recording B/W, (3) 3.5" HDD, (10th Gen) Intel Core i5, 16GB RAM, 256 GB SSD OS Drive, Windows 10 IoT Enterprise, (2) DisplayPort output, (1) DisplayPort to HDMI adapter included, Dual GbE NICs, Single 550W power supply, Keyboard and mouse included	\$	7,190.00
WRT-P-5201W-16TB	Mini-tower form factor Wisenet WAVE Network Video Recorder with 4 Professional licenses, Wisenet WAVE pre-installed, 16TB raw, 470 Mbps recording B/W, (2) 3.5" HDD, (10th Gen) Intel Core i5, 16GB RAM, 256 GB SSD OS Drive, Windows 10 IoT Enterprise, (2) DisplayPort output, (1) DisplayPort to HDMI adapter included, Dual GbE NICs, Single 550W power supply, Keyboard and mouse included	\$	7,610.00
WRT-P-5201W-20TB	Mini-tower form factor Wisenet WAVE Network Video Recorder with 4 Professional licenses, Wisenet WAVE pre-installed, 20TB raw, 470 Mbps recording B/W, (2) 3.5" HDD, (10th Gen) Intel Core i5, 16GB RAM, 256 GB SSD OS Drive, Windows 10 IoT Enterprise, (2) DisplayPort output, (1) DisplayPort to HDMI adapter included, Dual GbE NICs, Single 550W power supply, Keyboard and mouse included	\$	8,140.00
WRT-P-5201W-24TB	Mini-tower form factor Wisenet WAVE Network Video Recorder with 4 Professional licenses, Wisenet WAVE pre-installed, 24TB raw, 470 Mbps recording B/W, (3) 3.5" HDD, (10th Gen) Intel Core i5, 16GB RAM, 256 GB SSD OS Drive, Windows 10 IoT Enterprise, (2) DisplayPort output, (1) DisplayPort to HDMI adapter included, Dual GbE NICs, Single 550W power supply, Keyboard and mouse included	\$	8,240.00
WRT-P-5201W-36TB	Mini-tower form factor Wisenet WAVE Network Video Recorder with 4 Professional licenses, Wisenet WAVE pre-installed, 36TB raw, 470 Mbps recording B/W, (3) 3.5" HDD, (10th Gen) Intel Core i5, 16GB RAM, 256 GB SSD OS Drive, Windows 10 IoT Enterprise, (2) DisplayPort output, (1) DisplayPort to HDMI adapter included, Dual GbE NICs, Single 550W power supply, Keyboard and mouse included	\$	9,540.00
WRR-P-E200W2-8TB	1U Wisenet WAVE Network Video Recorder with 4 Professional licenses, Wisenet WAVE pre-installed, 8TB raw (7TB usable after disk formatting & JBOD configuration), 470 Mbps recording B/W, 4 HDD Bay (3.5" with up to 3 hot plug drives), Intel Xeon, 16GB RAM, 480GB SSD OS drive, Windows 10 IoT Enterprise, Nvidia GPU, MiniDP output, VGA output, Dual GbE NICs, IPMI, Single 250W power supply, Keyboard and mouse included, Rail kit included	\$	8,520.00
WRR-P-E200W2-12TB	1U Wisenet WAVE Network Video Recorder with 4 Professional licenses, Wisenet WAVE pre-installed, 12TB raw (11TB usable after disk formatting & JBOD configuration), 470 Mbps recording B/W, 4 HDD Bay (3.5" with up to 3 hot plug drives), Intel Xeon, 16GB RAM, 480GB SSD OS drive, Windows 10 IoT Enterprise, Nvidia GPU, MiniDP output, VGA output, Dual GbE NICs, IPMI, Single 250W power supply, Keyboard and mouse included, Rail kit included	\$	9,630.00

[illegible]

[illegible]

[illegible]

[illegible]

WRR-Q-A201W-12TB	2U Wisenet WAVE Network Video Recorder with 4 Professional licenses, Wisenet WAVE pre-installed, 12TB raw (7TB usable after disk formatting & RAID 5 configuration), 470 Mbps recording B/W, 12 HDD Bay (3.5" with up to 10 hot plug storage drives), AMD EPYC, 16GB RAM, Dual 480GB SSD OS drives (RAID 1), Windows 10 IoT Enterprise, Support RAID 0/1/5/6 + 2GB cache, Nvidia GPU, MiniDP output, VGA output, Dual GbE NICs, IPMI, Redundant 750W power supplies, Keyboard and mouse included, Rail kit included	\$	17,598.00
WRR-Q-A201W-16TB	2U Wisenet WAVE Network Video Recorder with 4 Professional licenses, Wisenet WAVE pre-installed, 16TB raw (11TB usable after disk formatting & RAID 5 configuration), 470 Mbps recording B/W, 12 HDD Bay (3.5" with up to 10 hot plug storage drives), AMD EPYC, 16GB RAM, Dual 480GB SSD OS drives (RAID 1), Windows 10 IoT Enterprise, Support RAID 0/1/5/6 + 2GB cache, Nvidia GPU, MiniDP output, VGA output, Dual GbE NICs, IPMI, Redundant 750W power supplies, Keyboard and mouse included, Rail kit included	\$	18,113.00
WRR-Q-A201W-20TB	2U Wisenet WAVE Network Video Recorder with 4 Professional licenses, Wisenet WAVE pre-installed, 20TB raw (14TB usable after disk formatting & RAID 5 configuration), 470 Mbps recording B/W, 12 HDD Bay (3.5" with up to 10 hot plug storage drives), AMD EPYC, 16GB RAM, Dual 480GB SSD OS drives (RAID 1), Windows 10 IoT Enterprise, Support RAID 0/1/5/6 + 2GB cache, Nvidia GPU, MiniDP output, VGA output, Dual GbE NICs, IPMI, Redundant 750W power supplies, Keyboard and mouse included, Rail kit included	\$	18,627.00
WRR-Q-A201W-24TB	2U Wisenet WAVE Network Video Recorder with 4 Professional licenses, Wisenet WAVE pre-installed, 24TB raw (18TB usable after disk formatting & RAID 5 configuration), 470 Mbps recording B/W, 12 HDD Bay (3.5" with up to 10 hot plug storage drives), AMD EPYC, 16GB RAM, Dual 480GB SSD OS drives (RAID 1), Windows 10 IoT Enterprise, Support RAID 0/1/5/6 + 2GB cache, Nvidia GPU, MiniDP output, VGA output, Dual GbE NICs, IPMI, Redundant 750W power supplies, Keyboard and mouse included, Rail kit included	\$	19,142.00
WRR-Q-A201W-32TB	2U Wisenet WAVE Network Video Recorder with 4 Professional licenses, Wisenet WAVE pre-installed, 32TB raw (22TB usable after disk formatting & RAID 5 configuration), 470 Mbps recording B/W, 12 HDD Bay (3.5" with up to 10 hot plug storage drives), AMD EPYC, 16GB RAM, Dual 480GB SSD OS drives (RAID 1), Windows 10 IoT Enterprise, Support RAID 0/1/5/6 + 2GB cache, Nvidia GPU, MiniDP output, VGA output, Dual GbE NICs, IPMI, Redundant 750W power supplies, Keyboard and mouse included, Rail kit included	\$	19,929.00
WRR-Q-A201W-40TB	2U Wisenet WAVE Network Video Recorder with 4 Professional licenses, Wisenet WAVE pre-installed, 40TB raw (29TB usable after disk formatting & RAID 5 configuration), 470 Mbps recording B/W, 12 HDD Bay (3.5" with up to 10 hot plug storage drives), AMD EPYC, 16GB RAM, Dual 480GB SSD OS drives (RAID 1), Windows 10 IoT Enterprise, Support RAID 0/1/5/6 + 2GB cache, Nvidia GPU, MiniDP output, VGA output, Dual GbE NICs, IPMI, Redundant 750W power supplies, Keyboard and mouse included, Rail kit included	\$	20,895.00
WRR-Q-A201W-48TB	2U Wisenet WAVE Network Video Recorder with 4 Professional licenses, Wisenet WAVE pre-installed, 48TB raw (37TB usable after disk formatting & RAID 5 configuration), 470 Mbps recording B/W, 12 HDD Bay (3.5" with up to 10 hot plug storage drives), AMD EPYC, 16GB RAM, Dual 480GB SSD OS drives (RAID 1), Windows 10 IoT Enterprise, Support RAID 0/1/5/6 + 2GB cache, Nvidia GPU, MiniDP output, VGA output, Dual GbE NICs, IPMI, Redundant 750W power supplies, Keyboard and mouse included, Rail kit included	\$	21,861.00
WRR-Q-A201W-56TB	2U Wisenet WAVE Network Video Recorder with 4 Professional licenses, Wisenet WAVE pre-installed, 56TB raw (44TB usable after disk formatting & RAID 5 configuration), 470 Mbps recording B/W, 12 HDD Bay (3.5" with up to 10 hot plug storage drives), AMD EPYC, 16GB RAM, Dual 480GB SSD OS drives (RAID 1), Windows 10 IoT Enterprise, Support RAID 0/1/5/6 + 2GB cache, Nvidia GPU, MiniDP output, VGA output, Dual GbE NICs, IPMI, Redundant 750W power supplies, Keyboard and mouse included, Rail kit included	\$	22,827.00
WRR-Q-A201W-64TB	2U Wisenet WAVE Network Video Recorder with 4 Professional licenses, Wisenet WAVE pre-installed, 64TB raw (52TB usable after disk formatting & RAID 5 configuration), 470 Mbps recording B/W, 12 HDD Bay (3.5" with up to 10 hot plug storage drives), AMD EPYC, 16GB RAM, Dual 480GB SSD OS drives (RAID 1), Windows 10 IoT Enterprise, Support RAID 0/1/5/6 + 2GB cache, Nvidia GPU, MiniDP output, VGA output, Dual GbE NICs, IPMI, Redundant 750W power supplies, Keyboard and mouse included, Rail kit included	\$	23,793.00
WRR-Q-A201W-72TB	2U Wisenet WAVE Network Video Recorder with 4 Professional licenses, Wisenet WAVE pre-installed, 72TB raw (59TB usable after disk formatting & RAID 5 configuration), 470 Mbps recording B/W, 12 HDD Bay (3.5" with up to 10 hot plug storage drives), AMD EPYC, 16GB RAM, Dual 480GB SSD OS drives (RAID 1), Windows 10 IoT Enterprise, Support RAID 0/1/5/6 + 2GB cache, Nvidia GPU, MiniDP output, VGA output, Dual GbE NICs, IPMI, Redundant 750W power supplies, Keyboard and mouse included, Rail kit included	\$	24,759.00
WRR-Q-A201W-80TB	2U Wisenet WAVE Network Video Recorder with 4 Professional licenses, Wisenet WAVE pre-installed, 80TB raw (67TB usable after disk formatting & RAID 5 configuration), 470 Mbps recording B/W, 12 HDD Bay (3.5" with up to 10 hot plug storage drives), AMD EPYC, 16GB RAM, Dual 480GB SSD OS drives (RAID 1), Windows 10 IoT Enterprise, Support RAID 0/1/5/6 + 2GB cache, Nvidia GPU, MiniDP output, VGA output, Dual GbE NICs, IPMI, Redundant 750W power supplies, Keyboard and mouse included, Rail kit included	\$	25,725.00
WRR-Q-A201W-96TB	2U Wisenet WAVE Network Video Recorder with 4 Professional licenses, Wisenet WAVE pre-installed, 96TB raw (78TB usable after disk formatting & RAID 5 configuration), 470 Mbps recording B/W, 12 HDD Bay (3.5" with up to 10 hot plug storage drives), AMD EPYC, 16GB RAM, Dual 480GB SSD OS drives (RAID 1), Windows 10 IoT Enterprise, Support RAID 0/1/5/6 + 2GB cache, Nvidia GPU, MiniDP output, VGA output, Dual GbE NICs, IPMI, Redundant 750W power supplies, Keyboard and mouse included, Rail kit included	\$	27,458.00
VER-CSTORE15-40TB	Veracity Coldstore 3U, 400mbps, L.A.I.D with SFS disk filing system, requires WAVE Server (not included) to operate, 15 internal SATA HDD bays, 40TB raw (effective: 32TB Normal COLDSTORE mode)	\$	22,750.00
VER-CSTORE15-48TB	Veracity Coldstore 3U, 400mbps, L.A.I.D with SFS disk filing system, requires WAVE Server (not included) to operate, 15 internal SATA HDD bays, 48TB raw (effective: 40TB Normal COLDSTORE mode)	\$	24,190.00
VER-CSTORE15-56TB	Veracity Coldstore 3U, 400mbps, L.A.I.D with SFS disk filing system, requires WAVE Server (not included) to operate, 15 internal SATA HDD bays, 56TB raw (effective: 48TB Normal COLDSTORE mode)	\$	25,630.00
VER-CSTORE15-64TB	Veracity Coldstore 3U, 400mbps, L.A.I.D with SFS disk filing system, requires WAVE Server (not included) to operate, 15 internal SATA HDD bays, 64TB raw (effective: 56TB Normal COLDSTORE mode)	\$	27,070.00
VER-CSTORE15-72TB	Veracity Coldstore 3U, 400mbps, L.A.I.D with SFS disk filing system, requires WAVE Server (not included) to operate, 15 internal SATA HDD bays, 72TB raw (effective: 64TB Normal COLDSTORE mode)	\$	28,510.00
VER-CSTORE15-80TB	Veracity Coldstore 3U, 400mbps, L.A.I.D with SFS disk filing system, requires WAVE Server (not included) to operate, 15 internal SATA HDD bays, 80TB raw (effective: 72TB Normal COLDSTORE mode)	\$	29,950.00
VER-CSTORE15-88TB	Veracity Coldstore 3U, 400mbps, L.A.I.D with SFS disk filing system, requires WAVE Server (not included) to operate, 15 internal SATA HDD bays, 88TB raw (effective: 80TB Normal COLDSTORE mode)	\$	31,390.00
VER-CSTORE15-96TB	Veracity Coldstore 3U, 400mbps, L.A.I.D with SFS disk filing system, requires WAVE Server (not included) to operate, 15 internal SATA HDD bays, 96TB raw (effective: 88TB Normal COLDSTORE mode)	\$	32,830.00
VER-CSTORE15-104TB	Veracity Coldstore 3U, 400mbps, L.A.I.D with SFS disk filing system, requires WAVE Server (not included) to operate, 15 internal SATA HDD bays, 104TB raw (effective: 96TB Normal COLDSTORE mode)	\$	34,270.00
VER-CSTORE15-112TB	Veracity Coldstore 3U, 400mbps, L.A.I.D with SFS disk filing system, requires WAVE Server (not included) to operate, 15 internal SATA HDD bays, 112TB raw (effective: 104TB Normal COLDSTORE mode)	\$	35,710.00
VER-CSTORE15-120TB	Veracity Coldstore 3U, 400mbps, L.A.I.D with SFS disk filing system, requires WAVE Server (not included) to operate, 15 internal SATA HDD bays, 120TB raw (effective: 112TB Normal COLDSTORE mode)	\$	37,150.00
VER-CSTORERAIL	Veracity Coldstore 3U Rack Rail accessory	\$	440.00
VER-CSTORECRDL	Veracity Coldstore 3U HDD cradle	\$	90.00
VER-CSTORE15-154TB	Veracity Coldstore 3U, 400mbps, L.A.I.D with SFS disk filing system, requires WAVE Server (not included) to operate, 15 internal SATA HDD bays, 154TB raw (effective: 140TB Normal COLDSTORE mode)	\$	43,270.00
VER-CSTORE15-182TB	Veracity Coldstore 3U, 400mbps, L.A.I.D with SFS disk filing system, requires WAVE Server (not included) to operate, 15 internal SATA HDD bays, 182TB raw (effective: 168TB Normal COLDSTORE mode)	\$	48,310.00
VER-CSTORE15-210TB	Veracity Coldstore 3U, 400mbps, L.A.I.D with SFS disk filing system, requires WAVE Server (not included) to operate, 15 internal SATA HDD bays, 210TB raw (effective: 196TB Normal COLDSTORE mode)	\$	53,350.00
(Wisenet SKY products are only available for Wisenet SKY certified partners)			
EN-SU301-0	Wisenet SKY Location Setup Fee Bridge 301 (Rack Form Factor)	\$	870.00
EN-SU304p-0	Wisenet SKY Location Setup Fee Bridge 304+ (Compact Form Factor)	\$	870.00
EN-SU305-0	Wisenet SKY Location Setup Fee Bridge 305 (Compact and Ruggedized Form Factor with 4 PoE Ports)	\$	1,132.00

EN-SU306p-0	Wisenet SKY Location Setup Fee Bridge 306+ (Compact and Ruggedized Form Factor)	\$	1,219.00
EN-SU401-0	Wisenet SKY Location Setup Fee Bridge 401 (Rack Form Factor)	\$	1,463.00
EN-SU404p-0	Wisenet SKY Location Setup Fee Bridge 404+ (Compact Form Factor)	\$	1,742.00
EN-SU501-0	Wisenet SKY Location Setup Fee Bridge 501 (Rack Form Factor)	\$	2,091.00
EN-BR320-0	Wisenet SKY CMVR 320 with 4TB (Rack Form Factor)	\$	1,306.00
EN-BR324p-0	Wisenet SKY CMVR 324+ with 4TB (Compact and Ruggedized Form Factor)	\$	1,306.00
EN-BR325-0	Wisenet SKY CMVR 325 with 2TB (Compact and Ruggedized Form Factor with 4 PoE Ports)	\$	1,306.00
EN-BR420-0	Wisenet SKY CMVR 420 with 10TB (Rack Form Factor)	\$	2,789.00
EN-BR520-0	Wisenet SKY CMVR 520 with 40TB Raid 5 (Enterprise Rack Form Factor)	\$	6,626.00
EN-BR620-0	Wisenet SKY CMVR 620 with 64TB Raid 5 (Enterprise Rack Form Factor)	\$	11,510.00
EN-BR820-0	Wisenet SKY CMVR 820 with 120TB Raid 6 (Enterprise Rack Form Factor)	\$	19,184.00
EN-DS100-0a	Wisenet SKY Local Display Station DS100 (Single Monitor Output)	\$	1,568.00
EN-DS200-0a	Wisenet SKY Local Display Station DS200 (Dual Monitor Output with 4K support)	\$	2,963.00
EN-SW05m-001	Wisenet SKY Switch SW05m (4 Port Managed POE+, with 100M Uplink)	\$	173.00
EN-SW10m-001	Wisenet SKY Switch SW10m (8 Port Managed POE+, with 2xGig Uplink)	\$	312.00
EN-SW18m-001	Wisenet SKY Switch SW18m (16 Port Managed POE+, with 2xGig Uplink)	\$	696.00
EN-SW26m-001	Wisenet SKY Switch SW26m (24 Port Managed POE+, with 2xGig Uplink)	\$	958.00
EN-SWSFP-001	Wisenet SKY Switch SFP Optical MMF Module (850nm, 1.25Gbps, 550m)	\$	59.00

XRN-6410DB4	8K NVR (Intel based), 64CH, No HDD, H.265/H.264/MJPEG, ARB (Automatic Recovery Backup) & Failover (N+1), 400Mbps recording/ up to 64Mbps playback throughput (RAID Mode), Dual stream recording, 16 Hot Swap HDD bays, iSCSI, redundant power, 2x HDMI dual display, Alarm I/O, 2-way audio, ONVIF, maximum camera resolution of 32MP recording/display and fisheye dewarping on WEB and CMS, Support RAID 5/6 HDD Hot Swapping is available when RAID Mode is configure. (NOTE: RAID cannot be configured with this HDD configuration).	\$	8,320.00
XRN-6410DB4-12TB	8K NVR (Intel based), 64CH, 12TB RAW, H.265/H.264/MJPEG, ARB (Automatic Recovery Backup) & Failover (N+1), 400Mbps recording/ up to 64Mbps playback throughput (RAID Mode), Dual stream recording, 16 Hot Swap HDD bays, iSCSI, redundant power, 2x HDMI dual display, Alarm I/O, 2-way audio, ONVIF, maximum camera resolution of 32MP recording/display and fisheye dewarping on WEB and CMS, Support RAID 5/6 (4TB * 3 RAID 5/6 Ready). Field configuration and setup required (recording storage - RAID 5: 8TB). HDD Hot Swapping is available when RAID Mode is configure.	\$	9,760.00
XRN-6410DB4-16TB	8K NVR (Intel based), 64CH, 16TB RAW, H.265/H.264/MJPEG, ARB (Automatic Recovery Backup) & Failover (N+1), 400Mbps recording/ up to 64Mbps playback throughput (RAID Mode), Dual stream recording, 16 Hot Swap HDD bays, iSCSI, redundant power, 2x HDMI dual display, Alarm I/O, 2-way audio, ONVIF, maximum camera resolution of 32MP recording/display and fisheye dewarping on WEB and CMS, Support RAID 5/6 (4TB * 4 RAID 5/6 Ready). Field configuration and setup required (recording storage - RAID 5: 12TB or RAID 6: 8TB). HDD Hot Swapping is available when RAID Mode is configure.	\$	10,240.00
XRN-6410DB4-20TB	8K NVR (Intel based), 64CH, 20TB RAW, H.265/H.264/MJPEG, ARB (Automatic Recovery Backup) & Failover (N+1), 400Mbps recording/ up to 64Mbps playback throughput (RAID Mode), Dual stream recording, 16 Hot Swap HDD bays, iSCSI, redundant power, 2x HDMI dual display, Alarm I/O, 2-way audio, ONVIF, maximum camera resolution of 32MP recording/display and fisheye dewarping on WEB and CMS, Support RAID 5/6 (4TB * 5 RAID 5/6 Ready). Field configuration and setup required (recording storage - RAID 5: 16TB or RAID 6: 12TB). HDD Hot Swapping is available when RAID Mode is configure.	\$	10,720.00
XRN-6410DB4-24TB	8K NVR (Intel based), 64CH, 24TB RAW, H.265/H.264/MJPEG, ARB (Automatic Recovery Backup) & Failover (N+1), 400Mbps recording/ up to 64Mbps playback throughput (RAID Mode), Dual stream recording, 16 Hot Swap HDD bays, iSCSI, redundant power, 2x HDMI dual display, Alarm I/O, 2-way audio, ONVIF, maximum camera resolution of 32MP recording/display and fisheye dewarping on WEB and CMS, Support RAID 5/6 (4TB * 6 RAID 5/6 Ready). Field configuration and setup required (recording storage - RAID 5: 20TB or RAID 6: 16TB). HDD Hot Swapping is available when RAID Mode is configure.	\$	11,200.00
XRN-6410DB4-32TB	8K NVR (Intel based), 64CH, 32TB RAW, H.265/H.264/MJPEG, ARB (Automatic Recovery Backup) & Failover (N+1), 400Mbps recording/ up to 64Mbps playback throughput (RAID Mode), Dual stream recording, 16 Hot Swap HDD bays, iSCSI, redundant power, 2x HDMI dual display, Alarm I/O, 2-way audio, ONVIF, maximum camera resolution of 32MP recording/display and fisheye dewarping on WEB and CMS, Support RAID 5/6 (8TB * 4 RAID 5/6 Ready). Field configuration and setup required (recording storage - RAID 5: 24TB or RAID 6: 20TB). HDD Hot Swapping is available when RAID Mode is configure.	\$	12,160.00
XRN-6410DB4-40TB	8K NVR (Intel based), 64CH, 40TB RAW, H.265/H.264/MJPEG, ARB (Automatic Recovery Backup) & Failover (N+1), 400Mbps recording/ up to 64Mbps playback throughput (RAID Mode), Dual stream recording, 16 Hot Swap HDD bays, iSCSI, redundant power, 2x HDMI dual display, Alarm I/O, 2-way audio, ONVIF, maximum camera resolution of 32MP recording/display and fisheye dewarping on WEB and CMS, Support RAID 5/6 (8TB * 5 RAID 5/6 Ready). Field configuration and setup required (recording storage - RAID 5: 32TB or RAID 6: 24TB). HDD Hot Swapping is available when RAID Mode is configure.	\$	13,120.00
XRN-6410DB4-48TB	8K NVR (Intel based), 64CH, 48TB RAW, H.265/H.264/MJPEG, ARB (Automatic Recovery Backup) & Failover (N+1), 400Mbps recording/ up to 64Mbps playback throughput (RAID Mode), Dual stream recording, 16 Hot Swap HDD bays, iSCSI, redundant power, 2x HDMI dual display, Alarm I/O, 2-way audio, ONVIF, maximum camera resolution of 32MP recording/display and fisheye dewarping on WEB and CMS, Support RAID 5/6 (8TB * 6 RAID 5/6 Ready). Field configuration and setup required (recording storage - RAID 5: 40TB or RAID 6: 32TB). HDD Hot Swapping is available when RAID Mode is configure.	\$	14,080.00
XRN-6410DB4-56TB	8K NVR (Intel based), 64CH, 56TB RAW, H.265/H.264/MJPEG, ARB (Automatic Recovery Backup) & Failover (N+1), 400Mbps recording/ up to 64Mbps playback throughput (RAID Mode), Dual stream recording, 16 Hot Swap HDD bays, iSCSI, redundant power, 2x HDMI dual display, Alarm I/O, 2-way audio, ONVIF, maximum camera resolution of 32MP recording/display and fisheye dewarping on WEB and CMS, Support RAID 5/6 (8TB * 7 RAID 5/6 Ready). Field configuration and setup required (recording storage - RAID 5: 48TB or RAID 6: 40TB). HDD Hot Swapping is available when RAID Mode is configure.	\$	15,040.00
XRN-6410DB4-64TB	8K NVR (Intel based), 64CH, 64TB RAW, H.265/H.264/MJPEG, ARB (Automatic Recovery Backup) & Failover (N+1), 400Mbps recording/ up to 64Mbps playback throughput (RAID Mode), Dual stream recording, 16 Hot Swap HDD bays, iSCSI, redundant power, 2x HDMI dual display, Alarm I/O, 2-way audio, ONVIF, maximum camera resolution of 32MP recording/display and fisheye dewarping on WEB and CMS, Support RAID 5/6 (8TB * 8 RAID 5/6 Ready). Field configuration and setup required (recording storage - RAID 5: 56TB or RAID 6: 48TB). HDD Hot Swapping is available when RAID Mode is configure.	\$	16,000.00
XRN-6410DB4-88TB	8K NVR (Intel based), 64CH, 88TB RAW, H.265/H.264/MJPEG, ARB (Automatic Recovery Backup) & Failover (N+1), 400Mbps recording/ up to 64Mbps playback throughput (RAID Mode), Dual stream recording, 16 Hot Swap HDD bays, iSCSI, redundant power, 2x HDMI dual display, Alarm I/O, 2-way audio, ONVIF, maximum camera resolution of 32MP recording/display and fisheye dewarping on WEB and CMS, Support RAID 5/6 (8TB * 11 RAID 5 Ready). Field configuration and setup required (recording storage - RAID 5: 72TB). HDD Hot Swapping is available when RAID Mode is configure.	\$	18,880.00
XRN-6410DB4-96TB	8K NVR (Intel based), 64CH, 96TB RAW, H.265/H.264/MJPEG, ARB (Automatic Recovery Backup) & Failover (N+1), 400Mbps recording/ up to 64Mbps playback throughput (RAID Mode), Dual stream recording, 16 Hot Swap HDD bays, iSCSI, redundant power, 2x HDMI dual display, Alarm I/O, 2-way audio, ONVIF, maximum camera resolution of 32MP recording/display and fisheye dewarping on WEB and CMS, Support RAID 5/6 (8TB * 12 RAID 5/6 Ready). Field configuration and setup required (recording storage - RAID 5: 80TB or RAID 6: 64TB). HDD Hot Swapping is available when RAID Mode is configure.	\$	19,840.00

[illegible]

XRN-3210B2-64TB	8K NVR (Intel based), 64TB RAW, 32 channels, H265,H264, MJPEG, 8 fixed internal SATA HDDs (10TB max per HDD), RAID 5 & 6, ARB (Automatic Recovery Backup), 400 Mbps recording / up to 32 Mbps playback, Dual stream recording, WiseStream technology, HDMI/VGA dual display, max. resolution of 32MP recording/display and fisheye dewarping on web and CMS, web UI 2.0 (no plugins required), AI search (Wisenet AI cameras only), QR Code. HDD Hot Swapping is available when RAID Mode is configure.	\$	12,387.00
XRN-3210B2	8K NVR (Intel based), No HDD, 32 channels, H265,H264, MJPEG, 8 fixed internal SATA HDDs (10TB max per HDD), ARB (Automatic Recovery Backup), 400 Mbps recording / up to 32 Mbps playback, Dual stream recording, WiseStream technology, HDMI/VGA dual display, max. resolution of 32MP recording/display and fisheye dewarping on web and CMS, web UI 2.0 (no plugins required), AI search (Wisenet AI cameras only), QR Code	\$	3,427.00
XRN-3210B2-12TB	8K NVR (Intel based), 12TB RAW, 32 channels, H265,H264, MJPEG, 8 fixed internal SATA HDDs (10TB max per HDD), ARB (Automatic Recovery Backup), 400 Mbps recording / up to 32 Mbps playback, Dual stream recording, WiseStream technology, HDMI/VGA dual display, max. resolution of 32MP recording/display and fisheye dewarping on web and CMS, web UI 2.0 (no plugins required), AI search (Wisenet AI cameras only), QR Code	\$	4,867.00
XRN-3210B2-16TB	8K NVR (Intel based), 16TB RAW, 32 channels, H265,H264, MJPEG, 8 fixed internal SATA HDDs (10TB max per HDD), ARB (Automatic Recovery Backup), 400 Mbps recording / up to 32 Mbps playback, Dual stream recording, WiseStream technology, HDMI/VGA dual display, max. resolution of 32MP recording/display and fisheye dewarping on web and CMS, web UI 2.0 (no plugins required), AI search (Wisenet AI cameras only), QR Code	\$	5,347.00
XRN-3210B2-24TB	8K NVR (Intel based), 24TB, 32 channels, H265,H264, MJPEG, 8 fixed internal SATA HDDs (10TB max per HDD), ARB (Automatic Recovery Backup), 400 Mbps recording / up to 32 Mbps playback, Dual stream recording, WiseStream technology, HDMI/VGA dual display, max. resolution of 32MP recording/display and fisheye dewarping on web and CMS, web UI 2.0 (no plugins required), AI search (Wisenet AI cameras only), QR Code	\$	6,307.00
XRN-3210B2-32TB	8K NVR (Intel based),32TB RAW,32 channels, H265,H264, MJPEG, 8 fixed internal SATA HDDs (10TB max per HDD), ARB (Automatic Recovery Backup), 400 Mbps recording / up to 32 Mbps playback, Dual stream recording, WiseStream technology, HDMI/VGA dual display, max. resolution of 32MP recording/display and fisheye dewarping on web and CMS, web UI 2.0 (no plugins required), AI search (Wisenet AI cameras only), QR Code	\$	7,267.00
XRN-3210B2-48TB	8K NVR (Intel based), 48TB RAW, 32 channels, H265,H264, MJPEG, 8 fixed internal SATA HDDs (10TB max per HDD), ARB (Automatic Recovery Backup), 400 Mbps recording / up to 32 Mbps playback, Dual stream recording, WiseStream technology, HDMI/VGA dual display, max. resolution of 32MP recording/display and fisheye dewarping on web and CMS, web UI 2.0 (no plugins required), AI search (Wisenet AI cameras only), QR Code	\$	9,187.00
XRN-3210B2-64TB	8K NVR (Intel based), 64TB RAW, 32 channels, H265,H264, MJPEG, 8 fixed internal SATA HDDs (10TB max per HDD), ARB (Automatic Recovery Backup), 400 Mbps recording / up to 32 Mbps playback, Dual stream recording, WiseStream technology, HDMI/VGA dual display, max. resolution of 32MP recording/display and fisheye dewarping on web and CMS, web UI 2.0 (no plugins required), AI search (Wisenet AI cameras only), QR Code	\$	11,107.00
XRN-3210B4	8K NVR (Intel based), 32CH No HDD, H.265/H.264/MJPEG, ARB (Automatic Recovery Backup) & Failover (N+1), 400Mbps recording/ up to 32Mbps playback throughput, Dual stream recording, 16 Hot Swap HDD bays, iSCSI, 2x HDMI dual display, Alarm I/O, 2-way audio, ONVIF, maximum camera resolution of 32MP recording/display and fisheye dewarping on WEB and CMS, Support RAID 5/6 (NOTE: RAID cannot be configured with this HDD configuration). HDD Hot Swapping is available when RAID Mode is configure.	\$	6,710.00
XRN-3210B4-12TB	8K NVR (Intel based), 32CH, 12TB RAW, H.265/H.264/MJPEG, ARB (Automatic Recovery Backup) & Failover (N+1), 400Mbps recording/ up to 32Mbps playback throughput (RAID Mode), Dual stream recording, 16 Hot Swap HDD bays, iSCSI, redundant power, 2x HDMI dual display, Alarm I/O, 2-way audio, ONVIF, maximum camera resolution of 32MP recording/display and fisheye dewarping on WEB and CMS, Support RAID 5/6 (4TB * 3 RAID 5/6 Ready). Field configuration and setup required (recording storage - RAID 5: 8TB). HDD Hot Swapping is available when RAID Mode is configure.	\$	8,150.00
XRN-3210B4-16TB	8K NVR (Intel based), 32CH, 16TB RAW, H.265/H.264/MJPEG, ARB (Automatic Recovery Backup) & Failover (N+1), 400Mbps recording/ up to 32Mbps playback throughput (RAID Mode), Dual stream recording, 16 Hot Swap HDD bays, iSCSI, redundant power, 2x HDMI dual display, Alarm I/O, 2-way audio, ONVIF, maximum camera resolution of 32MP recording/display and fisheye dewarping on WEB and CMS, Support RAID 5/6 (4TB * 4 RAID 5/6 Ready). Field configuration and setup required (recording storage - RAID 5: 12TB or RAID 6: 8TB). HDD Hot Swapping is available when RAID Mode is configure.	\$	8,630.00
XRN-3210B4-20TB	8K NVR (Intel based), 32CH, 20TB RAW, H.265/H.264/MJPEG, ARB (Automatic Recovery Backup) & Failover (N+1), 400Mbps recording/ up to 32Mbps playback throughput (RAID Mode), Dual stream recording, 16 Hot Swap HDD bays, iSCSI, redundant power, 2x HDMI dual display, Alarm I/O, 2-way audio, ONVIF, maximum camera resolution of 32MP recording/display and fisheye dewarping on WEB and CMS, Support RAID 5/6 (4TB * 5 RAID 5/6 Ready). Field configuration and setup required (recording storage - RAID 5: 16TB or RAID 6: 12TB). HDD Hot Swapping is available when RAID Mode is configure.	\$	9,110.00
XRN-3210B4-24TB	8K NVR (Intel based), 32CH, 24TB RAW, H.265/H.264/MJPEG, ARB (Automatic Recovery Backup) & Failover (N+1), 400Mbps recording/ up to 32Mbps playback throughput (RAID Mode), Dual stream recording, 16 Hot Swap HDD bays, iSCSI, redundant power, 2x HDMI dual display, Alarm I/O, 2-way audio, ONVIF, maximum camera resolution of 32MP recording/display and fisheye dewarping on WEB and CMS, Support RAID 5/6 (4TB * 6 RAID 5/6 Ready). Field configuration and setup required (recording storage - RAID 5: 20TB or RAID 6: 16TB). HDD Hot Swapping is available when RAID Mode is configure.	\$	9,590.00
XRN-3210B4-32TB	8K NVR (Intel based), 32CH, 32TB RAW, H.265/H.264/MJPEG, ARB (Automatic Recovery Backup) & Failover (N+1), 400Mbps recording/ up to 32Mbps playback throughput (RAID Mode), Dual stream recording, 16 Hot Swap HDD bays, iSCSI, redundant power, 2x HDMI dual display, Alarm I/O, 2-way audio, ONVIF, maximum camera resolution of 32MP recording/display and fisheye dewarping on WEB and CMS, Support RAID 5/6 (8TB * 4 RAID 5/6 Ready). Field configuration and setup required (recording storage - RAID 5: 24TB or RAID 6: 20TB). HDD Hot Swapping is available when RAID Mode is configure.	\$	10,550.00
XRN-3210B4-40TB	8K NVR (Intel based), 32CH, 40TB RAW, H.265/H.264/MJPEG, ARB (Automatic Recovery Backup) & Failover (N+1), 400Mbps recording/ up to 32Mbps playback throughput (RAID Mode), Dual stream recording, 16 Hot Swap HDD bays, iSCSI, redundant power, 2x HDMI dual display, Alarm I/O, 2-way audio, ONVIF, maximum camera resolution of 32MP recording/display and fisheye dewarping on WEB and CMS, Support RAID 5/6 (8TB * 5 RAID 5/6 Ready). Field configuration and setup required (recording storage - RAID 5: 32TB or RAID 6: 24TB). HDD Hot Swapping is available when RAID Mode is configure.	\$	11,510.00
XRN-3210B4-48TB	8K NVR (Intel based), 32CH, 48TB RAW, H.265/H.264/MJPEG, ARB (Automatic Recovery Backup) & Failover (N+1), 400Mbps recording/ up to 32Mbps playback throughput (RAID Mode), Dual stream recording, 16 Hot Swap HDD bays, iSCSI, redundant power, 2x HDMI dual display, Alarm I/O, 2-way audio, ONVIF, maximum camera resolution of 32MP recording/display and fisheye dewarping on WEB and CMS, Support RAID 5/6 (8TB * 6 RAID 5/6 Ready). Field configuration and setup required (recording storage - RAID 5: 40TB or RAID 6: 32TB). HDD Hot Swapping is available when RAID Mode is configure.	\$	12,470.00
XRN-3210B4-56TB	8K NVR (Intel based), 32CH, 56TB RAW, H.265/H.264/MJPEG, ARB (Automatic Recovery Backup) & Failover (N+1), 400Mbps recording/ up to 32Mbps playback throughput (RAID Mode), Dual stream recording, 16 Hot Swap HDD bays, iSCSI, redundant power, 2x HDMI dual display, Alarm I/O, 2-way audio, ONVIF, maximum camera resolution of 32MP recording/display and fisheye dewarping on WEB and CMS, Support RAID 5/6 (8TB * 7 RAID 5/6 Ready). Field configuration and setup required (recording storage - RAID 5: 48TB or RAID 6: 40TB).HDD Hot Swapping is available when RAID Mode is configure.	\$	13,430.00
XRN-3210B4-64TB	8K NVR (Intel based), 32CH, 64TB RAW, H.265/H.264/MJPEG, ARB (Automatic Recovery Backup) & Failover (N+1), 400Mbps recording/ up to 32Mbps playback throughput (RAID Mode), Dual stream recording, 16 Hot Swap HDD bays, iSCSI, redundant power, 2x HDMI dual display, Alarm I/O, 2-way audio, ONVIF, maximum camera resolution of 32MP recording/display and fisheye dewarping on WEB and CMS, Support RAID 5/6 (8TB * 8 RAID 5/6 Ready). Field configuration and setup required (recording storage - RAID 5: 56TB or RAID 6: 48TB).HDD Hot Swapping is available when RAID Mode is configure.	\$	14,390.00

XRN-3210B4-88TB	8K NVR (Intel based), 32CH, 88TB RAW, H.265/H.264/MJPEG, ARB (Automatic Recovery Backup) & Failover (N+1), 400Mbps recording/ up to 32Mbps playback throughput (RAID Mode), Dual stream recording, 16 Hot Swap HDD bays, iSCSI, redundant power, 2x HDMI dual display, Alarm I/O, 2-way audio, ONVIF, maximum camera resolution of 32MP recording/display and fisheye dewarping on WEB and CMS, Support RAID 5/6 (8TB * 11 RAID 5 Ready). Field configuration and setup required (recording storage - RAID 5: 72TB). HDD Hot Swapping is available when RAID Mode is configure.	\$	17,270.00
XRN-3210B4-96TB	8K NVR (Intel based), 32CH, 96TB RAW, H.265/H.264/MJPEG, ARB (Automatic Recovery Backup) & Failover (N+1), 400Mbps recording/ up to 32Mbps playback throughput (RAID Mode), Dual stream recording, 16 Hot Swap HDD bays, iSCSI, redundant power, 2x HDMI dual display, Alarm I/O, 2-way audio, ONVIF, maximum camera resolution of 32MP recording/display and fisheye dewarping on WEB and CMS, Support RAID 5/6 (8TB * 12 RAID 5/6 Ready). Field configuration and setup required (recording storage - RAID 5: 80TB or RAID 6: 64TB). HDD Hot Swapping is available when RAID Mode is configure.	\$	18,230.00
XRN-3010A	4K NVR, No HDD, supports: 64 channels, H.265/H.264/MJPEG, ARB (Automatic Recovery Backup), 8 fixed internal SATA HDDs (64TB max), e-SATA/iSCSI storage, WiseStream technology, dual monitor out, max. resolution of 12MP recording/display and fisheye dewarping on web and CMS, QR code.	\$	4,250.00
XRN-3010A-4TB	4K NVR, 4TB RAW, supports: 64 channels, H.265/H.264/MJPEG, ARB (Automatic Recovery Backup), 8 fixed internal SATA HDDs (64TB max), e-SATA/iSCSI storage, WiseStream technology, dual monitor out, max. resolution of 12MP recording/display and fisheye dewarping on web and CMS, QR code.	\$	4,970.00
XRN-3010A-8TB	4K NVR, 8TB RAW, supports: 64 channels, H.265/H.264/MJPEG, ARB (Automatic Recovery Backup), 8 fixed internal SATA HDDs (64TB max), e-SATA/iSCSI storage, WiseStream technology, dual monitor out, max. resolution of 12MP recording/display and fisheye dewarping on web and CMS, QR code.	\$	5,690.00
XRN-3010A-12TB	4K NVR, 12TB RAW, supports: 64 channels, H.265/H.264/MJPEG, ARB (Automatic Recovery Backup), 8 fixed internal SATA HDDs (64TB max), e-SATA/iSCSI storage, WiseStream technology, dual monitor out, max. resolution of 12MP recording/display and fisheye dewarping on web and CMS, QR code.	\$	6,410.00
XRN-3010A-16TB	4K NVR, 16TB RAW, supports: 64 channels, H.265/H.264/MJPEG, ARB (Automatic Recovery Backup), 8 fixed internal SATA HDDs (64TB max), e-SATA/iSCSI storage, WiseStream technology, dual monitor out, max. resolution of 12MP recording/display and fisheye dewarping on web and CMS, QR code.	\$	7,130.00
XRN-3010A-20TB	4K NVR, 20TB RAW, supports: 64 channels, H.265/H.264/MJPEG, ARB (Automatic Recovery Backup), 8 fixed internal SATA HDDs (64TB max), e-SATA/iSCSI storage, WiseStream technology, dual monitor out, max. resolution of 12MP recording/display and fisheye dewarping on web and CMS, QR code.	\$	7,850.00
XRN-3010A-24TB	4K NVR, 24TB RAW, supports: 64 channels, H.265/H.264/MJPEG, ARB (Automatic Recovery Backup), 8 fixed internal SATA HDDs (64TB max), e-SATA/iSCSI storage, WiseStream technology, dual monitor out, max. resolution of 12MP recording/display and fisheye dewarping on web and CMS, QR code.	\$	8,570.00
XRN-3010A-30TB	4K NVR, 30TB RAW, supports: 64 channels, H.265/H.264/MJPEG, ARB (Automatic Recovery Backup), 8 fixed internal SATA HDDs (64TB max), e-SATA/iSCSI storage, WiseStream technology, dual monitor out, max. resolution of 12MP recording/display and fisheye dewarping on web and CMS, QR code.	\$	9,650.00
XRN-3010A-36TB	4K NVR, 36TB RAW, supports: 64 channels, H.265/H.264/MJPEG, ARB (Automatic Recovery Backup), 8 fixed internal SATA HDDs (64TB max), e-SATA/iSCSI storage, WiseStream technology, dual monitor out, max. resolution of 12MP recording/display and fisheye dewarping on web and CMS, QR code.	\$	10,730.00
XRN-3010A-40TB	4K NVR, 40TB RAW, supports: 64 channels, H.265/H.264/MJPEG, ARB (Automatic Recovery Backup), 8 fixed internal SATA HDDs (64TB max), e-SATA/iSCSI storage, WiseStream technology, dual monitor out, max. resolution of 12MP recording/display and fisheye dewarping on web and CMS, QR code.	\$	11,450.00
XRN-3010A-48TB	4K NVR, 48TB RAW, supports: 64 channels, H.265/H.264/MJPEG, ARB (Automatic Recovery Backup), 8 fixed internal SATA HDDs (64TB max), e-SATA/iSCSI storage, WiseStream technology, dual monitor out, max. resolution of 12MP recording/display and fisheye dewarping on web and CMS, QR code.	\$	12,890.00
XRN-3010A-64TB	4K NVR, 64TB RAW, supports: 64 channels, H.265/H.264/MJPEG, ARB (Automatic Recovery Backup), 8 fixed internal SATA HDDs (64TB max), e-SATA/iSCSI storage, WiseStream technology, dual monitor out, max. resolution of 12MP recording/display and fisheye dewarping on web and CMS, QR code.	\$	15,770.00
XRN-2010A	4K NVR, No HDD, that supports: up to 32 channels, H.265/H.264/MJPEG, ARB (Automatic Recovery Backup) & Failover (N+1), 8 fixed internal SATA HDDs (with a maximum internal storage capacity of 48TB), e-SATA/iSCSI storage, WiseStream compression technology, dual monitor video out, maximum camera resolution of 12MP recording/display and fisheye dewarping on web and CMS, QR code.	\$	2,819.00
XRN-2010A-2TB	4K NVR, 2TB RAW, that supports: up to 32 channels, H.265/H.264/MJPEG, ARB (Automatic Recovery Backup) & Failover (N+1), 8 fixed internal SATA HDDs (with a maximum internal storage capacity of 48TB), e-SATA/iSCSI storage, WiseStream compression technology, dual monitor video out, maximum camera resolution of 12MP recording/display and fisheye dewarping on web and CMS, QR code.	\$	3,179.00
XRN-2010A-4TB	4K NVR, 4TB RAW, that supports: up to 32 channels, H.265/H.264/MJPEG, ARB (Automatic Recovery Backup) & Failover (N+1), 8 fixed internal SATA HDDs (with a maximum internal storage capacity of 48TB), e-SATA/iSCSI storage, WiseStream compression technology, dual monitor video out, maximum camera resolution of 12MP recording/display and fisheye dewarping on web and CMS, QR code.	\$	3,539.00
XRN-2010A-6TB	4K NVR, 6TB RAW, that supports: up to 32 channels, H.265/H.264/MJPEG, ARB (Automatic Recovery Backup) & Failover (N+1), 8 fixed internal SATA HDDs (with a maximum internal storage capacity of 48TB), e-SATA/iSCSI storage, WiseStream compression technology, dual monitor video out, maximum camera resolution of 12MP recording/display and fisheye dewarping on web and CMS, QR code.	\$	3,899.00
XRN-2010A-8TB	4K NVR, 8TB RAW, that supports: up to 32 channels, H.265/H.264/MJPEG, ARB (Automatic Recovery Backup) & Failover (N+1), 8 fixed internal SATA HDDs (with a maximum internal storage capacity of 48TB), e-SATA/iSCSI storage, WiseStream compression technology, dual monitor video out, maximum camera resolution of 12MP recording/display and fisheye dewarping on web and CMS, QR code.	\$	4,259.00
XRN-2010A-12TB	4K NVR, 12TB RAW, that supports: up to 32 channels, H.265/H.264/MJPEG, ARB (Automatic Recovery Backup) & Failover (N+1), 8 fixed internal SATA HDDs (with a maximum internal storage capacity of 48TB), e-SATA/iSCSI storage, WiseStream compression technology, dual monitor video out, maximum camera resolution of 12MP recording/display and fisheye dewarping on web and CMS, QR code.	\$	4,979.00
XRN-2010A-16TB	4K NVR, 16TB RAW, that supports: up to 32 channels, H.265/H.264/MJPEG, ARB (Automatic Recovery Backup) & Failover (N+1), 8 fixed internal SATA HDDs (with a maximum internal storage capacity of 48TB), e-SATA/iSCSI storage, WiseStream compression technology, dual monitor video out, maximum camera resolution of 12MP recording/display and fisheye dewarping on web and CMS, QR code.	\$	5,699.00
XRN-2010A-20TB	4K NVR, 20TB RAW, that supports: up to 32 channels, H.265/H.264/MJPEG, ARB (Automatic Recovery Backup) & Failover (N+1), 8 fixed internal SATA HDDs (with a maximum internal storage capacity of 48TB), e-SATA/iSCSI storage, WiseStream compression technology, dual monitor video out, maximum camera resolution of 12MP recording/display and fisheye dewarping on web and CMS, QR code.	\$	6,419.00
XRN-2010A-24TB	4K NVR, 24TB RAW, that supports: up to 32 channels, H.265/H.264/MJPEG, ARB (Automatic Recovery Backup) & Failover (N+1), 8 fixed internal SATA HDDs (with a maximum internal storage capacity of 48TB), e-SATA/iSCSI storage, WiseStream compression technology, dual monitor video out, maximum camera resolution of 12MP recording/display and fisheye dewarping on web and CMS, QR code.	\$	7,139.00
XRN-2010A-30TB	4K NVR, 30TB RAW, that supports: up to 32 channels, H.265/H.264/MJPEG, ARB (Automatic Recovery Backup) & Failover (N+1), 8 fixed internal SATA HDDs (with a maximum internal storage capacity of 48TB), e-SATA/iSCSI storage, WiseStream compression technology, dual monitor video out, maximum camera resolution of 12MP recording/display and fisheye dewarping on web and CMS, QR code.	\$	8,219.00
XRN-2010A-36TB	4K NVR, 36TB RAW, that supports: up to 32 channels, H.265/H.264/MJPEG, ARB (Automatic Recovery Backup) & Failover (N+1), 8 fixed internal SATA HDDs (with a maximum internal storage capacity of 48TB), e-SATA/iSCSI storage, WiseStream compression technology, dual monitor video out, maximum camera resolution of 12MP recording/display and fisheye dewarping on web and CMS, QR code.	\$	9,299.00

[illegible]

QRN-820S-6TB	4K NVR, 6TB RAW, supports: 8 PoE ports (PoE Budget 65W), H.265/H.264/MJPEG, ARB (Automatic Recovery Backup), 1 fixed internal SATA HDDs (6TB max), max. resolution of 8MP recording/display, QR code connect, Dual track recording, Advanced GUI	\$	1,840.00
XRN-410S	4K NVR, no HDD, supports: 4 channels with 4 PoE/PoE+ ports, H.265/H.264/MJPEG, ARB (Automatic Recovery Backup), 1 fixed internal SATA HDDs (6TB max), WiseStream technology, max. resolution of 8MP recording/display and fisheye dewarping on web and CMS.	\$	585.00
XRN-410S-1TB	4K NVR, 1TB RAW, supports: 4 channels with 4 PoE/PoE+ ports, H.265/H.264/MJPEG, ARB (Automatic Recovery Backup), 1 fixed internal SATA HDDs (6TB max), WiseStream technology, max. resolution of 8MP recording/display and fisheye dewarping on web and CMS.	\$	765.00
XRN-410S-2TB	4K NVR, 2TB RAW, supports: 4 channels with 4 PoE/PoE+ ports, H.265/H.264/MJPEG, ARB (Automatic Recovery Backup), 1 fixed internal SATA HDDs (6TB max), WiseStream technology, max. resolution of 8MP recording/display and fisheye dewarping on web and CMS.	\$	945.00
XRN-410S-4TB	4K NVR, 4TB RAW, supports: 4 channels with 4 PoE/PoE+ ports, H.265/H.264/MJPEG, ARB (Automatic Recovery Backup), 1 fixed internal SATA HDDs (6TB max), WiseStream technology, max. resolution of 8MP recording/display and fisheye dewarping on web and CMS.	\$	1,305.00
XRN-410S-6TB	4K NVR, 6TB RAW, supports: 4 channels with 4 PoE/PoE+ ports, H.265/H.264/MJPEG, ARB (Automatic Recovery Backup), 1 fixed internal SATA HDDs (6TB max), WiseStream technology, max. resolution of 8MP recording/display and fisheye dewarping on web and CMS.	\$	1,665.00
XRN-420S	4K NVR (Intel based), 4CH with 4 PoE/PoE+ ports (PoE Budget 50W), H265,H264, MJPEG, 1 fixed internal SATA HDDs (6TB max), ARB (Automatic Recovery Backup), 50 Mbps recording / up to 32 Mbps playback, Dual stream recording, WiseStream technology, HDMI/VGA dual display, max. resolution of 8MP recording/display, AI search (Wisenet AI cameras only), QR Code	\$	587.00
XRN-420S-2TB	4K NVR (Intel based) 2TB RAW, 4CH with 4 PoE/PoE+ ports (PoE Budget 50W), H265,H264, MJPEG, 1 fixed internal SATA HDDs (6TB max), ARB (Automatic Recovery Backup), 50 Mbps recording / up to 32 Mbps playback, Dual stream recording, WiseStream technology, HDMI/VGA dual display, max. resolution of 8MP recording/display, AI search (Wisenet AI cameras only), QR Code	\$	947.00
XRN-420S-4TB	4K NVR (Intel based) 4TB RAW, 4CH with 4 PoE/PoE+ ports (PoE Budget 50W), H265,H264, MJPEG, 1 fixed internal SATA HDDs (6TB max), ARB (Automatic Recovery Backup), 50 Mbps recording / up to 32 Mbps playback, Dual stream recording, WiseStream technology, HDMI/VGA dual display, max. resolution of 8MP recording/display, AI search (Wisenet AI cameras only), QR Code	\$	1,307.00
XRN-420S-6TB	4K NVR (Intel based) 6TB RAW, 4CH with 4 PoE/PoE+ ports (PoE Budget 50W), H265,H264, MJPEG, 1 fixed internal SATA HDDs (6TB max), ARB (Automatic Recovery Backup), 50 Mbps recording / up to 32 Mbps playback, Dual stream recording, WiseStream technology, HDMI/VGA dual display, max. resolution of 8MP recording/display, AI search (Wisenet AI cameras only), QR Code	\$	1,667.00
QRN-430S	4K NVR (Intel based), 4CH with 4 PoE/PoE+ ports (PoE Budget 35W), H265,H264, MJPEG, 1 fixed internal SATA HDDs (6TB max), ARB (Automatic Recovery Backup), 40 Mbps recording / up to 32 Mbps playback, Dual stream recording, WiseStream technology, 4K HDMI display, max. resolution of 8MP recording/display, QR Code	\$	517.00
QRN-430S-2TB	4K NVR (Intel based), 2TB RAW, 4CH with 4 PoE/PoE+ ports (PoE Budget 35W), H265,H264, MJPEG, 1 fixed internal SATA HDDs (6TB max), ARB (Automatic Recovery Backup), 40 Mbps recording / up to 32 Mbps playback, Dual stream recording, WiseStream technology, 4K HDMI display, max. resolution of 8MP recording/display, QR Code	\$	877.00
QRN-430S-4TB	4K NVR (Intel based), 4TB RAW, 4CH with 4 PoE/PoE+ ports (PoE Budget 35W), H265,H264, MJPEG, 1 fixed internal SATA HDDs (6TB max), ARB (Automatic Recovery Backup), 40 Mbps recording / up to 32 Mbps playback, Dual stream recording, WiseStream technology, 4K HDMI display, max. resolution of 8MP recording/display, QR Code	\$	1,237.00
QRN-430S-6TB	4K NVR (Intel based), 6TB RAW, 4CH with 4 PoE/PoE+ ports (PoE Budget 35W), H265,H264, MJPEG, 1 fixed internal SATA HDDs (6TB max), ARB (Automatic Recovery Backup), 40 Mbps recording / up to 32 Mbps playback, Dual stream recording, WiseStream technology, 4K HDMI display, max. resolution of 8MP recording/display, QR Code	\$	1,665.00

SPE-1620	Encoder, 16CH H.265/H.264/MJPEG, 15fps @ 2MP, AHD/CVI/TVI/CVBS compatible, RS-485/422 Interface, Pelco C when using CVBS or ACP up-coax protocol @ AHD, ONVIF protocol support, HDMI output, I/O 16/4, Audio in/out 4/1, 12VDC	\$	1,135.00
SPE-1610	Encoder, 16CH H.264/MJPEG, 30fps @ 2MP or lower and 15 fps @ 4MP, AHD/CVI/TVI/CVBS compatible, RS-485/422 Interface, Pelco C when using CVBS or ACP up-coax protocol @ AHD, ONVIF protocol support, HDMI output, I/O 16/4, Audio in/out 4/1, 12VDC	\$	1,365.00
SPE-420	Encoder, 4CH H.265/H.264/MJPEG, 5MP : 12fps/CH, 4MP : 15fps/CH, 1080p : 30fps/CH, 720p/WD1/4CIF/CIF : 30fps, AHD/CVI/TVI/CVBS compatible, RS-485/422 Interface, Pelco C when using CVBS or ACP up-coax protocol @ AHD, ONVIF protocol support, HDMI output, I/O 4/2, Audio in/out 4/1, DC12V, PoE(IEEE 802.3af)	\$	535.00
SPE-410	Encoder, 4CH H.264/MJPEG, 30fps @ 2MP or lower and 15 fps @ 4MP, AHD/CVI/TVI/CVBS compatible, RS-485/422 Interface, Pelco C when using CVBS or ACP up-coax protocol @ AHD, ONVIF protocol support, HDMI output, I/O 4/2, Audio in/out 4/1, 12VDC/ PoE	\$	535.00
SPE-110	Encoder, 1CH H.264/MJPEG, 30fps @ 2MP or lower and 15fps @ 4MP, AHD/CVI/TVI/CVBS compatible, RS-485/422 Interface, Pelco C when using CVBS or ACP up-coax protocol @ AHD, ONVIF protocol support, 12VDC/ PoE	\$	260.00
SPD-151	Video decoding up to 48 cameras on HDMI / VGA, 1 camera decoding on BNC, Max. 4K resolution@HDMI, Max. 1080p@VGA, Various view mode (HDMI 1 / 2x2 / 3x3 / 4x4 / 5x5 / 6x6 (32Ch Only,VGA 1 / 2x2 / 3x3 / 4x4,BNC 1 Tile merge support), 12V DC, PoE, Up to 49CH, H.265 / H.264 / MJPEG codec, Layout Sequence Support, Management using Web-Viewer	\$	800.00
SPD-150	Decoder, 49CH on 3 different monitors: HDMI 32 channel max, VGA 16 channel max, BNC 1 channel, H.265, H.264, MJPEG, Onvif support, decode up to 12MP, configurable through the attached monitor only no web based configuration, PoE or 12VDC	\$	800.00

SWT-G11MGHP	Hardened 11 Port - 2 x 100/1000/2500FX + 1 x 100/1000FX SFP Ports and 8 x 10/100/1000TX Ports Managed Switch, four 1000Mbps TX with 30W PoE, four 1000Mbps TX Combo Ports with 60W PoE, Hardened 48VDC 480Watt (10A) DIN Rail High Temp Power Supply (-40°C to +71°C With -40°C Start-Up) Included	\$	3,850.00
SWT-F11MGHP	Hardened 3 FX SFP 100/1000/2500Mbps FX + 8 Port 10/100Mbps TX Ports Managed Switch 60 Watt PoE, Hardened 48VDC 480Watt (10A) DIN Rail High Temp Power Supply (-40°C to +71°C With -40°C Start-Up) Included	\$	3,100.00
SBP-300HF	RJ-45 to Fiber mounting accessory for PTZ SNP-6320H/5430H	\$	269.00
SBP-302HF	RJ-45 to Fiber mounting accessory for PTZ XNP-6370RH, PNP-9200RH	\$	269.00
SBP-303HF	RJ-45 to Fiber mounting accessory for PTZ XNP-6320H/6321H, XNP-6550RH and QNP-6230H	\$	269.00
TMC-FSTM1ACM-A	Hardened mini media fiber converter (A),100mbps, ST connector, multi-mode, 1 fiber , power supply included (not hardened), TMC-FSTM1-B required to work as a pair	\$	730.00
TMC-FSTS1ACM-A	Hardened mini media fiber converter (A),100mbps, ST connector, single-mode, 1 fiber, power supply included (not hardened), TMC-FSTS1-B required to work as a pair	\$	850.00
TMC-FSTM1POEM-A	Hardened media fiber converter (A), 100mbps, ST Connector, multi-mode, 1 fiber, PoE+ output, 48V power supply included (not hardened), TMC-FSTM1-B required to work as a pair	\$	900.00
TMC-FSTS1POEM-A	Hardened media fiber converter (A), 100mbps, ST Connector, single-mode, 1 fiber, PoE+ output, 48V power supply included (not hardened), TMC-FSTS1-B required to work as a pair	\$	1,025.00
TMC-FSTM1-B	Hardened media fiber converter (B), cage mountable, 100mbps, ST connector, multi-mode, 1 fiber, power supply included, TMC-FSTM1ACM-A or TMC-FSTM1POEM-A required to work as a pair	\$	730.00
TMC-FSTS1-B	Hardened media fiber converter (B), cage mountable, 100mbps, ST connector, single-mode, 1 fiber, power supply included, TMC-FSTS1ACM-A or TMC-FSTS1POEM-A required to work as a pair	\$	850.00
TMC-FSCM1ACM-A	Hardened mini media fiber converter (A),100mbps, SC connector, multi-mode, 1 fiber , power supply included (not hardened), TMC-FSCM1-B required to work as a pair	\$	730.00
TMC-FSCS1ACM-A	Hardened mini media fiber converter (A),100mbps, SC connector, single-mode, 1 fiber, power supply included (not hardened), TMC-FSCS1-B required to work as a pair	\$	850.00

TMC-FSCM1POEM-A	Hardened media fiber converter (A), 100Mbps, SC Connector, multi-mode, 1 fiber, PoE+ output, 48V power supply included (not hardened), TMC-FSCM1-B required to work as a pair	\$	900.00
TMC-FSCS1POEM-A	Hardened media fiber converter (A), 100Mbps, SC Connector, single-mode, 1 fiber, PoE+ output, 48V power supply included (not hardened), TMC-FSCS1-B required to work as a pair	\$	1,025.00
TMC-FSCM1-B	Hardened media fiber converter (B), cage mountable, 100Mbps, SC connector, multi-mode, 1 fiber, power supply included, TMC-FSCM1ACM-A or TMC-FSCM1POEM-A required to work as a pair	\$	730.00
TMC-FSCS1-B	Hardened media fiber converter (B), cage mountable, 100Mbps, SC connector, single-mode, 1 fiber, power supply included, TMC-FSCS1ACM-A or TMC-FSCS1POEM-A required to work as a pair	\$	850.00
TMC-GSFPM	10/100/1000Mbps Multi-Rate media converter, SFP, 100FX/1000FX selectable, small size, SFP module required	\$	1,125.00
TMC-GSFP	10/100/1000Mbps Multi-Rate media converter, SFP, 100FX/1000FX selectable, SFP module required	\$	1,125.00
TMC-GSFPPOEM	10/100/1000Mbps Multi-Rate media converter, SFP, 100FX/1000FX selectable, small size, PoE+, SFP module required	\$	1,225.00
TMC-FSFPPOE30M	Hardened 100Mbps Media Converter, SFP, 48V POE, Power Supply Included. 30w output, SFP module required	\$	760.00
SFP-GRJC	Copper 10/100/1000Mbps RJ45, MSA Compliant	\$	225.00
SFP-FLCM202	100Mbps, 1310nm, 2km, LC, 2 Fiber, Multi Mode, MSA Compliant	\$	160.00
SFP-FLCS220	100Mbps, 1310nm, 20km, LC, 2 Fiber, Single Mode, MSA Compliant	\$	170.00
SFP-FSCM102-A	100Mbps, 1310nm, 2km, SC, 1 Fiber, Pair with SFP-FSCM102-B, Multi Mode, MSA Compliant	\$	260.00
SFP-FSCM102-B	100Mbps, 1550nm, 2km, SC, 1 Fiber, Pair with SFP-FSCM102-A, Multi Mode, MSA Compliant	\$	260.00
SFP-FSCS120-A	100Mbps, 1310nm, 20km, SC, 1 Fiber, Pair with SFP-FSCM102-B, Single Mode, MSA Compliant	\$	260.00
SFP-FSCS120-B	100Mbps, 1550nm, 20km, SC, 1 Fiber, Pair with SFP-FSCM102-A, Single Mode, MSA Compliant	\$	260.00
SFP-GLCS215	1000Mbps, 1310nm, 15km, LC, 2 Fiber, Single Mode, MSA Compliant	\$	160.00
SFP-GLCS120-A	1000Mbps, 1310nm, 20km, LC, 1 Fiber, Pair with SFP-GLCS120-B, Single Mode, MSA Compliant	\$	385.00
SFP-GLCS120-B	1000Mbps, 1550nm, 20km, LC, 1 Fiber, Pair with SFP-GLCS120-A, Single Mode, MSA Compliant	\$	385.00
SFP-GLCM202	1000Mbps 1310nm, 2km, 2 Fiber, LC, Multi Mode, MSA Compliant	\$	325.00
SBP-C14	14 slot card cage rack, power supply included	\$	1,025.00
SBP-C03	3 slot card cage rack, power supply included	\$	580.00
SBP-C14PS1	90-264 VAC 50/60hz power supply for SBP-C14	\$	580.00
SBP-C14BP1	1 slot blank filler panel for SBP-C14 card cage	\$	35.00
SBP-C14BP3	3 slot blank filler panel for SBP-C14 card cage	\$	35.00
SBP-UDR	Universal DIN-Rail mount adapter kit that allow the Hanwha product to be mounted on the adaptor in a vertical axis configuration	\$	35.00
TEU-F01	Single-Channel Ethernet over UTP with Pass-through PoE	\$	470.00
TEC-F01	Single-Channel Ethernet over COAX with Pass-through PoE	\$	440.00
TEU-F04	Four-Channel Ethernet over UTP with Pass-through PoE	\$	1,700.00
TEC-F04	Four-Channel Ethernet over COAX with Pass-through PoE	\$	1,650.00
TEU-F16	Sixteen-Channel Ethernet over UTP with Pass-through PoE	\$	4,900.00
TEC-F16	Sixteen-Channel Ethernet over COAX with Pass-through PoE	\$	4,850.00
TER-F01	100 Meter Ethernet Repeater Pass-Through PoE Power	\$	385.00
TER-F01PD	100 Meter Ethernet Repeater External Power	\$	385.00

HCF-8010V	5MP (2560x1944) resolution, 20FPS @5MP, BLC, Day & Night (ICR), Digital Wide Dynamic Range, Coaxial communication (HD / SD mode), Selectable universal output (TVI / AHD / CVBS), IP66, IK10, Power 12VDC/24VAC	\$	399.00
HCB-7000A	Wisenet HD+ 4MP box camera, AHD or CVBS formats are available, RS485 /Coaxial Control, true D/N, 24VAC/12VDC (Require 4MP or higher CS Mount Lens).	\$	180.00
HCO-7070RA	Wisenet HD+ 4MP IR bullet camera, AHD or CVBS formats are available, manual vari-focal Lens (3.1X) (3.2-10mm), true D/N, 24VAC/12VDC, IR distance 98 feet, IP66/IK10.	\$	300.00
HCO-7010RA	Wisenet HD+ 4MP IR bullet camera, AHD or CVBS formats are available, 2.8 mm fixed lens, true D/N, 12VDC, IR distance 65 feet, IP66/IK10.	\$	200.00
HCO-7020RA	Wisenet HD+ 4MP IR bullet camera, AHD or CVBS formats are available, 4.0 mm fixed lens, true D/N, 12VDC, IR distance 82 feet, IP66/IK10.	\$	200.00
HCO-7030RA	Wisenet HD+ 4MP IR bullet camera, AHD or CVBS formats are available, 6.0 mm fixed lens, true D/N, 12VDC, IR distance 98 feet, IP66/IK10.	\$	200.00
HCV-7070RA	Wisenet HD+ 4MP IR outdoor dome camera, AHD or CVBS formats are available, manual vari-focal Lens (3.1X) (3.2-10mm), true D/N, 24VAC/12VDC, IR distance 98 feet, IP66/IK10.	\$	300.00
HCV-7010RA	Wisenet HD+ 4MP IR outdoor dome camera, AHD or CVBS formats are available, 2.8 mm fixed lens, true D/N, 12VDC, IR distance 65 feet, IP66/IK10.	\$	200.00
HCV-7020RA	Wisenet HD+ 4MP IR outdoor dome camera, AHD or CVBS formats are available, 4.0 mm fixed lens, true D/N, 12VDC, IR distance 82 feet, IP66/IK10.	\$	200.00
HCV-7030RA	Wisenet HD+ 4MP IR outdoor dome camera, AHD or CVBS formats are available, 6.0 mm fixed lens, true D/N, 12VDC, IR distance 98 feet, IP66/IK10.	\$	200.00
HCD-7070RA	Wisenet HD+ 4MP IR indoor dome camera, AHD or CVBS formats are available, manual vari-focal Lens (3.1X) (3.2-10mm), true D/N, 24VAC/12VDC, IR distance 65 feet.	\$	270.00
HCD-7010RA	Wisenet HD+ 4MP IR indoor dome camera, AHD or CVBS formats are available, 2.8 mm fixed lens, true D/N, 12VDC, IR distance 65 feet.	\$	180.00
HCD-7020RA	Wisenet HD+ 4MP IR indoor dome camera, AHD or CVBS formats are available, 4.0 mm fixed lens, true D/N, 12VDC, IR distance 82 feet.	\$	180.00
HCD-7030RA	Wisenet HD+ 4MP IR indoor dome camera, AHD or CVBS formats are available, 6.0 mm fixed lens, true D/N, 12VDC, IR distance 98 feet.	\$	180.00
HCZ-6321	Wisenet HD+ 2MP zoom box, AHD or CVBS formats are available, true WDR (120dB), 32X optical zoom, RS485 /Coaxial Control(ACP), true D/N, 12VDC	\$	575.00
HCB-6000	Wisenet HD+ 2MP, Full HD(1080p) 30fps box camera, AHD/TVI/CVI/CVBS, 120 dB true WDR, RS485 /Coaxial Control, true D/N, 24VAC/12VDC (Require 2MP or higher CS Mount Lens)	\$	180.00
HCB-6001	Wisenet HD+ 2MP, Full HD(1080p) 30fps box camera, AHD/TVI/CVI/CVBS, 120 dB true WDR, RS485 /Coaxial Control, simple focus, true D/N, 24VAC/12VDC (Require 2MP or higher CS Mount Lens)	\$	215.00
HCD-6070R	Wisenet HD+ 2MP, Full HD(1080p) 30fps IR indoor dome camera, AHD/TVI/CVI/CVBS, manual Vari-focal Lens (3.1X) (3.2-10mm), 120 dB true WDR, true D/N, 24VAC/12VDC, IR distance 65 feet	\$	270.00
HCD-6080R	Wisenet HD+ 2MP, Full HD(1080p) 30fps IR indoor dome camera, AHD/TVI/CVI/CVBS, motorized vari-focal lens (3.1X) (3.2-10mm), 120 dB true WDR, true D/N, 24VAC/12VDC, IR distance 65 feet	\$	320.00
HCD-6010	Wisenet HD+ 2MP indoor dome camera, AHD, CVI, TVI, CVBS formats are available, 2.8 mm fixed lens, true D/N, 12VDC	\$	180.00
HCD-6020R	Wisenet HD+ 2MP IR indoor dome camera, AHD, CVI, TVI, CVBS formats are available, 4.0 mm fixed lens, true D/N, 12VDC	\$	210.00
HCV-6070R	Wisenet HD+ 2MP, Full HD(1080p) 30fps IR outdoor dome camera, AHD/TVI/CVI/CVBS, manual Vari-focal Lens (3.1X) (3.2-10mm), 120 dB true WDR, true D/N, 24VAC/12VDC, IR distance 98 feet, IP66/IK10	\$	300.00
HCV-6080R	Wisenet HD+ 2MP, Full HD(1080p) 30fps IR outdoor dome camera, AHD/TVI/CVI/CVBS, motorized vari-focal lens (3.1X) (3.2-10mm), 120 dB true WDR, true D/N, 24VAC/12VDC, IR distance 98 feet, IP66/IK10	\$	350.00
HCO-6070R	Wisenet HD+ 2MP, Full HD(1080p) 30fps IR outdoor bullet camera, AHD/TVI/CVI/CVBS, manual Vari-focal Lens (3.1X) (3.2-10mm), 120 dB true WDR, true D/N, 24VAC/12VDC, IR distance 98 feet, IP66/IK10	\$	300.00
HCO-6020R	Wisenet HD+ 2MP IR bullet camera, AHD, CVI, TVI, CVBS formats are available, 4.0 mm fixed lens, true D/N, 12VDC	\$	210.00
HCO-6080R	Wisenet HD+ 2MP, Full HD(1080p) 30fps IR outdoor bullet camera, AHD/TVI/CVI/CVBS, motorized vari-focal lens (3.1X) (3.2-10mm), 120 dB true WDR, true D/N, 24VAC/12VDC, IR distance 98 feet, IP66/IK10	\$	350.00
HCP-6320A	Wisenet HD+ 2MP, Full HD(1080p) 30fps PTZ camera, Optical zoom lens 32X (4.44-142.6mm), true WDR 120dB, RS485/Up coax (ACP protocol only) PTZ control, true D/N, 24VAC.	\$	1,270.00

HCP-6320HA	Wisenet HD+ 2MP, Full HD(1080p) 30fps PTZ camera, Optical zoom lens 32X (4.44~142.6mm), RS485/Up coax (ACP protocol only) PTZ control, true WDR 120dB, true D/N, 24VAC, IP66 IK10.	\$	1,470.00
SCO-6085R	Wisenet HD+ 2MP, Full HD(1080p) 30fps IR bullet camera, 1/2.8" 2M CMOS, vari-focal Lens (3.1X) (3.2-10mm), 60dB DWDR, Coaxial Control, true D/N, 24VAC/12VDC, IR distance 98.43 feet, IP66 IK10	\$	250.00
SCV-6085R	Wisenet HD+ 2MP, Full HD(1080p) 30fps IR vandal dome camera, 1/2.8" 2M CMOS, Vari-focal Lens (3.1X) (3.2-10mm), 60dB DWDR, true D/N, 24VAC/12VDC, IR distance 98.42 feet, IP66 IK10	\$	250.00
SCD-6085R	Wisenet HD+ 2MP, Full HD(1080p) 30fps IR dome camera, 1/2.8" 2M CMOS, vari-focal Lens (3.1X) (3.2-10mm), 60dB DWDR, Coaxial Control, true D/N, 24VAC/12VDC, IR distance 65.62 feet	\$	230.00
SCB-6005	Wisenet HD+ 2MP, Full HD(1080p) 30fps, 1/2.8" 2M CMOS, 60dB DWDR, RS485 /Coaxial Control, true D/N, 24VAC/12VDC (Requires 2MP or higher CS Mount Lens)	\$	159.00

HRX-1632	Wisenet HD+ Pentabrid DVR AHD (up to 4MP), TVI (up to 4MP), CVI (up to 4MP), CVBS and IP (up to 8MP), Max. Analog 16CH + NW 8CH, up to 8MP, 15/12fps@4MP, 15/12fps@2MP recording (frame rate at higher resolutions will vary), triple codec H.265/H.264/MJPEG, Recording Bandwidth Max. 80Mbps, Playback Bandwidth 32Mbps. 16CH audio input/ 1CH audio output, 16 alarm input and 4 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code , Up to 4 SATA HDDs (6TB/HDD)	\$	1,134.00
HRX-1632-4TB	Wisenet HD+ Pentabrid DVR AHD (up to 4MP), - 4TB Raw Storage.TVI (up to 4MP), CVI (up to 4MP), CVBS and IP (up to 8MP), Max. Analog 16CH + NW 8CH, up to 8MP, 15/12fps@4MP, 15/12fps@2MP recording (frame rate at higher resolutions will vary), triple codec H.265/H.264/MJPEG, Recording Bandwidth Max. 80Mbps, Playback Bandwidth 32Mbps. 16CH audio input/ 1CH audio output, 16 alarm input and 4 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code , Up to 4 SATA HDDs (6TB/HDD)	\$	1,614.00
HRX-1632-6TB	Wisenet HD+ Pentabrid DVR AHD (up to 4MP), - 6TB Raw Storage.TVI (up to 4MP), CVI (up to 4MP), CVBS and IP (up to 8MP), Max. Analog 16CH + NW 8CH, up to 8MP, 15/12fps@4MP, 15/12fps@2MP recording (frame rate at higher resolutions will vary), triple codec H.265/H.264/MJPEG, Recording Bandwidth Max. 80Mbps, Playback Bandwidth 32Mbps. 16CH audio input/ 1CH audio output, 16 alarm input and 4 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code , Up to 4 SATA HDDs (6TB/HDD)	\$	2,094.00
HRX-1632-8TB	Wisenet HD+ Pentabrid DVR AHD (up to 4MP), - 8TB Raw Storage.TVI (up to 4MP), CVI (up to 4MP), CVBS and IP (up to 8MP), Max. Analog 16CH + NW 8CH, up to 8MP, 15/12fps@4MP, 15/12fps@2MP recording (frame rate at higher resolutions will vary), triple codec H.265/H.264/MJPEG, Recording Bandwidth Max. 80Mbps, Playback Bandwidth 32Mbps. 16CH audio input/ 1CH audio output, 16 alarm input and 4 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code , Up to 4 SATA HDDs (6TB/HDD)	\$	2,574.00
HRX-1632-12TB	Wisenet HD+ Pentabrid DVR AHD (up to 4MP), - 12TB Raw Storage.TVI (up to 4MP), CVI (up to 4MP), CVBS and IP (up to 8MP), Max. Analog 16CH + NW 8CH, up to 8MP, 15/12fps@4MP, 15/12fps@2MP recording (frame rate at higher resolutions will vary), triple codec H.265/H.264/MJPEG, Recording Bandwidth Max. 80Mbps, Playback Bandwidth 32Mbps. 16CH audio input/ 1CH audio output, 16 alarm input and 4 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code , Up to 4 SATA HDDs (6TB/HDD)	\$	3,054.00
HRX-1632-16TB	Wisenet HD+ Pentabrid DVR AHD (up to 4MP), - 16TB Raw Storage.TVI (up to 4MP), CVI (up to 4MP), CVBS and IP (up to 8MP), Max. Analog 16CH + NW 8CH, up to 8MP, 15/12fps@4MP, 15/12fps@2MP recording (frame rate at higher resolutions will vary), triple codec H.265/H.264/MJPEG, Recording Bandwidth Max. 80Mbps, Playback Bandwidth 32Mbps. 16CH audio input/ 1CH audio output, 16 alarm input and 4 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code , Up to 4 SATA HDDs (6TB/HDD)	\$	3,534.00
HRX-1632-24TB	Wisenet HD+ Pentabrid DVR AHD (up to 4MP), - 24TB Raw Storage.TVI (up to 4MP), CVI (up to 4MP), CVBS and IP (up to 8MP), Max. Analog 16CH + NW 8CH, up to 8MP, 15/12fps@4MP, 15/12fps@2MP recording (frame rate at higher resolutions will vary), triple codec H.265/H.264/MJPEG, Recording Bandwidth Max. 80Mbps, Playback Bandwidth 32Mbps. 16CH audio input/ 1CH audio output, 16 alarm input and 4 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code , Up to 4 SATA HDDs (6TB/HDD)	\$	4,014.00
HRX-1621	Wisenet HD+ Pentabrid DVR AHD (up to 8MP), TVI (up to 8MP), CVI (up to 5MP), CVBS and IP (up to 8MP), 16CH analog + 2CH IP and up to 18CH IP, recording 1080p @ 30fps/ channel (frame rate at higher resolutions will vary), triple codec H.265/H.264/MJPEG, 70Mbps throughput on analog and 51mbps throughput on IP cameras), 16CH audio input/ 1CH audio output, 16 alarm input and 4 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code , Up to 8 internal HD	\$	1,250.00
HRX-1621-4TB	Wisenet HD+ Pentabrid DVR AHD (up to 8MP), TVI (up to 8MP), CVI (up to 5MP), CVBS and IP (up to 8MP), 16CH analog + 2CH IP and up to 18CH IP, recording 1080p @ 30fps/ channel (frame rate at higher resolutions will vary), triple codec H.265/H.264/MJPEG, 70Mbps throughput on analog and 51mbps throughput on IP cameras), 16CH audio input/ 1CH audio output, 16 alarm input and 4 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code , Up to 8 internal HD	\$	1,970.00
HRX-1621-8TB	Wisenet HD+ Pentabrid DVR AHD (up to 8MP), TVI (up to 8MP), CVI (up to 5MP), CVBS and IP (up to 8MP), 16CH analog + 2CH IP and up to 18CH IP, recording 1080p @ 30fps/ channel (frame rate at higher resolutions will vary), triple codec H.265/H.264/MJPEG, 70Mbps throughput on analog and 51mbps throughput on IP cameras), 16CH audio input/ 1CH audio output, 16 alarm input and 4 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code , Up to 8 internal HD	\$	2,690.00
HRX-1621-12TB	Wisenet HD+ Pentabrid DVR AHD (up to 8MP), TVI (up to 8MP), CVI (up to 5MP), CVBS and IP (up to 8MP), 16CH analog + 2CH IP and up to 18CH IP, recording 1080p @ 30fps/ channel (frame rate at higher resolutions will vary), triple codec H.265/H.264/MJPEG, 70Mbps throughput on analog and 51mbps throughput on IP cameras), 16CH audio input/ 1CH audio output, 16 alarm input and 4 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code , Up to 8 internal HD	\$	3,410.00
HRX-1621-16TB	Wisenet HD+ Pentabrid DVR AHD (up to 8MP), TVI (up to 8MP), CVI (up to 5MP), CVBS and IP (up to 8MP), 16CH analog + 2CH IP and up to 18CH IP, recording 1080p @ 30fps/ channel (frame rate at higher resolutions will vary), triple codec H.265/H.264/MJPEG, 70Mbps throughput on analog and 51mbps throughput on IP cameras), 16CH audio input/ 1CH audio output, 16 alarm input and 4 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code , Up to 8 internal HD	\$	4,130.00
HRX-1621-20TB	Wisenet HD+ Pentabrid DVR AHD (up to 8MP), TVI (up to 8MP), CVI (up to 5MP), CVBS and IP (up to 8MP), 16CH analog + 2CH IP and up to 18CH IP, recording 1080p @ 30fps/ channel (frame rate at higher resolutions will vary), triple codec H.265/H.264/MJPEG, 70Mbps throughput on analog and 51mbps throughput on IP cameras), 16CH audio input/ 1CH audio output, 16 alarm input and 4 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code , Up to 8 internal HD	\$	4,850.00
HRX-1621-24TB	Wisenet HD+ Pentabrid DVR AHD (up to 8MP), TVI (up to 8MP), CVI (up to 5MP), CVBS and IP (up to 8MP), 16CH analog + 2CH IP and up to 18CH IP, recording 1080p @ 30fps/ channel (frame rate at higher resolutions will vary), triple codec H.265/H.264/MJPEG, 70Mbps throughput on analog and 51mbps throughput on IP cameras), 16CH audio input/ 1CH audio output, 16 alarm input and 4 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code , Up to 8 internal HD	\$	5,570.00
HRX-1621-30TB	Wisenet HD+ Pentabrid DVR AHD (up to 8MP), TVI (up to 8MP), CVI (up to 5MP), CVBS and IP (up to 8MP), 16CH analog + 2CH IP and up to 18CH IP, recording 1080p @ 30fps/ channel (frame rate at higher resolutions will vary), triple codec H.265/H.264/MJPEG, 70Mbps throughput on analog and 51mbps throughput on IP cameras), 16CH audio input/ 1CH audio output, 16 alarm input and 4 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code , Up to 8 internal HD	\$	6,650.00
HRX-1621-36TB	Wisenet HD+ Pentabrid DVR AHD (up to 8MP), TVI (up to 8MP), CVI (up to 5MP), CVBS and IP (up to 8MP), 16CH analog + 2CH IP and up to 18CH IP, recording 1080p @ 30fps/ channel (frame rate at higher resolutions will vary), triple codec H.265/H.264/MJPEG, 70Mbps throughput on analog and 51mbps throughput on IP cameras), 16CH audio input/ 1CH audio output, 16 alarm input and 4 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code , Up to 8 internal HD	\$	7,730.00

[illegible]

HRX-421	Wisenet HD+ Pentabrid DVR AHD (up to 8MP), TVI (up to 8MP), CVI (up to 5MP), CVBS and IP (up to 8MP), 4CH analog + 2CH IP and up to 6CH IP, recording 1080p @ 30fps/ channel (frame rate at higher resolutions will vary), triple codec H.265/H.264/MJPEG, 25Mbps throughput on analog and 17mbps throughput on IP cameras), 2 internal HDD, 4CH audio input/ 1CH audio output, 4 alarm input and 2 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code	\$	300.00
HRX-421-2TB	Wisenet HD+ Pentabrid DVR AHD (up to 8MP), TVI (up to 8MP), CVI (up to 5MP), CVBS and IP (up to 8MP), 4CH analog + 2CH IP and up to 6CH IP, recording 1080p @ 30fps/ channel (frame rate at higher resolutions will vary), triple codec H.265/H.264/MJPEG, 25Mbps throughput on analog and 17mbps throughput on IP cameras), 2 internal HDD, 4CH audio input/ 1CH audio output, 4 alarm input and 2 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code	\$	660.00
HRX-421-4TB	Wisenet HD+ Pentabrid DVR AHD (up to 8MP), TVI (up to 8MP), CVI (up to 5MP), CVBS and IP (up to 8MP), 4CH analog + 2CH IP and up to 6CH IP, recording 1080p @ 30fps/ channel (frame rate at higher resolutions will vary), triple codec H.265/H.264/MJPEG, 25Mbps throughput on analog and 17mbps throughput on IP cameras), 2 internal HDD, 4CH audio input/ 1CH audio output, 4 alarm input and 2 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code	\$	1,020.00
HRX-421-6TB	Wisenet HD+ Pentabrid DVR AHD (up to 8MP), TVI (up to 8MP), CVI (up to 5MP), CVBS and IP (up to 8MP), 4CH analog + 2CH IP and up to 6CH IP, recording 1080p @ 30fps/ channel (frame rate at higher resolutions will vary), triple codec H.265/H.264/MJPEG, 25Mbps throughput on analog and 17mbps throughput on IP cameras), 2 internal HDD, 4CH audio input/ 1CH audio output, 4 alarm input and 2 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code	\$	1,380.00
HRX-421-8TB	Wisenet HD+ Pentabrid DVR AHD (up to 8MP), TVI (up to 8MP), CVI (up to 5MP), CVBS and IP (up to 8MP), 4CH analog + 2CH IP and up to 6CH IP, recording 1080p @ 30fps/ channel (frame rate at higher resolutions will vary), triple codec H.265/H.264/MJPEG, 25Mbps throughput on analog and 17mbps throughput on IP cameras), 2 internal HDD, 4CH audio input/ 1CH audio output, 4 alarm input and 2 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code	\$	1,740.00
HRX-421-12TB	Wisenet HD+ Pentabrid DVR AHD (up to 8MP), TVI (up to 8MP), CVI (up to 5MP), CVBS and IP (up to 8MP), 4CH analog + 2CH IP and up to 6CH IP, recording 1080p @ 30fps/ channel (frame rate at higher resolutions will vary), triple codec H.265/H.264/MJPEG, 25Mbps throughput on analog and 17mbps throughput on IP cameras), 2 internal HDD, 4CH audio input/ 1CH audio output, 4 alarm input and 2 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code	\$	2,460.00
HRX-420	Wisenet HD+ Pentabrid DVR AHD (up to 8MP), TVI (up to 8MP), CVI (up to 5MP), CVBS and IP (up to 8MP), 4CH analog + 2CH IP and up to 6CH IP, recording 1080p @ 30fps/ channel (frame rate at higher resolutions will vary), triple codec H.265/H.264/MJPEG, 25Mbps throughput on analog and 17mbps throughput on IP cameras), 1 internal HDD, 1CH audio input/ 1CH audio output, 4 alarm input and 1 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code	\$	275.00
HRX-420-2TB	Wisenet HD+ Pentabrid DVR AHD (up to 8MP), TVI (up to 8MP), CVI (up to 5MP), CVBS and IP (up to 8MP), 4CH analog + 2CH IP and up to 6CH IP, recording 1080p @ 30fps/ channel (frame rate at higher resolutions will vary), triple codec H.265/H.264/MJPEG, 25Mbps throughput on analog and 17mbps throughput on IP cameras), 1 internal HDD, 1CH audio input/ 1CH audio output, 4 alarm input and 1 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code	\$	635.00
HRX-420-4TB	Wisenet HD+ Pentabrid DVR AHD (up to 8MP), TVI (up to 8MP), CVI (up to 5MP), CVBS and IP (up to 8MP), 4CH analog + 2CH IP and up to 6CH IP, recording 1080p @ 30fps/ channel (frame rate at higher resolutions will vary), triple codec H.265/H.264/MJPEG, 25Mbps throughput on analog and 17mbps throughput on IP cameras), 1 internal HDD, 1CH audio input/ 1CH audio output, 4 alarm input and 1 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code	\$	995.00
HRX-420-6TB	Wisenet HD+ Pentabrid DVR AHD (up to 8MP), TVI (up to 8MP), CVI (up to 5MP), CVBS and IP (up to 8MP), 4CH analog + 2CH IP and up to 6CH IP, recording 1080p @ 30fps/ channel (frame rate at higher resolutions will vary), triple codec H.265/H.264/MJPEG, 25Mbps throughput on analog and 17mbps throughput on IP cameras), 1 internal HDD, 1CH audio input/ 1CH audio output, 4 alarm input and 1 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code	\$	1,355.00
SRX-AU1211	Optional D-Sub adapter with 12 RCA audio connector for SRD-16XX series	\$	70.00
SLA-C-E24	Canon 24mm f1.4L, Auto-Iris (EF 24mm f/1.4L II USM) : Horizontal field of view: 8K 62.1° , CarePak 4 Years warranty	\$	5,175.00
SLA-C-E50	Canon 50mm f1.2, Auto-Iris (EF 50mm f/1.2 USM) : Horizontal field of view: 8K 31.6° , CarePak 4 Years Warranty	\$	4,315.00
SLA-C-E85	Canon 85mm f1.2L, Auto-Iris (EF 85mm f/1.2L II USM) : Horizontal field of view: 8K 19.2° , CarePak 4 Years Warranty	\$	6,235.00
SLA-C-E2470	Canon 24-70mm f/2.8L II USM (EF 24-70mm f/2.8L USM) : Horizontal field of view :8K 62.1° ~ 23.2° , CarePak 4 Years Warranty	\$	5,345.00
SLA-C-E70200	Canon 70-200mm f2.8L, Auto-Iris, Vari Focal (EF 70-200mm f/2.8L USM) : Horizontal field of view: 8K 23.2° ~ 8.3° , CarePak 4 Years Warranty	\$	5,945.00
SLA-C-I3910	1/1.8" 3.9-10mm F1.5 Varifocal, HD Series P-iris (i-CS Mount) Day/Night IR (12 MP capable) for AI Box Camera (PNB-A9001)	\$	455.00
SLA-C-I2885	1/2.7" 2.8-8.5mm F1.2 Varifocal, HD Series P-iris (i-CS Mount) Day/Night IR (8 MP capable) for WN7 Box Cameras (XNB-9002 and XNB-8002)	\$	435.00
SLA-T1080F	1.6mm fixed lens module, compatible with the XNB-6001, straight body style, 2MP @ 60fps, 0.03 Lux, 120dB WDR, 187° horizontal field of view, 8 meters cable (26 feet cable)	\$	310.00
SLA-T2480	2.4mm fixed lens module, compatible with the XNB-6001, straight body style, 2MP @ 60fps, 0.45 Lux, 120dB WDR, 138° horizontal field of view, 8 meters (26 feet cable)	\$	215.00
SLA-T2480V	2.4mm fixed lens module, compatible with the XNB-6001, right angle body style, 2MP @ 60fps, 0.45 Lux, 120dB WDR, 138° horizontal field of view, 8 meters/ 26 feet cable	\$	215.00
SLA-T4680	4.6mm pinhole lens module, compatible with the XNB-6001, straight body style, 2MP @ 60fps, 0.06 Lux, 120dB WDR, 73° horizontal field of view, 8 meters/ 26 feet cable	\$	215.00
SLA-T4680V	4.6mm pinhole lens module, compatible with the XNB-6001, right angle body style, 2MP @ 60fps, 0.06 Lux, 120dB WDR, 73° horizontal field of view, 8 meters/ 26 feet cable	\$	215.00
SLA-T4680A	4.6mm pinhole lens module, compatible with PNM-9000QB, straight body style, 2MP @ 30fps, 0.06 Lux, 73° horizontal field of view, 8 meters/ 26 feet cable	\$	215.00
SLA-T4680VA	4.6mm pinhole lens module, compatible with PNM-9000QB, right angle body style, 2MP @ 30fps, 0.06 Lux, 73° horizontal field of view, 8 meters/ 26 feet cable	\$	215.00
SLA-T2480A	2.4mm fixed lens module, compatible with PNM-9000QB, straight body style, 2MP @ 30fps, 0.45 Lux, 138° horizontal field of view, 8 meters/ 26 feet cable	\$	215.00
SLA-T2480VA	2.4mm fixed lens module, compatible with PNM-9000QB, right angle body style, 2MP @ 30fps, 0.45 Lux, 138° horizontal field of view, 8 meters/ 26 feet cable	\$	215.00
SLA-T1080FA	1.6mm fixed lens module, compatible with PNM-9000QB, straight body style, 2MP @ 30fps, 0.03 Lux, 187° horizontal field of view, 8 meters cable/ 26 feet cable	\$	310.00
SLA-H-4680VA	Height strip with 4.6mm pinhole lens module, compatible with PNM-9000QB, right angle body style, 2MP @ 30fps, 0.06 Lux, 73° horizontal field of view, 8 meters/ 26 feet cable	\$	545.00
SLA-T4680D	Door Jamb head with a 4.6mm lens, compatible with XNB-6001 (not included) 8m (26 feet) cable, black color	\$	270.00
SLA-T4680DS	Door Jamb head with a 4.6mm lens, compatible with XNB-6001 (not included) 8m (26 feet) cable, silver color	\$	270.00

SLA-T4680DW	Door Jamb head with a 4.6mm lens, compatible with XNB-6001 (not included) 8m (26 feet) cable, white color	\$	270.00
SLA-T-M410DN	Megapixel Lens, image sensor from 1/2.3" up to 1/1.7", Up to 12MP resolution, Vari-focal (4~10mm), DC auto iris, CS-Mount, Compatible with: XNB-6005/8000, PNB-A9001	\$	360.00
SLA-T-M1250DN	Megapixel Lens, image sensor from 1/2.3" up to 1/1.7", Up to 12MP resolution, Vari-focal (12~50mm), DC auto iris, CS-Mount, Compatible with: XNB-6005/8000, PNB-A9001	\$	360.00
SLA-T-M940DN	Lens, 1/2.3", Up to 4K Vari-focal(9~40mm), Auto DC IRIS, CS-Mount, compatible with: XNB-6000, HCB-6000/6001/7000/7000A	\$	369.00
SLA-2M2400P	1/2.8" 2MP CMOS with a 2.4mm fixed focal lens, FoV: H: 135.4°, V: 71.2° for the PNM-9320VQP and PNM-9322VQP	\$	85.00
SLA-2M2800P	1/2.8" 2MP CMOS with a 2.8mm fixed focal lens, FoV: H: 107.4°, V: 62.2°, for the PNM-9320VQP and PNM-9322VQP	\$	85.00
SLA-2M3600P	1/2.8" 2MP CMOS with a 3.6mm fixed focal lens, FoV: H: 94.8°, V: 49.3°, for the PNM-9320VQP and PNM-9322VQP	\$	85.00
SLA-2M6000P	1/2.8" 2MP CMOS with a 6.0mm fixed focal lens, FoV: H: 50.4°, V: 28.8°, for the PNM-9320VQP and PNM-9322VQP	\$	85.00
SLA-2M1200P	1/2.8" 2MP CMOS with a 12.0mm fixed focal lens, FoV: H: 26.3°, V: 14.9°, for the PNM-9320VQP and PNM-9322VQP	\$	85.00
SLA-5M3700P	1/1.8" 5MP CMOS with a 3.7mm fixed focal lens, FoV: H: 97.5°, V: 71.9° for the PNM-9320VQP and PNM-9322VQP	\$	250.00
SLA-5M4600P	1/1.8" 5MP CMOS with a 4.6mm fixed focal lens, FoV: H: 77.9°, V: 57.9° for the PNM-9320VQP and PNM-9322VQP	\$	250.00
SLA-5M7000P	1/1.8" 5MP CMOS with a 7.0mm fixed focal lens, FoV: H: 50.7°, V: 37.8° for the PNM-9320VQP and PNM-9322VQP	\$	250.00
SLA-2M2400Q	1/2.8" 2MP CMOS with a 2.4mm fixed focal lens, FoV: H: 135.4°, V: 71.2° for the PNM-9000VQ	\$	85.00
SLA-2M2800Q	1/2.8" 2MP CMOS with a 2.8mm fixed focal lens, FoV: H: 107.4°, V: 62.2°, for the PNM-9000VQ	\$	85.00
SLA-2M3600Q	1/2.8" 2MP CMOS with a 3.6mm fixed focal lens, FoV: H: 94.8°, V: 49.3°, for the PNM-9000VQ	\$	85.00
SLA-2M6000Q	1/2.8" 2MP CMOS with a 6.0mm fixed focal lens, FoV: H: 50.4°, V: 28.8°, for the PNM-9000VQ	\$	85.00
SLA-5M3700Q	1/1.8" 5MP CMOS with a 3.7mm fixed focal lens, FoV: H: 97.5°, V: 71.9° for the PNM-9000VQ	\$	250.00
SLA-5M4600Q	1/1.8" 5MP CMOS with a 4.6mm fixed focal lens, FoV: H: 77.9°, V: 57.9° for the PNM-9000VQ	\$	250.00
SLA-5M7000Q	1/1.8" 5MP CMOS with a 7.0mm fixed focal lens, FoV: H: 50.7°, V: 37.8° for the PNM-9000VQ	\$	250.00
SLA-5M3700D	1/1.8" 5MP CMOS with a 3.7mm fixed focal lens, FoV: H: 97.5°, V: 71.9° for the PNM-9000VD	\$	250.00
SLA-5M4600D	1/1.8" 5MP CMOS with a 4.6mm fixed focal lens, FoV: H: 77.9°, V: 57.9° for the PNM-9000VD	\$	250.00
SLA-5M7000D	1/1.8" 5MP CMOS with a 7.0mm fixed focal lens, FoV: H: 50.7°, V: 37.8° for the PNM-9000VD	\$	250.00
SLA-2M2400D	1/2.8" 2MP CMOS with a 2.4mm fixed focal lens, FoV: H: 135.4°, V: 71.2°, for the PNM-7000VD	\$	85.00
SLA-2M2800D	1/2.8" 2MP CMOS with a 2.8mm fixed focal lens, FoV: H: 107.4°, V: 62.2°, for the PNM-7000VD	\$	85.00
SLA-2M3600D	1/2.8" 2MP CMOS with a 3.6mm fixed focal lens, FoV: H: 94.8°, V: 49.3°, for the PNM-7000VD	\$	85.00
SLA-2M6000D	1/2.8" 2MP CMOS with a 6.0mm fixed focal lens, FoV: H: 50.4°, V: 28.8°, for the PNM-7000VD	\$	85.00
SLA-2M2402D	1/2.8" 2MP CMOS with a 2.4mm fixed focal lens, FoV: H: 135.4°, V: 71.2°, for the PNM-7002VD	\$	85.00
SLA-2M2802D	1/2.8" 2MP CMOS with a 2.8mm fixed focal lens, FoV: H: 107.4°, V: 62.2°, for the PNM-7002VD	\$	85.00
SLA-2M3602D	1/2.8" 2MP CMOS with a 3.6mm fixed focal lens, FoV: H: 94.8°, V: 49.3°, for the PNM-7002VD	\$	85.00
SLA-2M6002D	1/2.8" 2MP CMOS with a 6.0mm fixed focal lens, FoV: H: 50.4°, V: 28.8°, for the PNM-7002VD	\$	85.00
SLA-M2890DN	Lens, 1/2.8", 3 MP, Vari-focal (2.8-9.0mm), Auto DC Iris, CS-Mount	\$	199.00
SLA-M2890PN	Lens, 1/2.8", 3 MP, Vari-focal (2.8-9.0mm), Auto P Iris, CS-Mount	\$	249.00
SLA-F-M419DN	Lens, 1/1.8", 6MP, Vari-focal (4.1-9mm), Auto DC Iris, CS-Mount	\$	299.00
SLA-F-M1550DNL	Lens, 1/2.7", 3 MP, Vari-focal (15-50mm), Auto DC Iris, CS-Mount, Tele Range 3.3x	\$	369.00

SPM-4210	Network I/O Box for PTZ plus, 4-configurable I/O ports, Audio I/O, PoE. Compatible with XNP-9300RW/9250R/9250 XNP-8300RW/8250R/8250, XNP-6400RW/6400R/6400	\$	265.00
SBS-165TM	Tilt Mount for TID-600R, 30° Tilt angle, Installable on Left or Right	\$	31.00
SHS-165F	Flush Mount for TID-600R, 2 Cover plates included (White, Dark Brown)	\$	107.00
SBC-165W	White Skin Cover for TID-600R	\$	22.00
SBD-120GP	Adaptor plate for Single, Double, 4" Octagon, supported cameras (QND-6070R/7080R, LND-6071R / 6072R, HCD-7070R/7070RA/6070R/6080R) Pack of 5	\$	45.00
SBD-110GP	Adaptor plate for Single, Double, 4" Octagon, supported cameras (7010R / 7020R / 7030R, XND-6010 / 6020R / 8020R / 8030R / 8040R, 6012R / 6022R / 6032R, HCD-7010RA / 7020RA/ 7030RA) Pack of 5	\$	45.00
SBP-B-100P	Single Gang Box Converter Plate for XNV-6011	\$	39.00
STB-2000	ATM mounting bracket for remote head lens, compatible with SLA-T2480, SLA-T2480A, SLA-T4680, SLA-T4680A lenses	\$	79.00
SBP-276HM	Cap adapter for the PNM-9000VQ and PNM-9030V	\$	75.00
SBP-329HM	Large Cap adapter (outdoor) for the Multi-Directional cameras PNM-9080VQ and PNM-9081VQ (Will fit the following accessories: SBP-300WM, SBP-300LM, SBP-300CM) (Will not Fit the SBP-300WM1)	\$	75.00
SBP-168HM	Cap Adapter for the XNP-6120H	\$	79.00
SBP-201HM	Cap Adapter for the PNM-9020V, HCM-9020VQ Multi-Sensor.	\$	49.00
SBP-201HMW	Cap Adapter for the PNM-9000VD, PNM-7002VD Multi-sensor	\$	49.00
SBP-300HM8	Cap Adapter for the PND-9080R, XND-6080V/RV, XND-8080RV, XND-L6080R/L6080RV/L6080V	\$	49.00
SBP-300HM7	Small cap adapter (aluminum), accessory for XNV-6011, SCD-6023R, QND-7010R/20R/30R, XND-6010/20R, XND-8020R/30R/40R, HCD-6010/6020R/7010RA/7020RA/7030RA	\$	49.00
SBP-300HMW7	Small cap adapter (aluminum), accessory for XNV-6011W, QND-8010R/20R/30R, QND-6012R/22R/32R, LND-6012R/22R/32R, HCF-8010V white color	\$	49.00
SBP-300HM6	Medium Cap Adapter (Aluminum), accessory for PNV-9080R, XNV-6080/R, XNV-8080R, XNV-6120/R, XND-6085V, XNV-6085, XNV-L6080/R, PNM-7000VD	\$	49.00
SBP-300HM5	Small cap adapter (aluminum), accessory for 5MP fisheye cameras (SNF-8010, SNF-8010VM, XNF-8010R/RV/RVM, PNF-9010R/RV/RVM), Works with Mounts (SBP-300CM, SBP-300LM, SBP-300WM, SBP-300WM1)	\$	49.00
SBP-301HM4	Medium Cap Adapter (Aluminum) Accessory, (SCD-6083R, SCD-5080, SCD-5082, SCD-5083, SCD-5083R, SND-6011R, SNF-7010, SNF-7010V, SNF-7010VM, SND-L6083R, SND-L5083R, HCD-6070R/6080R) Works with Mounts (SBP-300WM1, SBP300WM, SBP-300CM, SBP-300LM), Ivory	\$	49.00
SBP-301HM3	Medium Cap Adapter Accessory, HCP-6320A, XNP-6320/6321, QNP-6230), Ivory	\$	49.00
SBP-301HMW3	Medium Cap Adapter Accessory, compatible with QNP-6250, QNP-6320, White color	\$	49.00
SBP-301HM5	Small Cap Adapter (Aluminum), accessory for SCV-6083R/6023R, QNV-7080R,QNV-6070R, HCV-6070R/6080R/7070RA, XNP-6040H, Ivory	\$	49.00
SBP-099HMW	Small cap adapter, accessory for Q-mini cameras: QNF-8010,QNF-9010,QND-6011, QND-6021, QND-8011, QND-8021 (White color)	\$	34.00
SBP-300HMW5	Small cap adapter, accessory for XNF-8010RW, (White color)	\$	49.00
SBP-302CM-06	Extension pendant pipe 6" long, fit the SBP-302CMB (Mounting backbox), SBP-302CMA (mounting plate), SBP-302CM (telescopic pendant mount) and the extension pipes SBP-302CM-12 and SBP-302CM-36	\$	45.00
SBP-301HMW2	Small cap adapter (aluminum) accessory, (QNV-8080R,QNV-6082R, LNV-6072R), white color	\$	49.00
SBP-300HM1	Large Cap Adapter Accessory, (SCP-3430/3371/3370/3250/3120/2430/2371/2370/2271/2270/2250, SNP-6200/5300/5200/3371/3302), Ivory	\$	79.00
SBP-317HMW	Can be used with PNM-9084RQZ/9085RQZ. Mount screw size : PF 1 1/2", White	\$	75.00
SBP-122HM	Small cap adapter for: (QND-7080R/6070R, QNV-7010R/20R/30R, QNV-6010R/20R/30R, XNV-6010/20R, XNV-8020R/30R/40R, HCD-6070R/6080R/7070R/7070RA, HCV-7010R/7010RA/7020R/7020RA/7030R/7030RA, LND-6071R, LNV-6011R/6021R/6031R, SCD-6083R)	\$	34.00
SBP-122HMW	Cap adapter for the (QND-8080R/6082R, QNV-8010R/20R/30R, QNV-6012R/22R/32R, LNV-6012R/22R/32R, HCF-8010V), white color	\$	34.00
SBP-167HM	Hanging cap (ivory) for the indoor X Plus dome cameras	\$	50.00
SBP-276HMW	Cap adapter for the PNM-9084QZ, PNM-8082VT, PNM-9022V, PNM-9031RV	\$	75.00

SBP-167HMMW	Hanging cap (white color) compatible with: XNF-9010R/RV/M, XND-9082RV/8082RV, XND-6081RV/6081REV, XND-8081RV/8081ERV, PND-A9081RV, XND-6083RV/C6083RV/C7083RV/8083RV/C8083RV/9083RV/C9083RV, XNV-C6083R/C7083R/C8083R/C9083R	\$	50.00
SBP-187HM	Hanging cap (ivory) for the outdoor X Plus dome cameras	\$	50.00
SBP-187HMMW	Hanging cap (white) for the outdoor X Plus dome cameras: XNV-8082R/9082R, XNV-6083R/8083R/9083R, XNV-6081/6081R/6081Z/6081RE/8081RE/8081R/8081Z	\$	50.00
SBC-170C	Silver Skin Cover for TNV-8011C	\$	35.00
SBC-170CB	Black Skin Cover for TNV-8011C	\$	35.00
SBC-170CW	White Skin Cover for TNV-8011C	\$	35.00
SBC-160B	Black skin cover for indoor X-Plus series domes XND-6081xx, XND-8081xx, XND-9082RV/8082RV QTY of 3	\$	50.00
SBC-180B	Black skin cover for outdoor X-Plus series domes XNV-6081xx, XNV-8081xx, XNV-9082R/8082R, QTY of 3	\$	50.00
SBC-140C	Stainless Steel Skin Cover for TNV-8010C, dimensions: 152.6 x 147.1 x 61.5mm (6" x 5.79" x 2.42")	\$	79.00
SBV-160WC	Weather cap for the following outdoor domes: (XNV-6080/R/8080R/PNV-9080R/ XNV-6120/R, XNV-L6080/R)	\$	30.00
SBV-120WC	Weather cap for the following outdoor domes: (XNV- 6010/6020/8020R/8030R/8040R, QNV- 7010R/7020R/7030R, HCV-7010RA/7020RA/7030RA)	\$	30.00
SBV-120WCW	Weather cap for the following outdoor domes: (QNV- 6012R/6022R/6032R/8010R/8020R/8030R, LNV-6012R/6022R/6032R), white color	\$	30.00
SBV-125BW	Back box for outdoor Flat-Eye (QNE-8011R and QNE-8021R), white color	\$	49.00
SBP-160TM	23° tilt mount for vandal outdoor domes (XNV-6080/R/8080R/L6080/L6080R, PNV-9080R/SNV-8081/8080R/7084R/6084R/6085R/5084R, SCV-6081R, XNV-6120/R, XNV-6085)	\$	25.00
SBP-160TMW1	Tilt Mount, compatible with: XNF-9010R/RV/M, XND-9082RV, XND-8082RV, XND-6081RV/6081REV, XND-8081RV/8081REV, PND-A9081RV	\$	49.00
SBP-300TM1	20° Tilt Angle Wall Mount Adapter (Poly Carbonate), Accessory for 5MP fisheye cameras (XNF-8010R/RV/RVM, PNF-9010R/RV/RVM), Ivory	\$	59.00
SPB-IND88W	Tinted dome for Indoor dome X-Core cameras	\$	80.00
SPB-VAN88W	Tinted dome for Vandal dome X-Core cameras	\$	85.00
SHD-1350FPW	In-ceiling Housing for X-Plus module cameras	\$	135.00
SPB-VAN85W	Tinted bubble for outdoor X-Plus cameras, compatible with: XNV-8081RE/8081R/8081Z, XNV-6081RE/6081R/6081/6081Z, PNV-A9081R, XNV-9082R/8082R	\$	80.00
SPB-IND85W	Tinted bubble for indoor X-Plus cameras, compatible with: XND-8081REV/8081RV/8081VZ, XND-6081REV/6081RV/6081V/6081VZ, PND-A9081RV, XND-9082RV/8082RV	\$	75.00
SPB-FCD85W	Tinted bubble for indoor flush mount X-Plus cameras, compatible with: XND-8081RF/8081FZ, XND-6081RF/6081F/6081FZ, PND-A9081RF, XNV-9082R/8082R	\$	75.00
SPB-PTZ71	Tinted replacement Bubble for XNP-6040H	\$	75.00
SPB-PTZ73	Tinted replacement Bubble for XNP-6120H	\$	100.00
SPB-PTZ85W	Smoked dome cover for PTZ Plus cameras: XNP-6400/6400R, XNP-8250/8250R, XNP-9250/9250R (not compatible with wiper models)	\$	100.00
SPB-VAN71	Tinted replacement Bubble for XNV-6120, XNV-6120R	\$	80.00
SPB-VAN81	Tinted replacement Bubble for XNV-6085	\$	80.00
SPB-IND83V	Tinted replacement Bubble for XND-6085V	\$	75.00
SPB-IND11	Tinted bubble (XND-6010/6020/8020R/8030R/8040R)	\$	25.00
SPB-IND12	Tinted bubble (QND- 6010R/6020R/6030R / 7010R/7020R/7030R, LND-6011R/6021R/6031R, HCD-7010RA/20RA/30RA)	\$	25.00
SPB-INW72	Smoked dome cover for White Q/L varifocal indoor domes, (except QND-8080R)	\$	25.00
SPB-IND72	Tinted bubble (QND-6070R/7080R, LND-6071R)	\$	25.00
SPB-IND81V	Tinted bubble (XND-6080V/XND-6080RV XND-8080RV)	\$	45.00
SPB-VAN11	Tinted bubble (XNV- 6010/6020/ 8020R/8030R/8040R)	\$	25.00
SPB-VAN12	Tinted bubble (QNV- 6010R/6020R/6030R/ 7010R/7020R/7030R, LNV-6011R/6021R/6031R)	\$	25.00
SPB-VAN72	Tinted bubble (HCV-6070R/6080R/7070RA, SCV-6083R)	\$	35.00
SPB-VAW12	Smoked dome cover for White Q/L fixed vandal domes (LNV-6012R/6022R/6032R, QNV-6012R/6022R/6032R/8010R/8020R/8030R)	\$	25.00
SPB-INW12	Smoked dome cover for White Q/L fixed indoor domes (LND-6012R/6022R/6032R, QND-6012R/6022R/6032R)	\$	25.00
SPB-INW13	Smoked dome cover for White 5MP Q series fixed lens (QND-8010R/8020R/8030R)	\$	25.00
SPB-INW73	Smoked dome cover for White QND-8080R	\$	25.00
SPB-VAN4	Accessory, tinted replacement Bubble for SCV-6023R	\$	69.00
SPB-VAN3	Accessory, tinted replacement Bubble for XNV-6080/6080R/L6080/L6080R, XNV-8080R	\$	69.00
SPB-IND6	Accessory, tinted replacement Bubble for SCD-6083R,HCD-6080R/6070R	\$	39.00
SPB-IND5	Accessory, tinted replacement Bubble for SND-5084/6083/6084/7084, SND-5084R/6084R/7084R	\$	39.00
SPB-PTZ6	Accessory, tinted replacement Bubble for Indoor PTZ: XNP-6320/6321, QNP-6230/6250/6320, HCP-6320A	\$	99.00
SPB-PTZ7	Accessory, tinted replacement Bubble for Outdoor PTZ: XNP-6320H/63210H, QNP-6230H, HCP-6320HA	\$	139.00
SPB-VAW72	Smoked dome cover for: QNV-8080R, QNV-6082R, LNV-6072R	\$	35.00
SPG-IND12B	Black cover for QND-6012R / 22R/ 32R, QND-7010R / 20R / 30R, LND-6012R/ 22R / 32R, HCD-6010/6020R/7010RA/7020RA/7030RA	\$	25.00
SPG-IND72B	Black cover for QND-6082R, QND-7080R, LND-6072R	\$	25.00
SPG-IND16B	Black cover for Q-mini cameras QND-6011, QND-6021, QND-8011, QND-8021	\$	25.00
SHD-315F	2X2 drop ceiling tile flush mount adaptor for the PNM-9084RQZ and PNM-9085RQZ	\$	250.00
SHD-1198FW	In-ceiling flush mount accessory for indoor dome: QND-8080R, QND-7080R, QND-6070R, HCD-7070RA, HCD-7070R, HCD-6080R, HCD-6070R, HCD-6020R, HCD-6010 (White color)	\$	79.00
SHF-1500F	In-ceiling flush mount accessory for XNF-8010R/RV/RVM, PNF-9010R/RV/RVM	\$	79.00
SHD-400F	In-ceiling flush mount accessory for XNV-6011, Aluminum Body, Ivory	\$	119.00
SHD-3000F1	In-ceiling flush mount accessory for PNV-9080R, XNV-6080R, XNV-8080R, XNV-L6080/L6080R	\$	79.00
SHD-3000F2	In-ceiling flush mount accessory for Indoor dome: HCD-6070R/6080R/7070RA, QND-7080R, SCD-6083R	\$	79.00
SHD-3000F3	In-ceiling flush mount accessory for vandal dome SCV-6083R/6023R, QNV-7080R,QNV-6070R, HCV-6070R/6080R, XNP-6040H	\$	79.00
SHD-3000FW2	In-ceiling flush mount accessory for Indoor dome (QND-6082R, LND-6072R), white color	\$	79.00
SHD-3000F4	In-ceiling flush mount accessory for PND-9080R, XND-6080RV, XND-6080V & XND-8080RV, XND-L6080/L6080R	\$	79.00
SHD-3000F5	In-ceiling flush mount accessory for PNM-9000VQ, plenum rated (UL2820)	\$	250.00
SHP-1680F	In-ceiling flush mount accessory for XNP-6120H, XND-6085V, XNV-6085	\$	79.00
SHD-B-3100FP1	Plenum rated In-ceiling flush mount accessory for PNV-9080R, XNV-6080R, XNV-8080R	\$	174.00
SHP-3701F	PTZ In-Ceiling flush mount accessory for: XNP-6320/6321, QNP-6230/6250/6320	\$	200.00
SHP-3701FB	PTZ In-Ceiling flush mount accessory with a tinted bubble for: HCP-6320A, XNP-6320/6321, QNP-6230/6250/6320	\$	200.00
SHD-1408FW	In-ceiling flush mount accessory for: HCV-6070R/6080R/7070RA, PND-9080R, QNV-6082R/7080R/8080R, XND-6080RV/6080V/8080RV/L6080RV/L6080V (White color)	\$	79.00
SHD-1408FPW	Plenum rated flush mount, white color. Compatible with HCD-6080R/7070RA, QND-6082R/8080R, XNV-6010/6020R/8020R/8030R/8040R, HCV-7010RA/7020RA/7030RA/6080R/6070R, LNV-6012R/6022R/6032R/6072R, QNV-6012R/6022R/6032R/6082R/8010R/8020R/8030R/8080R, XND-6080V/6080RV/8080RV, XND-L6080V/6080RV, XNP-6040H	\$	125.00
SHD-1128FPW	Plenum rated flush mount, white color. Compatible with: QNF-8010/9010, HCD-6010/6020R/7010RA/7020RA/7030RA, QND-6011/6021/8011/8021/6012R/6022R/6032R/ 7010R/7020R/7030R/8010R/8020R/8030R, LND-6012R/6022R/6032R, XND-6010/6020R/8020R/8030R/8040R, XNV-6011/6011W	\$	79.00
SHP-1560FW	White color PTZ-Plus flush mount. Compatible with XNP-9250/9250R/8250/8250R/6400/6400R, QNP-6320R/6250R	\$	119.00
SHP-1560FPW	Plenum rated PTZ-Plus flush mount, white color. Compatible with XNP-9250/9250R/8250/8250R/6400/6400R, QNP-6320R/6250R	\$	159.00

SBP-1680FPW	White color PTZ flush mount. Compatible with HCP-6320/6320A, QNP-6230/6250/6320, XNP-6320/6321/6120H	\$	159.00
SHP-1680FW	In-ceiling flush mount accessory for XNP-6120H, XND-6085V, XNV-6085, XNV-6120, XNV-6120R (White color)	\$	79.00
SBU-500WM	Wall mount for the TNU-6321	\$	325.00
SBP-137WM1	Outdoor wall mount for outdoor domes (QNV-7010R/7020R/7030R, XNV-6010/6020R/8020R/8030R/8040R, HCV-6080R/6070R/7010RA/7020RA/7030RA/7070RA, SCV-6023R/6083R, XNP-6040H)	\$	65.00
SBP-137WMW1	Outdoor wall mount for outdoor domes (QNV-6012R/6022R/6032R/8010R/8020R/8030R, 8080R/6082R), white color	\$	65.00
SBP-125WMW	Outdoor wall mount for outdoor Flat-Eye (QNE-8011R and QNE-8021R), white color	\$	65.00
SBP-120WM	Indoor Wall mount for indoor domes (QND-7080R/7030R/7020R/7010R/6070R/6030R/6020R/6010R, XND-6010/6020/8020R/8030R/8040R, SCD-6083R/6023R)	\$	25.00
SBP-300WMW	White Gooseneck mount	\$	79.00
SBP-390WMW2	Wall Mount Accessory, 2x knock out built-in, compatible with all full size outdoor PTZs and all caps, White color	\$	215.00
SBP-120WMW	Indoor wall mount for indoor domes (QND-8080R/8030R/8020R/8010R/6082R/6032R/6022R/6012R), white color	\$	25.00
SBP-300WM1	Wall Mount Accessory, All caps except SBP-329HM and all outdoor PTZs Ivory	\$	79.00
SBP-300WMW1	Wall Mount Accessory (white), Compatible with white hanging caps	\$	79.00
SBP-300WMS1	Stainless Steel wall mount for stainless steel cameras PTZ: XNP-6320HS, QNP-6320HS and dome cameras: XNV-6080RSA, XNV-8080RSA, (need to purchase a separate cap SBP-300HMS6 for the dome cameras)	\$	625.00
SBP-390WM1	Wall Mount Accessory, 2x knock out built-in, compatible with all full size outdoor PTZs and all caps, Ivory color	\$	215.00
SBP-390WM2	Wall Mount Accessory, 2x knock out built-in, compatible with all full size outdoor PTZs and all caps, Ivory color as well as SBP-300PM pole mount adaptor and SBP-300KM corner mount adaptor	\$	215.00
SBP-300WM	Wall Mount Accessory, All caps and all outdoor PTZs Ivory	\$	79.00
SBP-300WMS	Stainless Steel wall mount (gooseneck) for stainless steel cameras PTZ: XNP-6320HS, QNP-6320HS and dome cameras: XNV-6080RSA, XNV-8080RSA, PNM-9002VQS (need to purchase a separate cap SBP-300HMS6 for the dome cameras)	\$	625.00
SBP-300HMS6	Stainless steel cap adaptor for XNV-6080RSA, XNV-8080RSA	\$	485.00
SBP-300PM	Pole Mount Adapter Accessory, use with SBP-300WM, Ivory	\$	79.00
SBP-302PM	Pole Mount Adapter Accessory, use with SBO-100B1, PNO-9080R, SNO-8081R SBO-100B1	\$	79.00
SBP-300PMW1	Pole Mount Adapter Accessory, use with SBP-300WMW1, White color, made of aluminum	\$	79.00
SBP-300PM1	Pole Mount Adapter Accessory, use with SBP-300WM,SBP-300WM1, SBP-390WM2, Ivory color, made of aluminum	\$	79.00
SBP-300PMS	Pole mount adaptor for the SBP-300WMS and SBP-300WMS1	\$	110.00
SBP-303PM	Pole mount adapter accessory for thermal bullet cameras, compatible with TNO-4040T, TNO-4030T, TNO-4050T, TNO-4030TR, TNO-4040TR, TNO-3010T/3020T/3030T	\$	79.00
SBP-300KM1	Corner Mount Adapter Accessory, ivory color	\$	79.00
SBP-300KM	Corner Mount Adapter Accessory, use with SBP-300WM, Ivory	\$	79.00
SBP-300KMW1	Corner Mount Adapter Accessory, use with SBP-300WMW1, White color, made of aluminum	\$	79.00
SBP-300KMS	Corner mount adaptor for the SBP-300WMS and SBP-300WMS1	\$	150.00
SBP-300LM	Parapet Mount Accessory, compatible with all full size outdoor PTZs and all caps, Ivory color	\$	395.00
SBP-300LMW	Parapet Mount Accessory, compatible with all full size outdoor PTZs and all caps, White	\$	395.00
SBP-302CM	Telescopic pendant mount Accessory, require a mounting plate SBP-302CMA	\$	250.00
SBP-300CMW	Pendant Mount Accessory, white	\$	79.00
SBP-302CMA	Mounting plate for the telescopic pendant mount SBP-302CM	\$	30.00
SBP-300CM	Pendant Mount Accessory, Ivory	\$	79.00
SBP-302CM-36	Extension pendant pipe 36" long, fit the SBP-302CMB (Mounting backbox), SBP-302CMA (mounting plate), SBP-302CM (telescopic pendant mount) and the extension pipes SBP-302CM-12 and SBP-302CM-36	\$	105.00
SBP-302CM-12	Extension pendant pipe 12" long, fit the SBP-302CMB (Mounting backbox), SBP-302CMA (mounting plate), SBP-302CM (telescopic pendant mount) and the extension pipes SBP-302CM-12 and SBP-302CM-36	\$	65.00
SBP-302CMB	Back box made to fit SBP-302CM telescopic pendant mount and the extension pipes (SBP-302CM-12 and SBP-302CM-36)	\$	190.00
SBP-302CMAS	Telescopic pendant mount accessory with 90 degrees swivel joint, 4.5' to 8' adjustable, includes SBP-302CMA for ceiling mount, Ivory color	\$	400.00
SBP-302CMS	Swivel adapter for pendant mount for SBP-302CM, SBP-302CM-12, SBP-302CM-36 and it also requires one mounting option either SBP-302CMA or SBP-302CMB	\$	120.00
SBP-100S	Stainless steel mount strap (QTY of 2) for wall pole mount: SBP-156WMW, SBP-300PMW, SBP-300PM	\$	10.00
SBP-156WMW	Wall/Pole mount, Material : Aluminum, Color : White, Dimensions :135(W)x183(H)x302(D)mm (5.31x7.20x11.89"), Compatible with: XNP-9300RW/8300RW/6400RW, QNP-6320R/6250R/6320H/6250H. Stainless Steel Pole straps are not included.	\$	149.00
SBP-156HMMW	Hanging mount, Material : Aluminum, Color : White, Dimensions : Φ95.5x77.0 mm (Φ3.76x3.03"), Compatible with: XNP-9300RW/8300RW/6400RW, QNP-6320R/6250R/6320H/6250H	\$	65.00
SBP-156CMW	Ceiling mount, Weight: 4.2 kg (9.3 lb), Material: Aluminum, Color: White, Compatible with: XNP-9300RW/8300RW/6400RW, QNP-6320R/6250R/6320H/6250H	\$	255.00
SBP-156LMW	Parapet mount, White color parapet mount , Weight : 7.1 kg (15.7 lb), Compatible with: XNP-9300RW/8300RW/6400RW, QNP-6320R/6250R/6320H/6250H	\$	435.00
SBP-156KMW	Corner mount, Material: Aluminum, Color: White, Dimensions : 276.8(W)x183.0(H)x158.5(D)mm (10.90x7.20x6.24"), Compatible with: XNP-9300RW/8300RW/6400RW, QNP-6320R/6250R/6320H/6250H	\$	119.00
SBP-099TMW	Tilt mount for Q fisheye cameras, Compatible with QNF-9010, QNF-8010	\$	49.00
SBP-125HMMW	Hanging Mount for QNE-8011R/8021R	\$	34.00
SHD-2510FPW	Plenum Flush Mount for PNM-9084QZ/8082VT	\$	250.00
SHD-1600FPW	Plenum Flush Mount for XNF-8010R/8010RV/9010RV/9010RVM, XND-6085V, XNV-6080R/6080R/8080R/L6080/L6080R/6120/6120R/6085	\$	189.00
SBL-100D	Dome bracket for SLA-T2480A, SLA-T4680A, SLA-T2480, SLA-T4680	\$	39.00
SBL-100C	Corner bracket for SLA-T2480A, SLA-T4680A, SLA-T2480, SLA-T4680	\$	39.00
SCL-150	Extension cable for remote head lens, 15m (49.2Ft), compatible with: PNM-9000QB, SLA-T4680A, SLA-T4680VA, SLA-T2480A, SLA-T2480VA, SLA-T1080FA	\$	95.00
STB-1520VW	Box camera swivel adapter, converting 1.5"NPT to ¼-20 UNC, Compatible with TNM-3620TDY (body temperature detection camera), SPI-35B (Blackbody), All other box cameras; white color	\$	130.00
STB-5075W	Floor stand with adjustable height; compatible with all box cameras, temperature detecting camera [TNM-3620TDY] , blackbody [SPI-35B] , and all other box cameras, extend between 50 inch to 75 inch; white color	\$	450.00
STB-4150V	Wall/Ceiling Mount Accessory for Box cameras	\$	29.00
SBP-300B	Wall Mount Base, Works with Mounts (SBP-300WM/300WM1), Ivory	\$	89.00
SBP-300BW	Wall Mount Base, Works with Mounts SBP-300WMW1, white	\$	89.00
SBV-120GW	Back Box with knockouts, Compatible with QNV-6012R/6022R/6032R,QNV-8010R/8020R/8030R	\$	49.00
SBO-100B1	IR Bullet camera Back box. (QNO-7030R/7020R/7010R, QNO-7080R, SCO-6083R, HCO-6080R/6070R/7010RA/7020RA/7030RA/7070RA, QNO-8010R/8020R/8030R, QNO-6012R/6022R/6032R/6082R)	\$	49.00
SBO-126B	IR bullet camera back box. (XNO-L6080R, QNO-8080R)	\$	49.00
SBO-147BA	Conduit Hole Adaptor for X-Core bullet cameras	\$	20.00
SBO-147B	Water-Proof Back Box for QNO-6082R	\$	75.00
SBV-160BW	White Back Box, Compatible with: XNF-9010RV/RVM, and all indoor X-Plus cameras (XND)	\$	49.00
SBV-158G	Vandal dome camera Back box. (PNV-9080R, XNV-6080R, XNV-8080R, XNV-6120/R, XNV-6085, PNM-7000VD)	\$	85.00
SBV-136B	Back Box with knockouts and water proof design, Compatible with SCV-6083R/6023R, QNV-7080R, HCV-6070R/6080R, XNP-6040H	\$	49.00
SBV-136BW	Back box with knockouts (QNV-8080R,QNV-6082R), white color	\$	49.00
SBF-100B1	Fisheye camera Back box. (XNF-8010R/RV/RVM, PNF-9010R/RV/RVM)	\$	49.00
SBV-116B	Back box with knockouts, compatible with XNV-6011	\$	49.00
SBP-300NB	Installation Back box compatible with (SBP-300WM, SBP-300WM1, SBP-300KM, SBP-300PM)	\$	300.00

SBP-300NBW	Installation Back box compatible with (SBP-300WMW, SBP-300WMW1, SBP-300KMW, SBP-300PMW)	\$	300.00
SBP-300NM	PVM camera (TNB-6030) mounting hardware.	\$	65.00
SBP-2CTW1	2'x2' drop ceiling tile (or half of 2'x4' ceiling tile) accessory with 1.5" NPT female thread, includes suspension wire, four turnbuckles, and anchors to suspend from wood or concrete structures, supports up to 50lb, scratch resistant fused epoxy white finish	\$	150.00
SBP-HCFW	1.5" coupler, female thread on both sides, White	\$	15.00
SBP-HCF	1.5" coupler, female thread on both sides, Ivory	\$	15.00
SBP-35PVMB	Telescopic PVM uni-strut mount, 3'-5.5' drop length, VESA compatible 75x75mm, 100x100mm, Up to 25° of tilt and 360° continuous rotation, black	\$	160.00
SBP-35PVMW	Telescopic PVM uni-strut mount, 3'-5.5' drop length, VESA compatible 75x75mm, 100x100mm, Up to 25° of tilt and 360° continuous rotation, white	\$	160.00
SBP-59PVMB	Telescopic PVM uni-strut mount, 5'-9' drop length, VESA compatible 75x75mm, 100x100mm, Up to 25° of tilt and 360° continuous rotation, black	\$	200.00
SBP-59PVMW	Telescopic PVM uni-strut mount, 5'-9' drop length, VESA compatible 75x75mm, 100x100mm, Up to 25° of tilt and 360° continuous rotation, white	\$	200.00
SBP-917PVMB	Telescopic PVM uni-strut mount, 9.5'-17' drop length, VESA compatible 75x75mm, 100x100mm, Up to 25° of tilt and 360° continuous rotation, black	\$	250.00
SBP-917PVMW	Telescopic PVM uni-strut mount, 9.5'-17' drop length, VESA compatible 75x75mm, 100x100mm, Up to 25° of tilt and 360° continuous rotation, white, Freight shipment only	\$	250.00
SBP-917PVMW1	Telescopic PVM uni-strut mount, 9.5'-17' drop length, VESA compatible 75x75mm, 100x100mm, Up to 25° of tilt and 360° continuous rotation, white	\$	300.00
STB-10PVMSC-B	Self-checkout monitor mount, accommodates one SMT-1030PV 10" PVM, easy height adjustment, angle optimized for best view, all installation hardware and brackets included, Powder coated black color, VESA 75 x 75 mm, product weight 3lbs	\$	150.00
STB-10PVMCWA-W	Horizontal gondola monitor mount, accommodates one SMT-1030PV 10" PVM, easy height adjustment, angle optimized for best view, all installation hardware and brackets included, Powder coated white color, VESA 75 x 75 mm, product weight 3lbs	\$	290.00
STB-10PVMGUX-W	Gondola upright monitor mount, accommodates one SMT-1030PV 10" PVM, easy height adjustment, angle optimized for best view, all installation hardware and brackets included, Powder coated white color, VESA 75 x 75 mm, product weight 3lbs	\$	310.00
SPI-35B	Body Temperature Reference (black body), 3", EC 80601-2-59 standard, 30°C to 45°C (86°F to 113°F), Accuracy of ±0.15°C (±0.3°F), 1/4-20" Tripod Mounting, 5% to 95%, non-condensing (RH), 18V, 1A, DC max, (Accessory for TNM-3620TDY)	\$	2,580.00
SPI-50	IR emitter up to 200m (656 feet), 25° IR angle, 850nm wave length, 24VAC, IP67, -40°C ~ +60°C (-40°F ~ 140°F). Compatible with the TNU-6321	\$	2,250.00
SHD-46VDB	Flush Door Jamb Lens Housing for SLA-T4680V lens (not included) and XNB-6001 (not included), black color	\$	150.00
SHD-46VDE	Flush Door Jamb Lens Housing for SLA-T4680V lens (not included) and XNB-6001 (not included), silver color	\$	150.00
SHP-3701H	PTZ Housing Accessory, IP66, IK10, Built-in Heater -58°F XNP-6320/6321, QNP-6230/6250/6320	\$	549.00
WWT-P-VESA	VESA mount + adapter box for WWT-P and WRT-P Micro form factor	\$	130.00
WRR-P-HDDCRDL	HDD cradle for WRR-P 1U and 2U server chassis	\$	80.00
SBP-302F	Ceiling tile support plate for the XND-6081FZ/8081FZ, XND-6081RF/8081RF, XND-9082RF/8082RF and SHD-3000F5	\$	160.00
SPC-100AC	24VAC module for the X Plus outdoor domes, compatible with QTY of 10	\$	325.00
SHB-9000H	TNB-9000 Box Camera Housing, Body/Sun shield : Aluminum, Front & Rear cap : ABS. Wall Mount Arm Included. Operating Temperature: -50°C ~ +60°C (-58°F ~ +140°F) / 10-100% RH (condensing), Weight: 6.2kg(13.67 lb), Color: White, IP66. Input Voltage 110vac, Thermostat controlled Fan and heater - UL 62368-1 Certified	\$	2,925.00
SHB-4301HP	Indoor/Outdoor PoE Housing w/Mounting Bracket Accessory, Heater/Blower, IP66	\$	450.00
SHB-4300H1	Indoor/Outdoor Housing w/Mounting Bracket Accessory, Heater/Blower -58°F~122°F, 24VAC, IP66	\$	349.00
SHB-4200	Indoor/Outdoor Housing w/Mounting Bracket Accessory, 14°F~122°F, IP66	\$	90.00
SHB-4200H	Indoor/Outdoor Housing w/Mounting Bracket Accessory, Heater/Blower, -31°F~122°F, 24VAC, IP66	\$	140.00
SBP-302CMW	Telescopic pendant mount Accessory, requires a mounting plate SBP-302CMAW or SBP-302CMBW (white color)	\$	250.00
SBP-302CMAW	Mounting plate for the telescopic pendant mount SBP-302CMW (white color)	\$	30.00
SBP-302CM-06W	Extension pendant pipe 6" long, fit the SBP-302CMBW (Mounting backbox), SBP-302CMAW (mounting plate), SBP-302CMW (telescopic pendant mount) and the extension pipes SBP-302CMW-06 SBP-302CMW-12 and SBP-302CMW-36; white color	\$	45.00
SBP-302CM-12W	Extension pendant pipe 12" long, fit the SBP-302CMBW (Mounting backbox), SBP-302CMAW (mounting plate), SBP-302CMW (telescopic pendant mount) and the extension pipes SBP-302CMW-06 SBP-302CMW-12 and SBP-302CMW-36; white color	\$	65.00
SBP-302CM-36W	Extension pendant pipe 36" long, fit the SBP-302CMBW (Mounting backbox), SBP-302CMAW (mounting plate), SBP-302CMW (telescopic pendant mount) and the extension pipes SBP-302CMW-06 SBP-302CMW-12 and SBP-302CMW-36; white color	\$	105.00
SBP-302CMBW	Back box made to fit SBP-302CMW telescopic pendant mount and the extension pipes (SBP-302-CMW-06, SBP-302CMW-12 and SBP-302CMW-36), White color	\$	190.00
SBP-302CMSW	Swivel adapter for pendant mount for SBP-302CMW, SBP-302CMW-06, SBP-302CMW-12, SBP-302CMW-36 and it also requires one mounting option either SBP-302CMAW or SBP-302CMBW; White color	\$	120.00
SBP-302CMASW	Telescopic pendant mount accessory with 90 degrees swivel joint, 4.5' to 8' adjustable, includes SBP-302CMAW for ceiling mount, White color	\$	400.00

SMT-3234	32" LED Monitor, 1080p (1920x1080), DVI, HDMI, VGA, CVBS, 16:9 aspect ratio, Built-in Speaker (2W X 2), VESA DPM Compatible (100x100mm)	\$	1,690.00
SMT-4343	43" LED Monitor, 2160p (4K), HDMI, DP, 16:9 aspect ratio, Built-in Speaker (2W X 2), VESA DPM Compatible (100x100mm/400x200mm)	\$	2,060.00
SMT-4343S	43" LED Monitor, 2160p (4K), HDMI, DP, 16:9 aspect ratio, Built-in Speaker (2W X 2), VESA DPM Compatible (100x100mm/400x200mm) + Single monitor desktop stand, compatible with SMT-4343 monitor, black color, 100x100 VESA mountable	\$	2,160.00
SMT-3230PV	32" IP public view monitor, 1080p (1920x1080), HDMI, VGA, Ethernet, 16:9 aspect ratio, Built-in speaker (2x2 W), VESA mountable (100 x 100mm / 200 x 100mm), black casing, face detection display for visual deterrent, 2MP IP camera built-in, 4.6mm fixed lens(73.8"H), 150dB WDR, H.265/H.264/MJPEG, HDMI input, slide show & live video, power supply included (12VDC)	\$	2,140.00
SMT-3211PVM-PIP	32" IP public view monitor, 1080p (1920x1080), HDMI, VGA, Ethernet, 16:9 aspect ratio, Built-in speaker (2x2 W), VESA mountable (100 x 100mm / 200 x 100mm), black casing, face detection display for visual deterrent, PIP, customizable text overlay with pre-configured "recording in progress" OSD, 2MP IP camera built-in, 4.6mm fixed lens(73.8"H), 150dB WDR, H.265/H.264/MJPEG, WiseStream II compression technology, micro SD/SDHC/SDXC, bi-directional audio, hallway view mode Power supply NOT included	\$	3,899.00
SMT-3211PVM	32" IP public view monitor, 1080p (1920x1080), HDMI, VGA, Ethernet, 16:9 aspect ratio, Built-in speaker (2x2 W), VESA mountable (100 x 100mm / 200 x 100mm), black casing, face detection display for visual deterrent, customizable text overlay with pre-configured "recording in progress" OSD, 2MP IP camera built-in, 4.6mm fixed lens(73.8"H), 150dB WDR, H.265/H.264/MJPEG, WiseStream II compression technology, micro SD/SDHC/SDXC, bi-directional audio, hallway view mode Power supply NOT included	\$	3,499.00

SMT-2730PV	27" IP public view monitor,1080p (1920x1080), HDMI, VGA, Ethernet, 16:9 aspect ratio, Built-in speaker (2x2 W), VESA mountable (100 x 100mm / 200 x 100mm), black casing, face detection display for visual deterrent, 2MP IP camera built-in, 4.6mm fixed lens(73.8°H), 150dB WDR, H.265/H.264/MJPEG, HDMI input, slide show & live video, power supply included (12VDC)	\$	1,980.00
SMT-2701PVM	27" IP public view monitor,1080p (1920x1080), HDMI, VGA, Ethernet, 16:9 aspect ratio, Built-in speaker (2x2 W), VESA mountable (100 x 100mm / 200 x 100mm), black casing, face detection display for visual deterrent, customizable text overlay with pre-configured "recording in progress" OSD, 2MP IP camera built-in, 4.6mm fixed lens(73.8°H), 150dB WDR, H.265/H.264/MJPEG, WiseStream II compression technology, micro SD/SDHC/SDXC, bi-directional audio, hallway view mode	\$	2,699.00
SMT-2233	22" LED Monitor, 1080p (1920x1080), 2 BNC loop through, HDMI, 16:9 aspect ratio, Built-in Speaker (2W), Tempered Glass, VESA DPM Compatible	\$	990.00
SMT-1935	19" LED Monitor, 600TVL (1280 x 1024), 2 BNC Loop Through, HDMI, VGA, 4:3 aspect ratio, Built-in Speaker (2X1W), VESA DPM Compatible	\$	690.00
SMT-1030PV	10" IP public view monitor,1080p (1920x1080), HDMI, VGA, Ethernet, 16:9 aspect ratio, Built-in speaker (2x2 W), VESA mountable (75 x 75mm), black casing, face detection display for visual deterrent, 2MP IP camera built-in, 4.6mm fixed lens(73.8°H), 150dB WDR, H.265/H.264/MJPEG, slide show & live video, power supply included (12VDC) or PoE+ powered	\$	1,000.00
SBM-3232	Single monitor desktop stand, compatible with SMT-3233 monitor, black color, 100x100 VESA mountable	\$	100.00
SBM-4343	Single monitor desktop stand, compatible with SMT-4343 monitor, black color, 100x100 VESA mountable	\$	100.00
SPC-7000	Controller, IP system keyboard with touch screen TFT LCD, Interchangeable 3D joystick & jog shuttle for left or right handed users, RS-485, DVR/NVR, Matrix & PTZ control, 1CH video input/output, SSM using USB interface only.	\$	1,300.00
SPC-2010	Controller, 3D joystick, 2 line text LCD display, built-in jog shuttle, up to 255 PTZ/zoom cameras, RS-485, DVR, supports Multi-protocol	\$	898.00
SPC-1010	Controller, PTZ joystick controller, 2 line text LCD display, up to 255 PTZ/zoom cameras, RS-485	\$	499.00
SPC-2000	Controller, USB 3D joystick	\$	798.00
PWR-DR12033	12VDC 33Watt (2.75A) DIN Rail High Temp Power Supply (-40°C to +71°C With -40°C Start-Up)	\$	190.00
PWR-24AC-1-3-ULW	Power supply, 24 VAC, 1 Output, 3 Amps, Nema 4X Enclosure, UL Listed, 110V only	\$	205.00
PWR-24AC-50VA-UL	Power supply, 24VAC 50VA, UL Listed, 110V only	\$	27.00
OP-A2FMD-01	One Camera License for Face Mask Detection Open Platform Application from a2 Technology. To be installed on Compatible X-Series Cameras (XNB-6000,XNO-6080R, XNO-6010R, XNO-6080R, XNO-6120R,XNV-6080, XNV-6080R, XNV-6010, XNV-6020R, XNV-6120R, XNV-6120, XNV-6011,XND-6080, XND-6080R, XND-6080V, XND-6080RV, XND-6010, XND-6020R, XND-6011F)	\$	500.00
DIN-SSDA006/CO	This is an on site engineering service that will be provided by one of Hanwha Techwin B2B security division trained personal for our STEP dealers to help configuring or training on product including cameras, recorders and software. This SKU is for one day, if multiple days are needed please reflect that by increasing the QTY of this SKU.	\$	3,000.00
DIN-SSDA003/CO	This is a professional firmware customization service that will be provided by Hanwha Techwin B2B security R&D Division to provide valuable functions on our network cameras and network recorders. This SKU is for one day engineering cost. For more details please contact us by emailing projectfwservice@hanwha.com	\$	500.00
DIN-SSDA008/CO	This is a remote engineering service that will be provided by a Hanwha Techwin B2B security division trained personnel for our STEP dealers to help configure or train on product including cameras, recorders and software. A reliable phone connection and internet connection (for a connection to the surveillance system via a remote desktop software) is required to be provided by the STEP partner. This SKU is for one day. If multiple days are needed please reflect that by increasing the QTY of the SKU	\$	2,000.00

Wisenet SKY Subscription Services

Category	Item #	Description	MSRP
Wisenet SKY	EN-M10-1	Wisenet SKY VMS M10 Camera Monthly (no cloud storage)	\$ 4.99
Wisenet SKY	EN-PR1-D30-1	Wisenet SKY VMS HD 30 Days 1FPS Cloud Preview Recording Monthly (CMVR only)	\$ 6.65
Wisenet SKY	EN-PR1-D60-1	Wisenet SKY VMS HD 60 Days 1FPS Cloud Preview Recording Monthly (CMVR only)	\$ 7.98
Wisenet SKY	EN-PR1-D90-1	Wisenet SKY VMS HD 90 Days 1FPS Cloud Preview Recording Monthly (CMVR only)	\$ 9.31
Wisenet SKY	EN-PR1-D180-1	Wisenet SKY VMS HD 180 Days 1FPS Cloud Preview Recording Monthly (CMVR only)	\$ 11.97
Wisenet SKY	EN-PR1-D365-1	Wisenet SKY VMS HD 1 Year 1FPS Cloud Preview Recording Monthly (CMVR only)	\$ 14.36
Wisenet SKY	EN-PR1-D730-1	Wisenet SKY VMS HD 2 Years 1FPS Cloud Preview Recording Monthly (CMVR only)	\$ 16.76
Wisenet SKY	EN-SD1-D7-1	Wisenet SKY VMS SD/Analog 7 Days Cloud Recording Monthly	\$ 6.99
Wisenet SKY	EN-SD1-D14-1	Wisenet SKY VMS SD/Analog 14 Days Cloud Recording Monthly	\$ 7.99
Wisenet SKY	EN-SD1-D30-1	Wisenet SKY VMS SD/Analog 30 Days Cloud Recording Monthly	\$ 8.99
Wisenet SKY	EN-SD1-D60-1	Wisenet SKY VMS SD/Analog 60 Days Cloud Recording Monthly	\$ 11.24
Wisenet SKY	EN-SD1-D90-1	Wisenet SKY VMS SD/Analog 90 Days Cloud Recording Monthly	\$ 13.49
Wisenet SKY	EN-SD1-D180-1	Wisenet SKY VMS SD/Analog 180 Days Cloud Recording Monthly	\$ 16.86
Wisenet SKY	EN-SD1-D365-1	Wisenet SKY VMS SD/Analog 1 Year Cloud Recording Monthly	\$ 26.97
Wisenet SKY	EN-SD1-D730-1	Wisenet SKY VMS SD/Analog 2 Year Cloud Recording Monthly	\$ 53.94
Wisenet SKY	EN-SD1-D1095-1	Wisenet SKY VMS SD/Analog 3 Year Cloud Recording Monthly	\$ 80.91
Wisenet SKY	EN-SD1-D1825-1	Wisenet SKY VMS SD/Analog 5 Year Cloud Recording Monthly	\$ 134.85
Wisenet SKY	EN-HD1-D7-1	Wisenet SKY VMS HD1 7 Days Cloud Recording Monthly	\$ 8.99
Wisenet SKY	EN-HD1-D14-1	Wisenet SKY VMS HD1 14 Days Cloud Recording Monthly	\$ 11.99
Wisenet SKY	EN-HD1-D30-1	Wisenet SKY VMS HD1 30 Days Cloud Recording Monthly	\$ 14.99
Wisenet SKY	EN-HD1-D60-1	Wisenet SKY VMS HD1 60 Days Cloud Recording Monthly	\$ 18.74
Wisenet SKY	EN-HD1-D90-1	Wisenet SKY VMS HD1 90 Days Cloud Recording Monthly	\$ 22.49
Wisenet SKY	EN-HD1-D180-1	Wisenet SKY VMS HD1 180 Days Cloud Recording Monthly	\$ 28.11
Wisenet SKY	EN-HD1-D365-1	Wisenet SKY VMS HD1 1 Year Cloud Recording Monthly	\$ 44.97
Wisenet SKY	EN-HD1-D730-1	Wisenet SKY VMS HD1 2 Year Cloud Recording Monthly	\$ 89.94
Wisenet SKY	EN-HD1-D1095-1	Wisenet SKY VMS HD1 3 Year Cloud Recording Monthly	\$ 134.91
Wisenet SKY	EN-HD1-D1825-1	Wisenet SKY VMS HD1 5 Year Cloud Recording Monthly	\$ 224.85
Wisenet SKY	EN-HD2-D7-1	Wisenet SKY VMS HD2 7 Days Cloud Recording Monthly	\$ 12.99
Wisenet SKY	EN-HD2-D14-1	Wisenet SKY VMS HD2 14 Days Cloud Recording Monthly	\$ 16.99
Wisenet SKY	EN-HD2-D30-1	Wisenet SKY VMS HD2 30 Days Cloud Recording Monthly	\$ 20.99
Wisenet SKY	EN-HD2-D60-1	Wisenet SKY VMS HD2 60 Days Cloud Recording Monthly	\$ 26.24
Wisenet SKY	EN-HD2-D90-1	Wisenet SKY VMS HD2 90 Days Cloud Recording Monthly	\$ 31.49
Wisenet SKY	EN-HD2-D180-1	Wisenet SKY VMS HD2 180 Days Cloud Recording Monthly	\$ 39.36
Wisenet SKY	EN-HD2-D365-1	Wisenet SKY VMS HD2 1 Year Cloud Recording Monthly	\$ 62.97
Wisenet SKY	EN-HD2-D730-1	Wisenet SKY VMS HD2 2 Year Cloud Recording Monthly	\$ 125.94
Wisenet SKY	EN-HD2-D1095-1	Wisenet SKY VMS HD2 3 Year Cloud Recording Monthly	\$ 188.91
Wisenet SKY	EN-HD2-D1825-1	Wisenet SKY VMS HD2 5 Year Cloud Recording Monthly	\$ 314.85
Wisenet SKY	EN-HD3-D7-1	Wisenet SKY VMS HD3 7 Days Cloud Recording Monthly	\$ 14.99
Wisenet SKY	EN-HD3-D14-1	Wisenet SKY VMS HD3 14 Days Cloud Recording Monthly	\$ 18.99
Wisenet SKY	EN-HD3-D30-1	Wisenet SKY VMS HD3 30 Days Cloud Recording Monthly	\$ 22.99
Wisenet SKY	EN-HD3-D60-1	Wisenet SKY VMS HD3 60 Days Cloud Recording Monthly	\$ 28.74
Wisenet SKY	EN-HD3-D90-1	Wisenet SKY VMS HD3 90 Days Cloud Recording Monthly	\$ 34.49
Wisenet SKY	EN-HD3-D180-1	Wisenet SKY VMS HD3 180 Days Cloud Recording Monthly	\$ 43.11
Wisenet SKY	EN-HD3-D365-1	Wisenet SKY VMS HD3 1 Year Cloud Recording Monthly	\$ 68.97
Wisenet SKY	EN-HD3-D730-1	Wisenet SKY VMS HD3 2 Year Cloud Recording Monthly	\$ 137.94
Wisenet SKY	EN-HD3-D1095-1	Wisenet SKY VMS HD3 3 Year Cloud Recording Monthly	\$ 206.91
Wisenet SKY	EN-HD3-D1825-1	Wisenet SKY VMS HD3 5 Year Cloud Recording Monthly	\$ 344.85
Wisenet SKY	EN-HD4-D7-1	Wisenet SKY VMS HD4 7 Days Cloud Recording Monthly	\$ 16.99
Wisenet SKY	EN-HD4-D14-1	Wisenet SKY VMS HD4 14 Days Cloud Recording Monthly	\$ 20.99
Wisenet SKY	EN-HD4-D30-1	Wisenet SKY VMS HD4 30 Days Cloud Recording Monthly	\$ 24.99
Wisenet SKY	EN-HD4-D60-1	Wisenet SKY VMS HD4 60 Days Cloud Recording Monthly	\$ 31.24
Wisenet SKY	EN-HD4-D90-1	Wisenet SKY VMS HD4 90 Days Cloud Recording Monthly	\$ 37.49
Wisenet SKY	EN-HD4-D180-1	Wisenet SKY VMS HD4 180 Days Cloud Recording Monthly	\$ 46.86
Wisenet SKY	EN-HD4-D365-1	Wisenet SKY VMS HD4 1 Year Cloud Recording Monthly	\$ 74.97
Wisenet SKY	EN-HD4-D730-1	Wisenet SKY VMS HD4 2 Year Cloud Recording Monthly	\$ 149.94
Wisenet SKY	EN-HD4-D1095-1	Wisenet SKY VMS HD4 3 Year Cloud Recording Monthly	\$ 224.91
Wisenet SKY	EN-HD4-D1825-1	Wisenet SKY VMS HD4 5 Year Cloud Recording Monthly	\$ 374.85
Wisenet SKY	EN-HD5-D7-1	Wisenet SKY VMS HD5 7 Days Cloud Recording Monthly	\$ 18.99
Wisenet SKY	EN-HD5-D14-1	Wisenet SKY VMS HD5 14 Days Cloud Recording Monthly	\$ 23.99
Wisenet SKY	EN-HD5-D30-1	Wisenet SKY VMS HD5 30 Days Cloud Recording Monthly	\$ 28.99
Wisenet SKY	EN-HD5-D60-1	Wisenet SKY VMS HD5 60 Days Cloud Recording Monthly	\$ 36.24
Wisenet SKY	EN-HD5-D90-1	Wisenet SKY VMS HD5 90 Days Cloud Recording Monthly	\$ 43.49
Wisenet SKY	EN-HD5-D180-1	Wisenet SKY VMS HD5 180 Days Cloud Recording Monthly	\$ 54.36
Wisenet SKY	EN-HD5-D365-1	Wisenet SKY VMS HD5 1 Year Cloud Recording Monthly	\$ 86.97
Wisenet SKY	EN-HD5-D730-1	Wisenet SKY VMS HD5 2 Year Cloud Recording Monthly	\$ 173.94
Wisenet SKY	EN-HD5-D1095-1	Wisenet SKY VMS HD5 3 Year Cloud Recording Monthly	\$ 260.91
Wisenet SKY	EN-HD5-D1825-1	Wisenet SKY VMS HD5 5 Year Cloud Recording Monthly	\$ 434.85
Wisenet SKY	EN-HD10-D7-1	Wisenet SKY VMS HD10 7 Days Cloud Recording Monthly	\$ 39.99
Wisenet SKY	EN-HD10-D14-1	Wisenet SKY VMS HD10 14 Days Cloud Recording Monthly	\$ 45.99
Wisenet SKY	EN-HD10-D30-1	Wisenet SKY VMS HD10 30 Days Cloud Recording Monthly	\$ 51.99
Wisenet SKY	EN-HD10-D60-1	Wisenet SKY VMS HD10 60 Days Cloud Recording Monthly	\$ 64.99
Wisenet SKY	EN-HD10-D90-1	Wisenet SKY VMS HD10 90 Days Cloud Recording Monthly	\$ 77.99
Wisenet SKY	EN-HD10-D180-1	Wisenet SKY VMS HD10 180 Days Cloud Recording Monthly	\$ 97.48
Wisenet SKY	EN-HD10-D365-1	Wisenet SKY VMS HD10 1 Year Cloud Recording Monthly	\$ 155.97
Wisenet SKY	EN-HD10-D730-1	Wisenet SKY VMS HD10 2 Year Cloud Recording Monthly	\$ 311.94
Wisenet SKY	EN-HD10-D1095-1	Wisenet SKY VMS HD10 3 Year Cloud Recording Monthly	\$ 467.91
Wisenet SKY	EN-HD10-D1825-1	Wisenet SKY VMS HD10 5 Year Cloud Recording Monthly	\$ 779.85
Wisenet SKY	EN-ANA-001-1	Wisenet SKY Analytic Line Cross Monthly	\$ 3.00
Wisenet SKY	EN-ANA-002-1	Wisenet SKY Analytic Counting Monthly	\$ 4.00
Wisenet SKY	EN-ANA-003-1	Wisenet SKY Analytic Area Intrusion Monthly	\$ 3.00
Wisenet SKY	EN-ANA-004-1	Wisenet SKY Analytic Camera Tamper Detect Monthly	\$ 3.00
Wisenet SKY	EN-ANA-005-1	Wisenet SKY Analytic Loitering Monthly	\$ 3.00
Wisenet SKY	EN-AS100-1	Wisenet SKY Archive Storage 100G Monthly	\$ 12.99
Wisenet SKY	EN-AS1000-1	Wisenet SKY Archive Storage 1000G Monthly	\$ 129.90

Limited Stock Products

Item #	Item Type	Description	MSRP
XNZ-L6320	2MP 32x Zoom Box	Wisenet X powered by Wisenet 5 network zoom box camera, 2MP, Full HD(1080p) @60fps, 32X optical zoom lens (4.44mm ~ 142.6mm) (61.8° ~ 2.19°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, advanced video analytics and sound classification, true D/N, built in SD card slot, HLC, defog detection, 12VDC/PoE	\$ 1,400.00
QNV-8030R	5MP IR Outdoor Dome	Wisenet Q network outdoor vandal dome camera, 5MP @ 30fps, 6.0mm fixed focal lens (49°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 98', defocus detection, hallway View, SD card, video analytics, CVBS, open platform, IP66, IK10, PoE, white color	\$ 470.00
QNV-6032R	2MP IR Outdoor Dome	Wisenet Q network outdoor vandal dome camera, 2MP @ 30fps, 6.0mm fixed focal lens (52°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 98', defocus detection, hallway View, one way audio and SD card, video analytics, CVBS, open platform, IP66, IK10, PoE/12VDC, white color	\$ 395.00
QNO-6032R	2MP IR Bullet	Wisenet Q network outdoor vandal bullet camera, 2MP @ 30fps, 6.0mm fixed focal lens (52°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 98', defocus detection, hallway View, one way audio and SD card, video analytics, CVBS, open platform, IP66, IK10, PoE/12VDC	\$ 379.00
QND-6032R	2MP IR Indoor Dome	Wisenet Q network indoor dome camera, 2MP @ 30fps, 6.0mm fixed focal lens (52°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 65', defocus detection, hallway View, one way audio and SD card, video analytics, CVBS, open platform, PoE/12VDC, white color	\$ 289.00
LVN-6032R	2MP IR Vandal Dome	L series outdoor vandal dome camera, 2MP @ 30fps, 6mm fixed focal lens (51°), Double codec H.264/MJPEG, Wisestream II, 120dB WDR, IR LEDs, hallway view, SD card, IP66, IK10, PoE, White	\$ 265.00
LNO-6032R	2MP IR Bullet	L series outdoor bullet camera, 2MP @ 30fps, 6mm fixed focal lens (51°), Double codec H.264/MJPEG, Wisestream II, 120dB WDR, IR LEDs, hallway view, SD card, IP66, PoE, White	\$ 249.00
LND-6032R	2MP IR Dome	L series indoor dome camera, 2MP @ 30fps, 6mm fixed focal lens (51°), Double codec H.264/MJPEG, Wisestream II, 120dB WDR, IR LEDs, hallway view, SD card, PoE, White	\$ 209.00
HCP-6320HA	AHD PTZ	Wisenet HD+ 2MP, Full HD(1080p) 30fps PTZ camera, Optical zoom lens 32X (4.44~142.6mm), RS485/Up coax (ACP protocol only) PTZ control, true WDR 120dB, true D/N, 24VAC, IP66 IK10.	\$ 1,470.00
HCP-6320A	AHD PTZ	Wisenet HD+ 2MP, Full HD(1080p) 30fps PTZ camera, Optical zoom lens 32X (4.44~142.6mm), true WDR 120dB, RS485/Up coax (ACP protocol only) PTZ control, true D/N, 24VAC.	\$ 1,270.00
SBM-3232	32" desktop stand	Single monitor desktop stand, compatible with SMT-3233 monitor, black color, 100x100 VESA mountable	\$ 100.00
PNV-A9081RLP	AI LPR Camera	4K Low-Moderate Speed LPR Vandal Dome Camera with Wisenet Road AI. Max. 4K resolution, 4.5~10mm(2.2x) M-Varifocal(4K) lens, 0.05Lux@F1.6 (Color), 0Lux (B/W, IR LED on), Day & Night(ICR), WDR(120dB), H.265, H.264, MJPEG codec, WiseStream III, POE+, IP66/67/IP6K9K, IK10+, NEMA4X LPR + MMCR: Make, Model & Color* Recognition on the Edge. 32GB Micro SD storage for up to 10,000 LPR/Vehicle images, Licensed open platform application for multiple regions/countries. (* Color recognition only during day time) CARE IS RECOMMENDED IN SELECTING THE INSTALL LOCATION – See product selector and quick reference guide for details. Use Hanwha pre-sales support consult at lpssupport@hanwha.com	\$ 3,050.00
PNO-A9081RLP	AI LPR Camera	4K Low-Moderate Speed LPR Bullet Camera with Wisenet Road AI. Max. 4K resolution, 4.5~10mm(2.2x) M-Varifocal(4K) lens, 0.05Lux@F1.6 (Color), 0Lux (B/W, IR LED on), Day & Night(ICR), WDR(120dB), H.265, H.264, MJPEG codec, WiseStream III, POE+, IP66/67/IP6K9K, IK10+, NEMA4X LPR + MMCR: Make, Model & Color* Recognition on the Edge. 32GB Micro SD storage for up to 10,000 LPR/Vehicle images, Licensed open platform application for multiple regions/countries. (* Color recognition only during day time) CARE IS RECOMMENDED IN SELECTING THE INSTALL LOCATION – See product selector and quick reference guide for details. Use Hanwha pre-sales support consult at lpssupport@hanwha.com	\$ 2,950.00
HRX-821	8CH AHD, TVI, CVI, CVBS, IP Recorder	Wisenet HD+ Pentabrid DVR AHD (up to 8MP), TVI (up to 8MP), CVI (up to 5MP), CVBS and IP (up to 8MP), 8CH analog + 2CH IP and up to 10CH IP, recording 1080p @ 30fps/ channel (frame rate at higher resolutions will vary), triple codec H.265/H.264/MJPEG, 40Mbps throughput on analog and 28mbps throughput on IP cameras), 4 internal HDD, 8CH audio input/ 1CH audio output, 8 alarm input and 4 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code	\$ 950.00
HRX-821-4TB	8CH AHD, TVI, CVI, CVBS, IP Recorder	Wisenet HD+ Pentabrid DVR AHD (up to 8MP), TVI (up to 8MP), CVI (up to 5MP), CVBS and IP (up to 8MP), 8CH analog + 2CH IP and up to 10CH IP, recording 1080p @ 30fps/ channel (frame rate at higher resolutions will vary), triple codec H.265/H.264/MJPEG, 40Mbps throughput on analog and 28mbps throughput on IP cameras), 4 internal HDD, 8CH audio input/ 1CH audio output, 8 alarm input and 4 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code	\$ 1,670.00
HRX-821-6TB	8CH AHD, TVI, CVI, CVBS, IP Recorder	Wisenet HD+ Pentabrid DVR AHD (up to 8MP), TVI (up to 8MP), CVI (up to 5MP), CVBS and IP (up to 8MP), 8CH analog + 2CH IP and up to 10CH IP, recording 1080p @ 30fps/ channel (frame rate at higher resolutions will vary), triple codec H.265/H.264/MJPEG, 40Mbps throughput on analog and 28mbps throughput on IP cameras), 4 internal HDD, 8CH audio input/ 1CH audio output, 8 alarm input and 4 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code	\$ 2,030.00

HRX-821-8TB	8CH AHD, TVI, CVI, CVBS, IP Recorder	Wisenet HD+ Pentabrid DVR AHD (up to 8MP), TVI (up to 8MP), CVI (up to 5MP), CVBS and IP (up to 8MP), 8CH analog + 2CH IP and up to 10CH IP, recording 1080p @ 30fps/ channel (frame rate at higher resolutions will vary), triple codec H.265/H.264/MJPEG, 40Mbps throughput on analog and 28mbps throughput on IP cameras), 4 internal HDD, 8CH audio input/ 1CH audio output, 8 alarm input and 4 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code	\$ 2,390.00
HRX-821-12TB	8CH AHD, TVI, CVI, CVBS, IP Recorder	Wisenet HD+ Pentabrid DVR AHD (up to 8MP), TVI (up to 8MP), CVI (up to 5MP), CVBS and IP (up to 8MP), 8CH analog + 2CH IP and up to 10CH IP, recording 1080p @ 30fps/ channel (frame rate at higher resolutions will vary), triple codec H.265/H.264/MJPEG, 40Mbps throughput on analog and 28mbps throughput on IP cameras), 4 internal HDD, 8CH audio input/ 1CH audio output, 8 alarm input and 4 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code	\$ 3,110.00
HRX-821-16TB	8CH AHD, TVI, CVI, CVBS, IP Recorder	Wisenet HD+ Pentabrid DVR AHD (up to 8MP), TVI (up to 8MP), CVI (up to 5MP), CVBS and IP (up to 8MP), 8CH analog + 2CH IP and up to 10CH IP, recording 1080p @ 30fps/ channel (frame rate at higher resolutions will vary), triple codec H.265/H.264/MJPEG, 40Mbps throughput on analog and 28mbps throughput on IP cameras), 4 internal HDD, 8CH audio input/ 1CH audio output, 8 alarm input and 4 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code	\$ 3,830.00
HRX-821-24TB	8CH AHD, TVI, CVI, CVBS, IP Recorder	Wisenet HD+ Pentabrid DVR AHD (up to 8MP), TVI (up to 8MP), CVI (up to 5MP), CVBS and IP (up to 8MP), 8CH analog + 2CH IP and up to 10CH IP, recording 1080p @ 30fps/ channel (frame rate at higher resolutions will vary), triple codec H.265/H.264/MJPEG, 40Mbps throughput on analog and 28mbps throughput on IP cameras), 4 internal HDD, 8CH audio input/ 1CH audio output, 8 alarm input and 4 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code	\$ 5,270.00
HRX-820	8CH AHD, TVI, CVI, CVBS, IP Recorder	Wisenet HD+ Pentabrid DVR AHD (up to 8MP), TVI (up to 8MP), CVI (up to 5MP), CVBS and IP (up to 8MP), 8CH analog + 2CH IP and up to 10CH IP, recording 1080p @ 30fps/ channel (frame rate at higher resolutions will vary), triple codec H.265/H.264/MJPEG, 40Mbps throughput on analog and 28mbps throughput on IP cameras), 2 internal HDD, 4CH audio input/ 1CH audio output, 8 alarm input and 4 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code	\$ 450.00
HRX-820-4TB	8CH AHD, TVI, CVI, CVBS, IP Recorder	Wisenet HD+ Pentabrid DVR AHD (up to 8MP), TVI (up to 8MP), CVI (up to 5MP), CVBS and IP (up to 8MP), 8CH analog + 2CH IP and up to 10CH IP, recording 1080p @ 30fps/ channel (frame rate at higher resolutions will vary), triple codec H.265/H.264/MJPEG, 40Mbps throughput on analog and 28mbps throughput on IP cameras), 2 internal HDD, 4CH audio input/ 1CH audio output, 8 alarm input and 4 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code	\$ 1,170.00
HRX-820-6TB	8CH AHD, TVI, CVI, CVBS, IP Recorder	Wisenet HD+ Pentabrid DVR AHD (up to 8MP), TVI (up to 8MP), CVI (up to 5MP), CVBS and IP (up to 8MP), 8CH analog + 2CH IP and up to 10CH IP, recording 1080p @ 30fps/ channel (frame rate at higher resolutions will vary), triple codec H.265/H.264/MJPEG, 40Mbps throughput on analog and 28mbps throughput on IP cameras), 2 internal HDD, 4CH audio input/ 1CH audio output, 8 alarm input and 4 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code	\$ 1,530.00
HRX-820-8TB	8CH AHD, TVI, CVI, CVBS, IP Recorder	Wisenet HD+ Pentabrid DVR AHD (up to 8MP), TVI (up to 8MP), CVI (up to 5MP), CVBS and IP (up to 8MP), 8CH analog + 2CH IP and up to 10CH IP, recording 1080p @ 30fps/ channel (frame rate at higher resolutions will vary), triple codec H.265/H.264/MJPEG, 40Mbps throughput on analog and 28mbps throughput on IP cameras), 2 internal HDD, 4CH audio input/ 1CH audio output, 8 alarm input and 4 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code	\$ 1,890.00
HRX-820-12TB	8CH AHD, TVI, CVI, CVBS, IP Recorder	Wisenet HD+ Pentabrid DVR AHD (up to 8MP), TVI (up to 8MP), CVI (up to 5MP), CVBS and IP (up to 8MP), 8CH analog + 2CH IP and up to 10CH IP, recording 1080p @ 30fps/ channel (frame rate at higher resolutions will vary), triple codec H.265/H.264/MJPEG, 40Mbps throughput on analog and 28mbps throughput on IP cameras), 2 internal HDD, 4CH audio input/ 1CH audio output, 8 alarm input and 4 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code	\$ 2,610.00
HRX-420	4CH AHD, TVI, CVI, CVBS, IP Recorder	Wisenet HD+ Pentabrid DVR AHD (up to 8MP), TVI (up to 8MP), CVI (up to 5MP), CVBS and IP (up to 8MP), 4CH analog + 2CH IP and up to 6CH IP, recording 1080p @ 30fps/ channel (frame rate at higher resolutions will vary), triple codec H.265/H.264/MJPEG, 25Mbps throughput on analog and 17mbps throughput on IP cameras), 1 internal HDD, 1CH audio input/ 1CH audio output, 4 alarm input and 1 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code	\$ 275.00
HRX-420-2TB	4CH AHD, TVI, CVI, CVBS, IP Recorder	Wisenet HD+ Pentabrid DVR AHD (up to 8MP), TVI (up to 8MP), CVI (up to 5MP), CVBS and IP (up to 8MP), 4CH analog + 2CH IP and up to 6CH IP, recording 1080p @ 30fps/ channel (frame rate at higher resolutions will vary), triple codec H.265/H.264/MJPEG, 25Mbps throughput on analog and 17mbps throughput on IP cameras), 1 internal HDD, 1CH audio input/ 1CH audio output, 4 alarm input and 1 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code	\$ 635.00
HRX-420-4TB	4CH AHD, TVI, CVI, CVBS, IP Recorder	Wisenet HD+ Pentabrid DVR AHD (up to 8MP), TVI (up to 8MP), CVI (up to 5MP), CVBS and IP (up to 8MP), 4CH analog + 2CH IP and up to 6CH IP, recording 1080p @ 30fps/ channel (frame rate at higher resolutions will vary), triple codec H.265/H.264/MJPEG, 25Mbps throughput on analog and 17mbps throughput on IP cameras), 1 internal HDD, 1CH audio input/ 1CH audio output, 4 alarm input and 1 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code	\$ 995.00
HRX-420-6TB	4CH AHD, TVI, CVI, CVBS, IP Recorder	Wisenet HD+ Pentabrid DVR AHD (up to 8MP), TVI (up to 8MP), CVI (up to 5MP), CVBS and IP (up to 8MP), 4CH analog + 2CH IP and up to 6CH IP, recording 1080p @ 30fps/ channel (frame rate at higher resolutions will vary), triple codec H.265/H.264/MJPEG, 25Mbps throughput on analog and 17mbps throughput on IP cameras), 1 internal HDD, 1CH audio input/ 1CH audio output, 4 alarm input and 1 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code	\$ 1,355.00
XNP-6320H	2MP 32X PTZ	Wisenet X powered by Wisenet 5 network outdoor PTZ camera, 2MP, Full HD(1080p) @ 60fps, 32X optical zoom lens (4.44mm ~142.6mm) (61.8° ~ 2.19°), Pan: 360° endless. Tilt: -15°~ 195°, triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, Auto Tracking, true D/N, dual SD card, HLC, defog detection, DIS(Gyro),24VAC/PoE+, IP66/IK10, -58°F ~ +131°F W/ 24VAC power supply	\$ 4,350.00
PNM-9085RQZ	5MP X 4 outdoor Dome, PTRZ w/IR	5MP x 4ch multi-directional camera, Motorized PTRZ support, Max. 30fps@5MP(H.265, H.264), 4.13~9.4mm(2.3x) motorized varifocal lens, IR viewable length : 30m, H.265, H.264, MJPEG codec, Multi streaming, Video analytics, WiseStream II ,IP66, IK10, NEMA4X	\$ 3,800.00

PNM-9084RQZ	2MP X 4 outdoor Dome, PTRZ w/IR	2MP x 4ch multi-directional camera, Motorized PTRZ support, Max. 60fps@2MP(H.265, H.264), 3.2~10mm(3.1x) motorized varifocal lens, IR viewable length : 30m, H.265, H.264, MJPEG codec, Multi streaming, Video analytics, WiseStream II, IP66, IK10, NEMA4X	\$ 2,880.00
PNM-9084QZ	2MP X 4 outdoor Dome, PTRZ	Wisenet P series network vandal outdoor Multi-sensor Multi-Directional dome camera, (2MP X 4 sensors) 8MP @ 60fps, motorized vari-focal lens 2x (3.0~6.0mm) (107°~56.3°), PTRZ (Pan/Tilt/Rotate/Zoom) remote adjustment, triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, defocus detection, built in analytics, true D/N, 4x SD card, hallway view, HLC, defog detection, Bi-Directional Audio, Alarm I/O 1/1, HPoE (injector included), IP66/IK10, -40°C ~ +55°C (-40°F ~ +131°F), White	\$ 2,200.00
XNP-6320	2MP 32X PTZ	Wisenet X powered by Wisenet 5 network indoor PTZ camera, 2MP, Full HD(1080p) @ 60fps, 32X optical zoom lens (4.44mm ~142.6mm) (61.8° ~ 2.19°), Pan: 360° endless. Tilt: -15°~ 195°, triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, Auto Tracking, true D/N, dual SD card, HLC, defog detection, DIS(Gyro), 24VAC/PoE+	\$ 4,000.00
SBP-276HM	Cap Adapter	Cap adapter for the PNM-9000VQ and PNM-9030V	\$ 75.00
SBP-300KM	Corner Mount Base	Corner Mount Adapter Accessory, use with SBP-300WM, Ivory	\$ 79.00
QNO-6012R	2MP IR Bullet	Wisenet Q network outdoor vandal bullet camera, 2MP @ 30fps, 2.8mm fixed focal lens (113°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 65', defocus detection, hallway View, one way audio and SD card, video analytics, CVBS, open platform, IP66, IK10, PoE/12VDC	\$ 379.00
QNO-6022R	2MP IR Bullet	Wisenet Q network outdoor vandal bullet camera, 2MP @ 30fps, 4.0mm fixed focal lens (87°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 82', defocus detection, hallway View, one way audio and SD card, video analytics, CVBS, open platform, IP66, IK10, PoE/12VDC	\$ 379.00
QNO-6082R	2MP IR Bullet	Wisenet Q network outdoor vandal bullet camera, 2MP @ 30fps, motorized vari-focal lens 3.1x (3.2 ~ 10.0mm) (109°~33°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 98', defocus detection, hallway View, one way audio and SD card, video analytics, CVBS, open platform, IP66, IK10, PoE/12VDC	\$ 519.00
QNV-6012R	2MP IR Outdoor Dome	Wisenet Q network outdoor vandal dome camera, 2MP @ 30fps, 2.8mm fixed focal lens (113°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 65', defocus detection, hallway View, one way audio and SD card, video analytics, CVBS, open platform, IP66, IK10, PoE/12VDC, white color	\$ 395.00
QNV-6022R	2MP IR Outdoor Dome	Wisenet Q network outdoor vandal dome camera, 2MP @ 30fps, 4.0mm fixed focal lens (87°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 82', defocus detection, hallway View, one way audio and SD card, video analytics, CVBS, open platform, IP66, IK10, PoE/12VDC, white color	\$ 395.00
QNV-6082R	2MP IR Outdoor Dome	Wisenet Q network outdoor vandal dome camera, 2MP @ 30fps, motorized vari-focal lens 3.1x (3.2 ~ 10.0mm) (109°~33°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 98', defocus detection, hallway View, one way audio and SD card, video analytics, CVBS, open platform, IP66, IK10, PoE/12VDC, white color	\$ 535.00
QND-6012R	2MP IR Indoor Dome	Wisenet Q network indoor dome camera, 2MP @ 30fps, 2.8mm fixed focal lens (113°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 65', defocus detection, hallway View, one way audio and SD card, video analytics, CVBS, open platform, PoE/12VDC, white color	\$ 289.00
QND-6022R	2MP IR Indoor Dome	Wisenet Q network indoor dome camera, 2MP @ 30fps, 4.0mm fixed focal lens (87°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 65', defocus detection, hallway View, one way audio and SD card, video analytics, CVBS, open platform, PoE/12VDC, white color	\$ 289.00
QND-6082R	2MP IR Indoor Dome	Wisenet Q network indoor dome camera, 2MP @ 30fps, motorized vari-focal lens 3.1x (3.2 ~ 10.0mm) (109°~33°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 98', defocus detection, hallway View, one way audio and SD card, video analytics, CVBS, open platform, PoE/12VDC, white color	\$ 459.00
XNP-6320RH	2MP IR 32x PTZ	Wisenet X powered by Wisenet 5 network IR PTZ camera, IR range for up to 656', 2MP, Full HD(1080p) @60fps, triple codec H.265/H.264/MJPEG, 32x optical zoom lens (4.44mm ~142.6mm) (61.8° ~ 2.19°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, advanced video analytics and sound classification, auto tracking, true D/N, dual SD card, HLC, defog detection, DIS(Gyro), IP66/IK10, 24VAC/HPoE	\$ 4,500.00
XNP-6321H	2MP 32x PTZ Outdoor	Wisenet X powered by Wisenet 5 network outdoor PTZ camera, 2MP, Full HD(1080p) @ 60fps, 32X optical zoom lens (4.44mm ~142.6mm) (61.8° ~ 2.19°), Pan: 360° endless. Tilt: -15°~ 195°, triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, true D/N, dual SD card, HLC, defog detection, DIS(Gyro), 24VAC/PoE+, IP66/IK10, -58°F ~ +131°F W/ 24VAC power supply	\$ 3,300.00
SBP-301HM4	Cap Adapter	Medium Cap Adapter (Aluminum) Accessory, (SCD-6083R, SCD-5080, SCD-5082, SCD-5083, SCD-5083R, SND-6011R, SNF-7010, SNF-7010V, SNF-7010VM, SND-L6083R, SND-L5083R, HCD-6070R/6080R) Works with Mounts (SBP-300WM1, SBP300WM, SBP-300CM, SBP-300LM), Ivory	\$ 49.00
SPB-VAN4	Tinted Bubble	Accessory, tinted replacement Bubble for SCV-6023R	\$ 69.00
SBP-329HM	Cap Adapter	Large Cap adapter (outdoor) for the Multi-Directional cameras PNM-9080VQ and PNM-9081VQ (Will fit the following accessories: SBP-300WM, SBP-300LM, SBP-300CM) (Will not Fit the SBP-300WM1)	\$ 75.00
SBP-201HM	Cap Adapter	Cap Adapter for the PNM-9020V, HCM-9020VQ Multi-Sensor.	\$ 49.00
SBP-2CTW	2'x2' ceiling tile, 1.5" NPT female thread	2'x2' drop ceiling tile (or half of 2'x4' ceiling tile) accessory with 1.5" NPT female thread, includes suspension wire, four turnbuckles, and anchors to suspend from wood or concrete structures, supports up to 50lb, scratch resistant fused epoxy white finish	\$ 150.00
QNP-6230RH	2MP IR 23x PTZ	Wisenet Q network outdoor IR PTZ camera, IR range for up to 328ft, 2MP, Full HD(1080p) 30fps, triple codec H.265/H.264/MJPEG with WiseStream II, 23x optical zoom (4.44 ~ 102.2mm) (61.8° ~ 3.08°), 120dB WDR, HLC, true D/N, 24VAC / HPoE, IP66, IK10, Built-in -58°F (-50°C) Heater (24VAC only) HPoE injector not included	\$ 2,000.00
QNP-6230H	2MP 23x PTZ	Wisenet Q network outdoor PTZ camera, 2MP, Full HD(1080p) 30fps, H.265/H.264/MJPEG, Optical Zoom Lens 23x (4.44-102.1mm), 120dB WDR, true D/N, 500°/sec Pan, SD/SDHC/SDXC, 24VAC/PoE+, Analytics, IP66, IK10, Heater on -58°F 24VAC	\$ 1,700.00
QNP-6230	2MP 23x PTZ	Wisenet Q network indoor PTZ camera, 2MP, Full HD(1080p) 30fps, H.265/H.264/MJPEG, Optical Zoom Lens 23x (4.44-102.1mm), 120dB WDR, true D/N, 500°/sec Pan, SD/SDHC/SDXC, 24VAC/PoE+	\$ 1,500.00
SBP-300PM	Pole Mount Base	Pole Mount Adapter Accessory, use with SBP-300WM, Ivory	\$ 79.00

[illegible]

HRX-1620-10TB	16CH AHD, TVI, CVI, CVBS, IP Recorder	Wisenet HD+ Pentabrid DVR AHD (up to 8MP), TVI (up to 8MP), CVI (up to 5MP), CVBS and IP (up to 8MP), 16CH analog + 2CH IP and up to 18CH IP, recording 1080p @ 30fps/ channel (frame rate at higher resolutions will vary), triple codec H.265/H.264/MJPEG, 70Mbps throughput on analog and 51mbps throughput on IP cameras), 2 internal HDD, 4CH audio input/ 1CH audio output, 16 alarm input and 4 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code	\$ 2,550.00
HRX-1620-12TB	16CH AHD, TVI, CVI, CVBS, IP Recorder	Wisenet HD+ Pentabrid DVR AHD (up to 8MP), TVI (up to 8MP), CVI (up to 5MP), CVBS and IP (up to 8MP), 16CH analog + 2CH IP and up to 18CH IP, recording 1080p @ 30fps/ channel (frame rate at higher resolutions will vary), triple codec H.265/H.264/MJPEG, 70Mbps throughput on analog and 51mbps throughput on IP cameras), 2 internal HDD, 4CH audio input/ 1CH audio output, 16 alarm input and 4 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code	\$ 2,910.00
SLA-2M2400D	PNM-7000VD Lens module	1/2.8" 2MP CMOS with a 2.4mm fixed focal lens, FoV: H: 135.4°, V: 71.2°, for the PNM-7000VD	\$ 85.00
SLA-2M2800D	PNM-7000VD Lens module	1/2.8" 2MP CMOS with a 2.8mm fixed focal lens, FoV: H: 107.4°, V: 62.2°, for the PNM-7000VD	\$ 85.00
SLA-2M3600D	PNM-7000VD Lens module	1/2.8" 2MP CMOS with a 3.6mm fixed focal lens, FoV: H: 94.8°, V: 49.3°, for the PNM-7000VD	\$ 85.00
SLA-2M6000D	PNM-7000VD Lens module	1/2.8" 2MP CMOS with a 6.0mm fixed focal lens, FoV: H: 50.4°, V: 28.8°, for the PNM-7000VD	\$ 85.00
SLA-C-E85	Canon EF 85mm f/1.2L II USM	Canon 85mm f1.2L, Auto-Iris (EF 85mm f/1.2L II USM) : Horizontal field of view: 8K 19.2° , CarePak 4 Years Warranty	\$ 6,235.00